

MSDS

Material Safety Data Sheet



1403 Herkimer Street
Joliet, IL 60432-1059
(877) EKI-CHEM
(815) 723-4000
www.eki-chem.com

24 HOUR EMERGENCY
TELEPHONE NUMBER
CALL CHEMTREC
1-800-424-9300

Giemsa Stain Solution, Stock

SECTION 1 PRODUCT IDENTIFICATION

NAME: Giemsa Stain Solution, Stock
EKI ORDER NUMBER: 4639
SYNONYMS: N/I
CAS NO: Does not apply
FORMULA: Does not apply
REVISION DATE: 20 April 2004

****LABEL HAZARD STATEMENT AND PRECAUTIONS****

DANGER! POISON! MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. HARMFUL IF INHALED. CAUSES IRRITATION. FLAMMABLE LIQUID AND VAPOR. Avoid contact with skin, eyes and clothing. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

SECTION 2 HAZARDOUS INGREDIENTS / EXPOSURE LIMITS

| INGREDIENT/CAS NO ----- | OSHA PEL ----- | ACGIH TLV ----- |
|----------------------------|-------------------|---------------------------------------|
| Methyl Alcohol/67-56-1 | 200 ppm TWA | 200 ppm TWA Skin 250 ppm STEL Skin |
| Glycerin/56-81-5 | N/E | N/E |

Methyl Alcohol, ~60%, is subject to the reporting requirements of SARA 313 and 40CFR372.

SECTION 3 PHYSICAL / CHEMICAL CHARACTERISTICS

| | |
|-------------------------------|------------------------|
| SOLUBILITY IN WATER: Miscible | BOILING POINT (C): N/E |
| VAPOR PRESSURE (mm Hg): N/E | VAPOR DENSITY: N/E |
| SPECIFIC GRAVITY: N/E | MELTING POINT (C): N/E |

EVAPORATION RATE: N/E
APPEARANCE AND ODOR: Dark blue liquid. Odor of methyl alcohol.

SECTION 4 FIRE / EXPLOSION HAZARD DATA

FLASH POINT (C): 11 (Closed Cup)
AUTOIGNITION TEMPERATURE (C): 463
FLAMMABLE LIMITS (%) UEL: 36 LEL: 6
EXTINGUISHING MEDIA: Use "alcohol" foam, dry chemical or CO₂.
SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive-pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Blanket fire and exposed containers with water spray. Flush vapor and spills with water spray. Vapors can flow to a distant ignition source and flash back.

SECTION 5 REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Heat, flames, ignition sources.

MATERIALS TO AVOID: Strong oxidizers, Aluminum.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, Formaldehyde.

HAZARDOUS POLYMERIZATION: Does not occur.

SECTION 6 HEALTH HAZARD DATA

ROUTES OF ENTRY AND EFFECTS OF OVEREXPOSURE

INHALATION: May cause irritation. Neurotoxic. May cause headache, nausea, vomiting, blurred vision, blindness, coma, death.

SKIN CONTACT: May cause irritation. Causes drying.

EYE CONTACT: Causes irritation.

SKIN ABSORPTION: See under INHALATION.

INGESTION: See under INHALATION.

CHRONIC: Visual impairment, liver enlargement, skin irritation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Skin or eye disorders, liver or kidney function.

CARCINOGENICITY: None.

FIRST AID PROCEDURES

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN CONTACT: Immediately flush with plenty of water for at least 15 minutes, while removing contaminated clothing and shoes. Get medical attention for persistent irritation.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

INGESTION: If conscious, immediately induce vomiting as directed by medical personnel.

SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED: Ventilate area and eliminate sources of ignition. Absorb spill with inert material and containerize for disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with all applicable federal, state, and local environmental regulations.

STORAGE: Store tightly closed in an approved Flammable Liquid storage area.

SECTION 8 CONTROL MEASURES

VENTILATION: Local preferred.

RESPIRATORY PROTECTION: Full facepiece respirator or self-contained breathing apparatus.

EYE PROTECTION: Chemical safety goggles.

SKIN PROTECTION: Rubber or neoprene gloves, lab coat and impervious apron.

| |
|--|
| <p>E K INDUSTRIES, INC. MAKES NO REPRESENTATION AS TO THE COMPREHENSIVENESS OR ACCURACY OF THIS INFORMATION. INDIVIDUALS RECEIVING THIS INFORMATION MUST EXERCISE THEIR INDEPENDENT JUDGMENT IN DETERMINING ITS APPROPRIATENESS FOR A PARTICULAR PURPOSE. ACCORDINGLY, E K INDUSTRIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES OF ANY KIND OR NATURE RESULTING FROM THE USE OF ANY SUCH INFORMATION. NO REPRESENTATIONS OR WARRANTIES OF ANY KIND OR NATURE, INCLUDING BUT NOT LIMITED TO: EXPRESS WARRANTIES, IMPLIED WARRANTIES OF MERCHANTABILITY, OR WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE, ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS.</p> |
|--|