



# Material Safety Data Sheet

Issuing Date 28-Apr-2011

Revision Date 20-Aug-2012

Revision Number 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** W5G-5BX-FL THERMOPLASTIC (884111)

**Product Code(s)** 884125

**Recommended Use** Traffic paint

**Product Technology** Thermo

### Supplier Address

Ennis-Flint  
5910 North Central Expressway  
Suite 1050  
Dallas TX 75206  
T: 800.331.8118  
800.331.8118 (For Technical Inquiries)

**Chemical Emergency Phone Number** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### **WARNING!**

### **Emergency Overview**

Product dust may be irritating to eyes, skin and respiratory system

May cause respiratory impairment and lung damage

May cause sensitization by skin contact

Cancer hazard

WARNING! This product contains a chemical known in the State of California to cause cancer.

**Appearance** White

**Physical State** Solid.

**Odor** Odorless

### Potential Health Effects

**Principle Routes of Exposure** Skin contact. Inhalation.

### **Acute Toxicity**

#### **Eyes**

May cause irritation. The molten product can cause serious burns.

#### **Skin**

May cause irritation. May cause sensitization by skin contact. The molten product can cause serious burns.

#### **Inhalation**

Inhalation of dust in high concentration may cause irritation of respiratory system. Excessive inhalation of vapors in molten state can cause nose and throat irritation, may cause nervous system depression characterized by headache, dizziness, nausea, staggering gait, confusion and unconsciousness. In molten state, the material does not give off fumes that are toxic or injurious to persons or property.

#### **Ingestion**

Ingestion may cause irritation to mucous membranes.

### **Chronic Effects**

Inhalation overexposure to free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

<b>Aggravated Medical Conditions</b>	Respiratory disorders. Lungs.
<b>Interactions with Other Chemicals</b>	Use of alcoholic beverages may enhance toxic effects.
<b>Environmental Hazard</b>	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Limestone	1317-65-3	30-60
Glass, oxide	65997-17-3	30-60
Modified Rosin Ester	Proprietary	10-30
Titanium dioxide	13463-67-7	7-13
Maleic Modified Rosin Ester	Proprietary	7-13
Paraffin	8002-74-2	5-10
Calcium carbonate	471-34-1	3-7
Quartz	14808-60-7	1-5
EVA polymer	RTH0039-UNK	1-5
Polyamide resin	Proprietary	1-5
Phthalate plasticizer	Proprietary	1-5
Silicon dioxide	7631-86-9	1-5
Aluminum hydroxide	21645-51-2	1-5

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician. Contact with molten materials, requires immediate medical assistance.
<b>Skin Contact</b>	Wash off with warm water and soap. In the case of skin irritation or allergic reactions see a physician. In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin. Removal of solidified molten material from skin requires medical assistance. If burned by contact with molten material, remove patient from heat source. Remove smoldering clothing, including shoes, boots and jewelry. Cool the burn with water or saline until the skin returns to normal temperature. Cover patient with dry clean sheet. Do not attempt to remove the molten thermoplastic from the skin. Removal could result in severe tissue damage. Do not use ice. Conduct primary survey. If indicated transport patient to emergency treatment facility.
<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician.
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Consult a physician.
<b>Notes to Physician</b>	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Not flammable.
<b>Flash Point</b>	> 500 °F
<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Explosion Data

<b>Sensitivity to Mechanical Impact</b>	None.			
<b>Sensitivity to Static Discharge</b>	None			
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
<b>NFPA</b>	<b>Health Hazard</b> 1	<b>Flammability</b> 1	<b>Instability</b> 0	<b>Physical and Chemical Hazards -</b>
<b>HMIS</b>	<b>Health Hazard</b> 1*	<b>Flammability</b> 1	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Use personal protective equipment. Ensure adequate ventilation. Avoid dust formation.
<b>Environmental Precautions</b>	Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Cleaning Up</b>	Use personal protective equipment. Avoid dust formation. Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Take up mechanically and collect in suitable container for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	<p>Ensure adequate ventilation. Avoid breathing dust. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid dust formation. Fine dust dispersed in air may ignite.</p> <p>Do not heat over 500°F in a closed container. This product when heated to above 500°F can lead to flashing. Appropriate protective equipment must be worn when mixing and applying this product.</p> <p>The thermoplastic bag can be hazardous when empty, because it can retain product residue. Therefore do not reuse container for food, clothing, or products for human or animal consumption or where skin contact may occur. Always obey hazard warnings and handle containers as if they were full.</p> <p>The meltable bag is compatible with the thermoplastic allowing them to melt and become part of the hot melt mixture at application temperature.</p>
<b>Storage</b>	Keep container tightly closed. Keep in properly labeled containers. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Glass, oxide 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable fraction	-	
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Paraffin 8002-74-2	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Calcium carbonate 471-34-1	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	30/(%SiO <sub>2</sub> +2) mg/m <sup>3</sup> TWA, Total Dust; 250/(%SiO <sub>2</sub> +5) mppcf TWA, respirable fraction; 10/(%SiO <sub>2</sub> +2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/( % SiO <sub>2</sub> )) mg/m <sup>3</sup> )	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems

### Personal Protective Equipment

#### Eye/Face Protection

Wear protective eyewear (safety glasses).

#### Skin and Body Protection

Wear protective gloves/clothing.

#### Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	White.	<b>Odor</b>	Odorless.
<b>Odor Threshold</b>	Not applicable	<b>Physical State</b>	Solid
<b>pH</b>	Not applicable		
<b>Flash Point</b>	> 500 °F	<b>Autoignition Temperature</b>	Not applicable
<b>Decomposition Temperature</b>	Not applicable	<b>Boiling Point/Boiling Range</b>	Not applicable
<b>Melting Point/Range</b>	Not applicable		
		<b>Flammability Limits in Air</b>	Not applicable
<b>Solubility</b>	Not applicable	<b>Evaporation Rate</b>	Not applicable
<b>Vapor Pressure</b>	Not applicable	<b>Vapor Density</b>	Not applicable
<b>VOC (g/l)</b>	0		

**10. STABILITY AND REACTIVITY**

<b>Stability</b>	Stable under recommended storage conditions.
<b>Incompatible Products</b>	None known based on information supplied.
<b>Conditions to Avoid</b>	Dust formation.
<b>Hazardous Decomposition Products</b>	Carbon oxides. Nitrogen oxides (NOx). Maleic acid.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Product Information

No acute toxicity information is available for this product.

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium dioxide	> 10000 mg/kg ( Rat )		> 6820 mg/m <sup>3</sup>
Paraffin	> 3750 mg/kg ( Rat )	> 3600 mg/kg ( Rabbit )	-
Calcium carbonate	= 6450 mg/kg ( Rat )		
Quartz	500 mg/kg ( Rat )		
Phthalate plasticizer	> 9750 mg/kg ( Rat )		>4.4 mg/L ( Rat ) 4 h
Silicon dioxide	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	>2.2 mg/L ( Rat ) 4 h
Petroleum distillates, hydrotreated heavy paraffinic	> 2000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 2.18 mg/L ( Rat ) 4 h
Aluminum hydroxide	> 5000 mg/kg ( Rat )	-	-
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	> 5000 mg/kg ( Rat )		> 12.6 mg/L ( Rat ) 4 h
Water	90 mL/kg ( Rat )	-	-
N,N'-Ethylenebis(stearamide)	> 5000 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	
Maleic anhydride	= 235 mg/kg ( Rat )	= 610 mg/kg ( Rat ) = 2620 mg/kg ( Rabbit )	

### Chronic Toxicity

#### Chronic Toxicity

Inhalation overexposure to free crystalline silica may cause delayed lung injury including silicosis, a disabling and potentially fatal lung disease. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Glass, oxide		Group 3		
Titanium dioxide		Group 2B		X
Quartz	A2	Group 1	Known	X
Silicon dioxide		Group 3		

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A4 - Not Classifiable as a Human Carcinogen

#### IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

#### NTP: (National Toxicity Program)

Known - Known Carcinogen

#### OSHA: (Occupational Safety & Health Administration)

X - Present

#### Target Organ Effects

Respiratory system. Lungs.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Phthalate plasticizer	EC50 96 h: > 1.8 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h: > 0.14 mg/L flow-through (Lepomis macrochirus) LC50 96 h: > 0.14 mg/L static (Pimephales promelas) LC50 96 h: > 0.17 mg/L static (Lepomis macrochirus) LC50 96 h: > 0.19 mg/L flow-through (Pimephales promelas) LC50 96 h: > 100 mg/L semi-static (Brachydanio rerio) LC50 96 h: > 500 mg/L static (Leuciscus idus)		EC50 48 h: > 0.06 mg/L Static (Daphnia magna) EC50 48 h: > 500 mg/L (Daphnia magna)
Silicon dioxide	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

## 13. DISPOSAL CONSIDERATIONS

### Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

### Contaminated Packaging

Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

### DOT

#### Proper shipping name

Not regulated (Product as shipped)  
Elevated temperature liquid, n.o.s. (Product in use)

#### Description

ELEVATED TEMPERATURE MATERIAL, LIQUID, N.O.S.(COMPOUND PAVEMENT MARKING), 9, UN 3257, III. (Product in use)

### TDG

Not regulated

### MEX

Not regulated

### ICAO

Not regulated

### IATA

Not regulated

### IMDG/IMO

Not regulated

## 15. REGULATORY INFORMATION

**International Inventories****TSCA**

All components are listed on the TSCA Inventory.

**DSL**

All components are listed either on the DSL or NDSL.

**Legend****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Phthalate plasticizer		X		

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	X	X	X		X
Titanium dioxide	X	X	X	-	X
Paraffin	X	X	X	-	X
Quartz	X	X	X	-	X
Diisononyl phthalate			X		
Silica		X	X		

**International Regulations**

Chemical Name	Carcinogen Status	Exposure Limits
Limestone		Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>



Paraffin		Mexico: TWA= 2 mg/m <sup>3</sup> Mexico: STEL= 6 mg/m <sup>3</sup>
Titanium dioxide		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Quartz		Mexico: TWA= 0.1 mg/m <sup>3</sup>

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

D2A Very toxic materials

D2B Toxic materials

**16. OTHER INFORMATION**

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 28-Apr-2011  
**Revision Date** 20-Aug-2012  
**Revision Note** (M)SDS sections updated: 1, 2, 4, 7, 9

**General Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

**End of Safety Data Sheet**