

Material Safety Data Sheet

TRAFFIC BAFETT BELUTIONS		
Issuing Date 18-Jan-2012	Revision Date	Revision Number 0
	1. PRODUCT AND COMPANY IDENTIFICATION	
Product Name	MN COUNTY PREMIX WATERBORNE PAINT	
Recommended Use	Traffic paint pre-mix.	
Product Technology	W/B	
Supplier Address Ennis Paint Inc. 5910 North Central Expressway Suite 1050 Dallas TX 75206 T: 800.331.8118 800.331.8118 (For Technical Inquirie	95)	
Chemical Emergency Phone Num	ber Chemtrec 1-800-424-9300	
	2. HAZARDS IDENTIFICATION	
DANGER!	Emergency Overview	
	Emergency Overview	
	y be harmful if swallowed, inhaled, or absorbed through skin May cause central nervous system depression May cause skin, eye, and respiratory tract irritation May adversely affect liver and kidney. Cancer hazard roduct contains a chemical known in the State of California t	
Appearance Yellow	Physical State Emulsion.	Odor Slight, Ammonia
Potential Health Effects Principle Routes of Exposure	Eye contact. Skin contact. Inhalation.	
Acute Toxicity Eyes Skin Inhalation Ingestion	May cause irritation. May cause irritation. May be harmful if absorbed through skin. May be harmful if inhaled. May cause central nervous system headache, dizziness, vomiting, and incoordination. Sanding ar if inhaled. May be harmful if swallowed. May cause blindness if swallowe as listed under "Inhalation".	depression with nausea, nd grinding dust may be harmful
Chronic Effects	This product contains crystalline silica (quartz) in a non-respirat crystalline silica is unlikely to occur from exposure to this produ- been classified by the International Agency for Research on C carcinogen (Group 1). This product contains titanium dioxide in Inhalation of titanium dioxide is unlikely to occur from exposure dioxide has been classified by the International Agency for Res- possibly carcinogenic to humans (Group 2B) by inhalation. Inh absorption of methanol can cause blindness. May cause adver-	uct. Crystalline silica (quartz) has ancer (IARC) as a known human n a non-respirable form. e to this product. Titanium search on Cancer (IARC) as nalation, ingestion, or skin

WPS-ENN-982352 - MN COUNTY PREMIX WATERBORNE PAINT

Aggravated Medical Conditions	Respiratory disorders. Lungs. Pre-existing eye disorders. Skin disorders. Liver disorders. Kidney disorders. Central nervous system.	
Interactions with Other Chemicals	Use of alcoholic beverages may enhance toxic effects.	
Environmental Hazard	See Section 12 for additional Ecological Information.	

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Methyl alcohol	67-56-1	1-5
Propylene glycol	57-55-6	1-5
Titanium dioxide	13463-67-7	1-5
Quartz	14808-60-7	0.1-1

4. FIRST AID MEASURES				
F = O = 1 = 1	Disco		an also condendes acceltos d	
Eye Contact		Rinse immediately with plenty of water, also under the eyelids, for at lea symptoms persist, call a physician.		or at least 15 minutes. It
Skin Contact		Wash off immediately with plenty of water. Remove and wash contaminated clothing before re use. If symptoms persist, call a physician.		
Inhalation	Move to fr	esh air. If breathing is diffi	cult, give oxygen. If sympton	ns persist, call a physician.
Ingestion		Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. If symptoms persist, call a physician.		iconscious person. Drink
Notes to Physician	Treat symptomatically.			
5. FIRE-FIGHTING MEASURES				
Flammable Properties	Not flamm	able.		
Flash Point	> 201°F / 93.8°C			
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		stances and the surrounding	
Explosion DataSensitivity to Mechanical ImpactNoneSensitivity to Static DischargeNone				
		fire, wear self-contained br or equivalent) and full pro	eathing apparatus pressure tective gear.	-demand, MSHA/NIOSH
NFPA Health H	lazard 1	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS Health H	azard 2*	Flammability 1	Physical Hazard 0	Personal Protection X

6. ACCIDENTAL RELEASE MEASURESPersonal PrecautionsUse personal protective equipment. Ensure adequate ventilation. Avoid contact with skin, eyes
and clothing.Environmental PrecautionsPrevent product from entering drains. Do not flush into surface water or sanitary sewer system.Methods for ContainmentPrevent further leakage or spillage if safe to do so.Methods for Cleaning UpUse personal protective equipment. Dike far ahead of liquid spill for later disposal. Soak up
with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Handling

Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product.

Storage

Keep container tightly closed. Keep in properly labeled containers. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Quartz	TWA: 0.025 mg/m ³ respirable fraction	30/(%SiO2+2) mg/m ³ TWA, Total	IDLH: 50 mg/m ³ respirable dust
14808-60-7		Dust;250/%SiO2+5) mppcf TWA,	TWA: 0.05 mg/m ³ respirable dust
		respirable fraction; 10/(%SiO2+2) mg/m ³	
		TWA, respirable	
		TWA: 0.1 mg/m ³ (vacated)	
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total dust	-
Methyl alcohol	STEL = 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260 mg/m ³	STEL: 325 mg/m ³
		(vacated) STEL: 250 ppm	STEL: 250 ppm
		(vacated) STEL: 325 mg/m ³	
		(vacated) S*	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Engineering Measures	Showers Eyewash stations Ventilation systems
Personal Protective Equipment Eye/Face Protection Skin and Body Protection Respiratory Protection	Wear protective eyewear (safety glasses). Protective gloves. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Threshold pH	Yellow. Not applicable Not applicable	Odor Physical State	Slight, Ammonia. Emulsion
Flash Point Decomposition Temperature Melting Point/Range	> 201°F / 93.8°C Not applicable Not applicable	Autoignition Temperature Boiling Point/Boiling Range	Not applicable Not applicable
Flammability Limits in Air Specific Gravity Evaporation Rate Vapor Density	Not applicable 1.55 - 1.75 Not applicable Not applicable	Solubility Vapor Pressure VOC (g/l)	Insoluble Not applicable <100
	10. STABILITY	AND REACTIVITY	

Stability	Stable under recommended storage conditions.
Incompatible Products	None known based on information supplied.
Conditions to Avoid	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides. Nitrogen oxides (NOx).
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

No acute toxicity information is available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 mg/kg (Rat)		
Titanium dioxide	> 10000 mg/kg (Rat)		> 6820 mg/m ³
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	83.2 mg/L (Rat) 4 h
			64000 ppm (Rat)4 h
Propylene glycol	20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-

Chronic Toxicity

Chronic Toxicity

This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. Inhalation, ingestion, or skin absorption of methanol can cause blindness. May cause adverse liver and kidney effects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		Х
Quartz	A2	Group 1	Known	Х

ACGIH: (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen IARC: (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program) Known - Known Carcinogen OSHA: (Occupational Safety & Health Administration) X - Present

Target Organ Effects

Liver. Kidney. Central nervous system (CNS). Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product Information LC50/96h/Fathead minnows = >750 mg/L

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol	-	LC50 96 h: 13500 - 17600	EC50 = 39000 mg/L 25 min	-
		mg/L flow-through (Lepomis	EC50 = 40000 mg/L 15 min	
		macrochirus)	EC50 = 43000 mg/L 5 min	
		LC50 96 h: 18 - 20 mL/L		
		static (Oncorhynchus mykiss)		
		LC50 96 h: 19500 - 20700		
		mg/L flow-through		
		(Oncorhynchus mykiss)		
		LC50 96 h: = 28200 mg/L		
		flow-through (Pimephales		
		promelas)		
		LC50 96 h: > 100 mg/L static		
		(Pimephales promelas)		
Propylene glycol	EC50 96 h: = 19000 mg/L	LC50 96 h: 41 - 47 mL/L	EC50 = 710 mg/L 30 min	EC50 48 h: > 1000 mg/L
	(Pseudokirchneriella	static (Oncorhynchus mykiss)		Static (Daphnia magna)
	subcapitata)	LC50 96 h: = 51400 mg/L		EC50 24 h: > 10000 mg/L
		static (Pimephales promelas)		(Daphnia magna)
		LC50 96 h: = 51600 mg/L		
		static (Oncorhynchus mykiss)		
		LC50 96 h: = 710 mg/L		
		(Pimephales promelas)		

Chemical Name	Log Pow
Methyl alcohol	-0.77

13. DISPOSAL CONSIDERATIONS

Waste Disposal MethodsThis material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR
261). This material could become a hazardous waste if it is mixed with or otherwise comes in
contact with a hazardous waste, if chemical additions are made to this material, or if the
material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the
altered material is a hazardous waste. Consult the appropriate state, regional, or local
regulations for additional requirements.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol - 67-56-1		Included in waste stream:		U154
-		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Not applicable

Chemical Name	California Hazardous Waste
Methyl alcohol	Toxic
	Ignitable

14. TRANSPORT INFORMATION

DOT	Not regulated
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
ΙΑΤΑ	Not regulated
IMDG/IMO	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	All components are listed on the TSCA Inventory.
DSL	All components are listed either on the DSL or NDSL.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Titanium dioxide	13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Quartz	Х	Х	Х	-	Х
Titanium dioxide	Х	Х	Х	-	Х
Methyl alcohol	Х	Х	Х	Х	Х
Propylene glycol	Х	-	Х	-	Х

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Quartz		Mexico: TWA= 0.1 mg/m ³
Titanium dioxide		Mexico: TWA= 10 mg/m ³
		Mexico: STEL= 20 mg/m ³
Methyl alcohol		Mexico: TWA= 200 ppm
		Mexico: TWA= 260 mg/m ³
		Mexico: STEL= 250 ppm
		Mexico: STEL= 310 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D1B Toxic materials D2A Very toxic materials D2B Toxic materials



Canadian National Pollutant Release Inventory (NPRI)

Chemical Name	NPRI
Methyl alcohol	Х

Legend X - Listed

16. OTHER INFORMATION

Prepared By Issuing Date Revision Date	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501 18-Jan-2012
Revision Note	Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

End of Safety Data Sheet