



Material Safety Data Sheet

Issuing Date 30-Jun-2011

Revision Date

Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name VocYellow Stock Solvent Paint

Product Code(s) 985152

UN-Number UN1263

Recommended Use Traffic paint

Product Technology S/B

Supplier Address

Ennis Paint Inc.
5910 North Central Expressway
Suite 1050
Dallas TX 75206
T: 800.331.8118
800.331.8118 (For Technical Inquiries)

Chemical Emergency Phone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Highly flammable liquid and vapor

Irritating to eyes and skin

Risk of serious damage to the lungs (by aspiration)

Causes central nervous system depression.

Cancer hazard

May adversely affect nervous system, liver, kidney and heart.

Contains a known or suspected reproductive toxin

WARNING! This product contains a chemical known in the State of California to cause cancer and birth defects or other reproductive harm.

Appearance Yellow

Physical State Liquid.

Odor No information available

Potential Health Effects

Principle Routes of Exposure

Inhalation. Skin contact. Eye contact.

Acute Toxicity

Eyes

Moderately irritating to the eyes

Skin

Irritating to skin. Repeated exposure may cause skin dryness or cracking.

Inhalation

Inhalation in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled.

Ingestion

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. May cause additional affects as listed under "Inhalation".

Chronic Effects	Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. May cause adverse liver and kidney effects. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).
Aggravated Medical Conditions	Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects. Liver disorders, kidney disorders, central nervous system, cardiovascular, blood disorders and respiratory disorders. Skin disorders. Pre-existing eye disorders.
Interactions with Other Chemicals	Use of alcoholic beverages may enhance toxic effects.
Environmental Hazard	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Toluene	108-88-3	40-70
Acetone	67-64-1	10-30
Naphtha, petroleum, hydrotreated light	64742-49-0	10-30
Titanium dioxide	13463-67-7	10-30
Methyl alcohol	67-56-1	3-7
Hexane	110-54-3	1-5
Xylenes (o-, m-, p- isomers)	1330-20-7	1-5
Quartz	14808-60-7	0.1-1
Ethyl benzene	100-41-4	0.1-1
Hexanoic acid, 2-ethyl-, lead(2+) salt	301-08-6	0.1-1
Benzene	71-43-2	<0.1

4. FIRST AID MEASURES

General Advice	If swallowed, get medical help or contact a Poison Control Center right away. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately.
Skin Contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. Consult a physician.
Inhalation	Move victim to fresh air. If breathing has stopped, contact emergency medical services immediately. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Notes to Physician	Aspiration hazard. Treat symptomatically.
Protection of First-aiders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Highly flammable liquid and vapor
-----------------------------	-----------------------------------

Flash Point	-14°F / -10°C			
Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or regular foam. Use water spray or fog; do not use straight streams.			
Unsuitable Extinguishing Media	CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.			
Explosion Data				
Sensitivity to Mechanical Impact	None			
Sensitivity to Static Discharge	Yes.			
Specific Hazards Arising from the Chemical	Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.			
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			
NFPA	Health Hazard 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Use personal protective equipment. Avoid contact with skin, eyes and clothing.
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined areas. Do not allow material to contaminate ground water system.
Methods for Containment	Dike far ahead of liquid spill for later disposal. A vapor suppressing foam may be used to reduce vapors.
Methods for Cleaning Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use non-sparking tools and equipment. Pick up and transfer to properly labeled containers.
Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing.
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep in properly labeled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Hexane 110-54-3	STEL: 1000 ppm other than n-Hexane TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	IDLH: 1100 ppm Ceiling: 510 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 50 ppm TWA: 180 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Ethyl benzene 100-41-4	STEL: 125 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Measures

Showers. Eyewash stations. Explosion proof ventilation systems.

Personal Protective Equipment

Eye/Face Protection

Tightly fitting safety goggles.

Skin and Body Protection

Wear protective gloves/clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal feeding stuffs.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Yellow.	Odor	No information available
Odor Threshold	No information available	Physical State	Liquid
pH	No information available.		
Flash Point	-14°F / -10°C	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Boiling Range	>35°C / >95°F
Melting Point/Range	No information available		
Flammability Limits in Air	(Toluene)	Explosion Limits	No information available.
Upper	7.1%		
Lower	1.1%		
Solubility	No information available.	Evaporation Rate	No information available
Vapor Pressure	No data available	Vapor Density	No data available

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Strong acids. Strong oxidizing agents. Chlorinated compounds.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Carbon oxides. Hydrocarbons.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

No acute toxicity information is available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	>5580 mg/kg (Rat)	12124 mg/kg (Rat) 8390 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Naphtha, petroleum, hydrotreated light	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	83.2 mg/L (Rat) 4 h 64000 ppm (Rat) 4 h
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Quartz	500 mg/kg (Rat)		
Titanium dioxide	> 10000 mg/kg (Rat)		> 6820 mg/m ³
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Xylenes (o-, m-, p- isomers)	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Ethyl benzene	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Chronic Toxicity

Chronic Toxicity

Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects. May cause adverse liver and kidney effects. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1).

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene		Group 3	-	-
Titanium dioxide		Group 2B		X
Xylenes (o-, m-, p- isomers)		Group 3	-	-
Quartz	A2	Group 1	Known	X
Ethyl benzene	A3	Group 2B		X
Hexanoic acid, 2-ethyl-, lead(2+) salt		Group 3	Reasonably Anticipated	X
Benzene	A1	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

Target Organ Effects

Central nervous system (CNS). Central vascular system (CVS). Kidney. Liver. Respiratory system.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Toluene	EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 15.22-19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89-7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1-17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0-15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87-70.34 mg/L Poecilia reticulata 96 h static	EC50 = 19.7 mg/L 30 min	EC50 48 h: 5.46 - 9.83 mg/L Static (Daphnia magna) EC50 48 h: = 11.5 mg/L (Daphnia magna)
Acetone		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Naphtha, petroleum, hydrotreated light				LC50 96 h: = 2.6 mg/L (Chaetogammarus marinus)
Methyl alcohol	-	LC50 96 h: 13500 - 17600 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 18 - 20 mL/L static (Oncorhynchus mykiss) LC50 96 h: 19500 - 20700 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 28200 mg/L flow-through (Pimephales promelas) LC50 96 h: > 100 mg/L static (Pimephales promelas)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-
Hexane		LC50 96 h: 2.1-2.98 mg/L flow-through (Pimephales promelas)		EC50 24 h: > 1000 mg/L (Daphnia magna)

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Xylenes (o-, m-, p- isomers)		LC50 96 h: 13.1-16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 13.5-17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 2.661-4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 23.53-29.97 mg/L static (Pimephales promelas) LC50 96 h: 30.26-40.75 mg/L static (Poecilia reticulata) LC50 96 h: 7.711-9.591 mg/L static (Lepomis macrochirus) LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio)	EC50 = 0.0084 mg/L 24 h	LC50 48 h: = 0.6 mg/L (Gammarus lacustris) EC50 48 h: = 3.82 mg/L (water flea)
Ethyl benzene	EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0-18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: 7.55-11 mg/L flow-through (Pimephales promelas) LC50 96 h: 9.1-15.6 mg/L static (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)
Benzene	EC50 72 h: = 29 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 10.7-14.7 mg/L flow-through (Pimephales promelas) LC50 96 h: 22330-41160 µg/L static (Pimephales promelas) LC50 96 h: 70000-142000 µg/L static (Lepomis macrochirus) LC50 96 h: = 22.49 mg/L static (Lepomis macrochirus) LC50 96 h: = 28.6 mg/L static (Poecilia reticulata) LC50 96 h: = 5.3 mg/L flow-through (Oncorhynchus mykiss)		EC50 48 h: 8.76 - 15.6 mg/L Static (Daphnia magna) EC50 48 h: = 10 mg/L (Daphnia magna)

Chemical Name	Log Pow
Toluene	2.65
Acetone	-0.24
Methyl alcohol	-0.77
Xylenes (o-, m-, p- isomers)	3.15
Ethyl benzene	3.118
Benzene	1.83

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Do not re-use empty containers.

US EPA Waste Number

D001
D008
D018
U019
U056
U154
U220

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Acetone - 67-64-1		Included in waste stream: F039		U002
Methyl alcohol - 67-56-1		Included in waste stream: F039		U154
Ethyl benzene - 100-41-4		Included in waste stream: F039		
Benzene - 71-43-2	waste number U019	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172	= 0.5 mg/L regulatory level	U019

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene - 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Toluene	Toxic Ignitable
Acetone	Ignitable
Methyl alcohol	Toxic Ignitable
Hexane	Toxic Ignitable
Xylenes (o-, m-, p- isomers)	Toxic Ignitable
Ethyl benzene	Toxic Ignitable

Chemical Name	California Hazardous Waste
Hexanoic acid, 2-ethyl-, lead(2+) salt	Toxic
Benzene	Toxic Ignitable

14. TRANSPORT INFORMATION

Note: This product contains hazardous materials with reportable quantities as listed in Section 15. Based on net weight of product, the shipping description and label may need to be marked with "RQ."

DOT

UN-Number	UN1263
Proper shipping name	Paint
Hazard Class	3
Subsidiary Class	None
Packing Group	II
Description	UN1263,Paint,3,PG II,Marine Pollutant
Emergency Response Guide Number	128

TDG

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263,PAINT,3,PG II,Marine Pollutant

MEX

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Description	UN1263 Paint,3,II

ICAO

UN-Number	UN1263
Proper shipping name	Paint related material
Hazard Class	3
Packing Group	II
Description	UN1263,Paint related material,3,PG II

IATA

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
ERG Code	3L
Description	UN1263,Paint,3,PG II

IMDG/IMO

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-E
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
Description	UN1263, Paint,3,PG II,Marine Pollutant, FP -10C

RID

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3

Packing Group	II
Classification Code	F1
Description	UN1263 Paint,3,II

ADR

UN-Number	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Description	UN1263 Paint,3,II

ADN

UN-No	UN1263
Proper Shipping Name	Paint
Hazard Class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263 Paint,3,II
Hazard Labels	3
Limited Quantity	LQ6
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	40-70	1.0
Methyl alcohol	67-56-1	3-7	1.0
Hexane	110-54-3	1-5	1.0
Ethyl benzene	100-41-4	0.1-1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl alcohol	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Hexane	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes (o-, m-, p- isomers)			RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Hexanoic acid, 2-ethyl-, lead(2+) salt	301-08-6	Carcinogen
Toluene	108-88-3	Developmental
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Hexanoic acid, 2-ethyl-, lead(2+) salt			X	X	
Toluene	X	X	X	X	X
Methyl alcohol	X	X	X	X	X
Hexane	X	X	X	X	X
Quartz	X	X	X	-	X
Titanium dioxide	X	X	X	-	X
Benzene	X	X	X	X	X
Acetone		X			X
Xylenes (o-, m-, p- isomers)		X			X
Ethyl benzene	X	X	X	X	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Zirconium ethyl hexoate		Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³
Dipropylene glycol monomethyl ether		Mexico: TWA 100 ppm Mexico: TWA 60 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 900 mg/m ³
Toluene		Mexico: TWA= 50 ppm Mexico: TWA= 188 mg/m ³
Methyl alcohol		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³
Hexane		Mexico: TWA 50 ppm Mexico: TWA 176 mg/m ³ Mexico: STEL 1000 ppm Mexico: STEL 3500 mg/m ³
Quartz		Mexico: TWA= 0.1 mg/m ³
Titanium dioxide		Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³

Chemical Name	Carcinogen Status	Exposure Limits
Acetone		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m ³ Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m ³
Xylenes (o-, m-, p- isomers)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid

D2A Very toxic materials

D2B Toxic materials



Canadian National Pollutant Release Inventory (NPRI)

Chemical Name	NPRI
Toluene	X
Methyl alcohol	X
Hexane	X
Xylenes (o-, m-, p- isomers)	X

Legend

X - Listed

16. OTHER INFORMATION

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501
30-Jun-2011

Issuing Date

Revision Date

Revision Note

Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

End of Safety Data Sheet