

Material Safety Data Sheet

Issuing Date 07-Feb-2012 Revision Date Revision Date

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name LOW-TEMP W/B WHITE

Product Code(s) T-44-5120

Recommended Use Traffic paint

Product Technology W/B

Supplier Address

Ennis Paint Inc.
5910 North Central Expressway

Suite 1050 Dallas TX 75206 T: 800.331.8118

800.331.8118 (For Technical Inquiries)

Chemical Emergency Phone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Harmful by inhalation, in contact with skin and if swallowed Causes central nervous system depression.

May cause skin, eye, and respiratory tract irritation May adversely affect liver and kidney.

Cancer hazard

WARNING! This product contains a chemical known in the State of California to cause cancer.

Appearance White Physical State Emulsion. Odor Slight, Ammonia

Potential Health Effects

Ingestion

Principle Routes of Exposure Eye contact. Skin contact. Inhalation.

Acute Toxicity

Eyes May cause irritation.

Skin Harmful if absorbed through skin. May cause irritation.

Inhalation Harmful by inhalation. May cause central nervous system depression with nausea, headache,

dizziness, vomiting, and incoordination. Sanding and grinding dust may be harmful if inhaled. Harmful if swallowed. May cause blindness if swallowed. May cause additional affects as listed

under "Inhalation".

Chronic Effects Inhalation, ingestion, or skin absorption of methanol can cause blindness. This product

contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic

to humans (Group 2B) by inhalation.

Respiratory disorders. Lungs. Pre-existing eye disorders. Skin disorders. Liver disorders. **Aggravated Medical Conditions**

Kidney disorders. Central nervous system.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Environmental Hazard Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Titanium dioxide	13463-67-7	15-40
Methyl alcohol	67-56-1	5-10
Quartz	14808-60-7	1-5

4. FIRST AID MEASURES

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

symptoms persist, call a physician.

Wash off immediately with plenty of water. Remove and wash contaminated clothing before re-**Skin Contact**

use. If symptoms persist, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink

plenty of water. If symptoms persist, call a physician.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Not flammable. Flammable Properties

> 201°F / 93.8°C **Flash Point**

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Explosion Data

Sensitivity to Mechanical Impact None

Sensitivity to Static Discharge None

Protective Equipment and As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

Precautions for Firefighters (approved or equivalent) and full protective gear.

Health Hazard 1 NFPA Flammability 1 **Instability** 0 **Physical and Chemical**

Hazards -

HMIS Health Hazard 2* Flammability 1 **Physical Hazard** 0 **Personal Protection X** **6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Avoid contact with skin, eyes

and clothing.

Environmental Precautions Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Use personal protective equipment. Dike far ahead of liquid spill for later disposal. Soak up

with inert absorbent material. Clean up promptly by sweeping or vacuum. Keep in suitable and

closed containers for disposal.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid contact with skin, eyes

and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or

smoke when using this product.

Storage Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled

containers. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lubricating oils, petroleum, hydrotreated spent 64742-58-1	TWA: 5 mg/m³, as oil mist, mineral STEL: TWA: 10 mg/m³, as oil mist, mineral	TWA: 5 mg/m³, as oil mist, mineral	
White mineral oil 8042-47-5	TWA: 5 mg/m³inhalable fraction excluding metal working fluids, highly & severely refined	TWA: 5 mg/m³ (vacated) TWA: 5 mg/m³	IDLH: 2500 mg/m³ TWA: 5 mg/m³ STEL: 10 mg/m³
Quartz 14808-60-7	TWA: 0.025 mg/m³respirable fraction	30/(%SiO2+2) mg/m³ TWA, Total Dust;250/%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m³ TWA, respirable TWA: 0.1 mg/m³ (vacated)	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Trade Secret	TWA: 5 mg/m³, as oil mist, mineral STEL: TWA: 10 mg/m³, as oil mist, mineral	TWA: 5 mg/m³, as oil mist, mineral	
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m³total dust (vacated) TWA: 10 mg/m³total dust	IDLH: 5000 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³ (vacated) STEL: 325 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 325 mg/m³ STEL: 250 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Engineering Measures Showers

Eyewash stations Ventilation systems

Personal Protective Equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection Safety glasses with side-shields.

Protective gloves.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance

with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing

before re-use. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceWhite.OdorSlight, Ammonia.

Odor Threshold Not applicable Physical State Emulsion

pH Not applicable

Flash Point > 201°F / 93.8°C Autoignition Temperature Not applicable

Decomposition Temperature Not applicable Boiling Point/Boiling Range Not applicable

Flammability Limits in Air Not applicable

SolubilityNot applicableEvaporation RateNot applicableVapor PressureNot applicableVapor DensityNot applicable

VOC (g/I) < 100

Melting Point/Range

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products None known based on information supplied.

Not applicable

Conditions to AvoidNone known based on information supplied.

Hazardous Decomposition Products Carbon oxides. Nitrogen oxides (NOx).

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

Harmful if swallowed, inhaled, or absorbed through skin.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Quartz	500 mg/kg (Rat)		
Titanium dioxide	> 10000 mg/kg (Rat)		> 6820 mg/m ³
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	83.2 mg/L (Rat) 4 h
			64000 ppm (Rat) 4 h

Chronic Toxicity

Chronic Toxicity

Inhalation, ingestion, or skin absorption of methanol can cause blindness. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen (Group 1). This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Quartz	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Target Organ Effects

Respiratory system. Liver. Kidney. Central nervous system (CNS).

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol	-	LC50 96 h: 13500 - 17600	EC50 = 39000 mg/L 25 min	-
		mg/L flow-through (Lepomis	EC50 = 40000 mg/L 15 min	
		macrochirus)	EC50 = 43000 mg/L 5 min	
		LC50 96 h: 18 - 20 mL/L	_	
		static (Oncorhynchus mykiss)		
		LC50 96 h: 19500 - 20700		
		mg/L flow-through		
		(Oncorhynchus mykiss)		
		LC50 96 h: = 28200 mg/L		
		flow-through (Pimephales		
		promelas)		
		LC50 96 h: > 100 mg/L static		
		(Pimephales promelas)		

Chemical Name	Log Pow
Methyl alcohol	-0.77

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol - 67-56-1		Included in waste stream:		U154
		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol	Toxic
·	Ignitable

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA All components are listed on the TSCA Inventory.

DSL All components are listed either on the DSL or NDSL.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	5-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Chemical Name	CAS-No	California Prop. 65
Quartz	14808-60-7	Carcinogen
Titanium dioxide	13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Quartz	X	X	X	-	X
Methyl alcohol	X	X	Х	Х	Х
Titanium dioxide	Х	X	X	-	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
White mineral oil		Mexico: TWA 5 mg/m ³
		Mexico: STEL 10 mg/m ³
Quartz		Mexico: TWA= 0.1 mg/m ³
Limestone		Mexico: TWA 10 mg/m ³
		Mexico: STEL 20 mg/m ³
Titanium dioxide		Mexico: TWA= 10 mg/m ³
		Mexico: STEL= 20 mg/m ³
Methyl alcohol		Mexico: TWA= 200 ppm
		Mexico: TWA= 260 mg/m ³
		Mexico: STEL= 250 ppm
		Mexico: STEL= 310 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D1B Toxic materials D2A Very toxic materials D2B Toxic materials



Chemical Name	NPRI
Methyl alcohol	X

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Prepared By Product Stewardship

23 British American Blvd.

Latham, NY 12110 1-800-572-6501

Issuing Date 07-Feb-2012

Revision Date

Revision Note Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication and it does not purport to be all inclusive and shall be used only as a guide. We urge each customer or recipient of this MSDS to study it carefully to become aware of and understand the potential hazards associated with the product. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text. Any use of the product not in conformance with this MSDS or in combination with any other product or process is the responsibility of the user. Customary precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Remove all soiled and contaminated clothing immediately.

End of Safety Data Sheet