HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: ENVIROMUL® RF SYSTEM with BARODENSE®

Revision Date: 03-Jan-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: ENVIROMUL® RF SYSTEM with BARODENSE®

Synonyms: None
Chemical Family: Blend
Application: Mud System

Manufacturer/Supplier Baroid Fluid Services

Product Service Line of Halliburton

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Hematite	1317-60-8	30 - 60%	Not applicable	Not applicable
Mineral oil		30 - 60%	5 mg/m ³	5 mg/m ³
Calcium chloride	10043-52-4	5 - 10%	Not applicable	Not applicable
Crystalline silica, quartz	14808-60-7	0 - 1%	0.025 mg/m ³	10 mg/m ³
				%SiO2 + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

3. HAZARDS IDENTIFICATION

Hazard Overview CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation. May be harmful if swallowed.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud if this product becomes dry. Avoid breathing or creating dust. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using dried product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

FIRST AID MEASURES

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation

develops or if breathing becomes difficult.

Wash with soap and water. Get medical attention if irritation persists. Skin

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes

and get medical attention if irritation persists.

Ingestion Get medical attention! If vomiting occurs, keep head lower than hips to prevent

aspiration.

Notes to Physician Not Applicable

FIRE FIGHTING MEASURES

Flash Point/Range (F): 255 Flash Point/Range (C): 123 Flash Point Method: **PMCC**

Autoignition Temperature (F): Not Determined **Autoignition Temperature (C):** Not Determined

Flammability Limits in Air - Lower (%): 0.9 Flammability Limits in Air - Upper (%):

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Decomposition in fire may produce toxic gases. **Special Exposure Hazards**

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

Health 1, Flammability 1, Reactivity 0 **NFPA Ratings: HMIS Ratings:** Health 1*, Flammability 1, Reactivity 0

ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate spill and stop leak where safe. Contain spill with sand or other inert materials.

Scoop up and remove.

HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing mist. This product contains

> quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud if this product becomes dry. Avoid breathing or creating dust. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using

dried product.

Storage Information Store away from oxidizers. Store in a cool well ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering ControlsUse approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits listed in Section 2.

Respiratory Protection When the potential exists for dust of this product to be created, wear a NIOSH

certified, European Standard En 149, or equivalent respirator when using this

product.

When the potential exists for aerosols or mists of this product to be created, use a respirator with a particulate filter for oil aerosols or a supplied-air respirator as

needed for adequate protection.

When the potential exists for heated vapors or fumes of this product to be created, use a respirator with an organic-vapor filter or a supplied-air respirator as needed for

adequate protection.

Hand Protection Impervious rubber gloves.

Skin Protection Normal work coveralls.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Color: Brown

Odor: Mild hydrocarbon pH: Not Determined

Specific Gravity @ 20 C (Water=1): 1.44

Density @ 20 C (lbs./gallon): 12

Bulk Density @ 20 C (lbs/ft3): Not Determined

Boiling Point/Range (F): 490 Boiling Point/Range (C): 254

Freezing Point/Range (F):

Freezing Point/Range (C):

Not Determined

Not Determined

Vapor Pressure @ 20 C (mmHg): 0.9
Vapor Density (Air=1): > 8

Percent Volatiles:

Evaporation Rate (Butyl Acetate=1):

Solubility in Water (g/100ml):

Not Determined
Insoluble
Not Determined
Not Determined

VOCs (Ibs./gallon):
Viscosity, Dynamic @ 20 C (centipoise):
Not Determined
Viscosity, Dynamic @ 20 C (centipoise):
Not Determined
Viscosity, Kinematic @ 20 C (centistrokes):
Not Determined
Partition Coefficient/n-Octanol/Water:
Not Determined
Not Determined
Not Determined
Not Determined
Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None anticipated

Incompatibility (Materials to

Avoid)

Strong oxidizers.

Hazardous Decomposition Products

Carbon monoxide and carbon dioxide.

Additional Guidelines

Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure

Eye or skin contact, inhalation.

Inhalation

May cause respiratory irritation. Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Skin Contact

May cause skin irritation. May cause an allergic skin reaction.

Eye Contact

May cause eye irritation.

Ingestion

Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

Aggravated Medical Conditions

Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Other Information

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).

ENVIROMUL® RF SYSTEM with BARODENSE® Page 4 of 7

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

Carcinogenicity Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June

1997).

Genotoxicity: Not determined

Reproductive /

Not determined

Developmental Toxicity:

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: TLM48: 181 mg/l (Arcatia tonsa)

Acute Crustaceans Toxicity: Not determined

Acute Algae Toxicity: E(B)C50: 491 mg/l (Skeletonema costatum)

Chemical Fate InformationNot determinedOther InformationNot applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

Not restricted

Canadian TDG

Not restricted

ADR

Not restricted

Air Transportation

ICAO/IATA

Not restricted

Sea Transportation

IMDG

Not restricted

Other Transportation Information

Labels: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals

This product does not contain a toxic chemical for routine annual "Toxic Chemical

Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity

Not applicable.

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class D2A Very Toxic Materials

Crystalline silica

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

END OF MSDS