#### **HALLIBURTON**

# MATERIAL SAFETY DATA SHEET

Product Trade Name: ES-4 PROPLOK SURFACTANT

Revision Date: 20-Dec-2012

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: ES-4 PROPLOK SURFACTANT

Synonyms:NoneChemical Family:BlendApplication:Surfactant

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Oxyalkylated resins	Mixture	30 - 60%	Not applicable	Not applicable
Isoamyl alcohol	123-51-3	10 - 30%	100 ppm	100 ppm
Heavy aromatic petroleum	64742-94-5	5 - 10%	Not applicable	Not applicable
naphtha				
Methanol	67-56-1	5 - 10%	200 ppm (S)	200 ppm

#### 3. HAZARDS IDENTIFICATION

**Hazard Overview** May cause skin and respiratory irritation. May cause eye burns. May cause

headache, dizziness, and other central nervous system effects. May be fatal if swallowed. May cause blindness. Repeated overexposure may cause liver and

kidney effects. Flammable.

#### 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Skin** In case of contact, immediately flush skin with plenty of soap and water for at least 15

minutes. Get medical attention. Remove contaminated clothing and launder before

reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Get medical attention! If vomiting occurs, keep head lower than hips to prevent

aspiration.

Notes to Physician Not Applicable

ES-4 PROPLOK SURFACTANT Page 1 of 6

#### FIRE FIGHTING MEASURES

Flash Point/Range (F): 77 Flash Point/Range (C): 25

Flash Point Method: Not Determined **Autoignition Temperature (F):** Not Determined **Autoignition Temperature (C):** Not Determined

Flammability Limits in Air - Lower (%): Flammability Limits in Air - Upper (%): 36.5

Water fog, carbon dioxide, foam, dry chemical. Fire Extinguishing Media

**Special Exposure Hazards** May be ignited by heat, sparks or flames. Use water spray to cool fire exposed

surfaces. Closed containers may explode in fire. Decomposition in fire may produce

toxic gases.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

Health 2, Flammability 3, Reactivity 0 **NFPA Ratings:** Health 2, Flammability 3, Reactivity 0 **HMIS Ratings:** 

#### ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

**Environmental Precautionary** 

**Measures** 

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

**Absorption** 

Isolate spill and stop leak where safe. Remove ignition sources and work with nonsparking tools. Contain spill with sand or other inert materials. Scoop up and

remove.

#### HANDLING AND STORAGE

**Handling Precautions** Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after

use. Launder contaminated clothing before reuse. Ground and bond containers

when transferring from one container to another.

Store away from oxidizers. Store in a well ventilated area. Keep from heat, sparks, **Storage Information** 

and open flames. Keep container closed when not in use. Product has a shelf life of

24 months.

# **EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering Controls** Use in a well ventilated area. Local exhaust ventilation should be used in areas

without good cross ventilation.

**Respiratory Protection** Positive pressure self-contained breathing apparatus if methanol is released.

**Hand Protection** Impervious rubber gloves.

**Skin Protection** Rubber apron.

Chemical goggles; also wear a face shield if splashing hazard exists. **Eve Protection** 

Other Precautions Eyewash fountains and safety showers must be easily accessible.

> **ES-4 PROPLOK SURFACTANT** Page 2 of 6

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Color: Straw Odor: Strong pH: 8
Specific Gravity @ 20 C (Water=1): 0.95
Density @ 20 C (lbs./gallon): 7.94

Bulk Density @ 20 C (lbs/ft3):

Boiling Point/Range (F):

Not Determined

Boiling Point/Range (C):

Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

Vapor Pressure @ 20 C (mmHg):

Not Determined

Percent Volatiles: <50

Evaporation Rate (Butyl Acetate=1): Not Determined

Solubility in Water (g/100ml): Soluble

Solubility in Solvents (g/100ml):

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistokes):

Partition Coefficient/n-Octanol/Water:

Molecular Weight (g/mole):

Not Determined

Not Determined

### 10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

**Conditions to Avoid** Keep away from heat, sparks and flame.

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong alkalis.

**Hazardous Decomposition** 

**Products** 

Toxic fumes. Oxides of sulfur. Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

### 11. TOXICOLOGICAL INFORMATION

**Principle Route of Exposure** Eye or skin contact, inhalation.

**Inhalation** May cause respiratory irritation. May cause central nervous system depression

including headache, dizziness, drowsiness, incoordination, slowed reaction time,

slurred speech, giddiness and unconsciousness.

**Skin Contact**Causes severe skin irritation with tissue destruction.

**Eye Contact** May cause severe eye irritation. May cause permanent eye damage.

**Ingestion** May be fatal or cause blindness if swallowed. May cause central nervous system

depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. Aspiration into the lungs may cause chemical programment in including coupling, difficulty breathing, who ging coupling up blood

pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

ES-4 PROPLOK SURFACTANT Page 3 of 6 Aggravated Medical Conditions Skin disorders. Eye ailments.

Chronic Effects/Carcinogenicity Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart,

central nervous system and spleen damage.

Other Information None known.

**Toxicity Tests** 

Oral Toxicity: Not determined

**Dermal Toxicity:** Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

**Developmental Toxicity:** 

### 12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

# **Ecotoxicological Information**

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

#### 13. DISPOSAL CONSIDERATIONS

**Disposal Method**Disposal should be made in accordance with federal, state, and local regulations.

**Contaminated Packaging** Follow all applicable national or local regulations.

Not determined

### 14. TRANSPORT INFORMATION

#### **Land Transportation**

#### DOT

UN1993, Flammable Liquid, N.O.S. (Contains Methanol, Heavy Aromatic Naphtha), 3, III, (25 C) NAERG 128

#### **Canadian TDG**

Flammable Liquid, N.O.S. (Contains Methanol, Heavy Aromatic Naphtha), 3, UN1993, III, (25 C)

#### **ADR**

UN1993, Flammable Liquid, N.O.S. (Contains Methanol, Heavy Aromatic Naphtha), 3, III

## **Air Transportation**

#### ICAO/IATA

UN1993, Flammable Liquid, N.O.S., 3, III (Contains Methanol, Heavy Aromatic Naphtha)

#### Sea Transportation

#### **IMDG**

UN1993,Flammable Liquid, N.O.S.(Contains Methanol, Heavy Aromatic Naphtha), 3, III, (25 C) EmS F-E, S-E

#### Other Transportation Information

Labels: Flammable Liquid

#### 15. REGULATORY INFORMATION

#### **US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely Hazardous Substances** 

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard Chronic Health Hazard

Fire Hazard

EPA SARA (313) Chemicals This produ

This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Methanol//67-56-1

EPA CERCLA/Superfund Reportable Spill Quantity

EPA Reportable Spill Quantity is 7871 Gallons based on Methanol (CAS: 67-56-1).

**EPA RCRA Hazardous Waste** 

Classification

If product becomes a waste, it does meet the criteria of a hazardous waste as

defined by the US EPA, because of:

Ignitability D001

**California Proposition 65** All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law
One or more components listed.

NJ Right-to-Know Law
One or more components listed.

PA Right-to-Know Law One or more components listed.

**Canadian Regulations** 

ES-4 PROPLOK SURFACTANT Page 5 of 6 **Canadian DSL Inventory** 

All components listed on inventory or are exempt.

**WHMIS Hazard Class** 

B2 Flammable Liquids D2B Toxic Materials

### 16. OTHER INFORMATION

# The following sections have been revised since the last issue of this MSDS

Not applicable

**Additional Information** 

For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement** 

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

\*\*\*END OF MSDS\*\*\*