

SAFETY DATA SHEET



Date Issued : 10/6/2014

MSDS No : 268

LACQUER WASH THINNER A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LACQUER WASH THINNER A**MANUFACTURER**

Tarr, LLC
P.O. Box 12570
Portland, OR 97212
Product Stewardship: 503-288-5294

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Physical:**

Flammable Liquids, Category 3

GHS LABEL

Flame

Exclamation
mark**SIGNAL WORD: DANGER****HAZARD STATEMENTS**

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H302: Harmful if swallowed.

PRECAUTIONARY STATEMENT(S)**Prevention:**

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May cause asphyxiation, or brain, lung or other organ injury if inhaled, swallowed or absorbed by the skin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

LACQUER WASH THINNER A

SKIN: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis. May cause abdominal pain, nausea and vomiting.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing eye and skin disorders may be aggravated by exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Acetone	35 - 45	67-64-1
Toluene	37 - 47	108-88-3
n-Heptane	< 2	142-82-5
Methylcyclohexane	< 2	108-87-2
Cyclohexane	< 1	110-82-7
Solvent naphtha, light aliphatic	15 - 25	64742-89-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

INGESTION: Do not give liquids if victim is unconscious or drowsy. Otherwise, give 2 glasses of water and induce vomiting by giving 30cc syrup of ipecac (or touching finger to the back of victim's throat). Keep victim's head below hips while vomiting. Call doctor.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IB flammable liquid.

GENERAL HAZARD: Flammable Liquid and Vapor! Contact with strong oxidizers may cause fire.

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be

LACQUER WASH THINNER A

formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep material out of storm sewers and ditches which lead to waterways.

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

LACQUER WASH THINNER A**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
Acetone	TWA	1000	2400	500			
	STEL			750			
Toluene	TWA	200		50 ^[2]	188 ^[2]		
	STEL	300 ^[1]	^[1]				
n-Heptane	TWA	500 %	2000	400 %			
	STEL			500			
Cyclohexane	TWA	300 ppm ^[3]	1050 mg/m ³ ^[3]	100 ppm	350 mg/m ³	NL ppm	NL ppm
	STEL	ppm	mg/m ³	ppm	mg/m ³	NL ppm	NL mg/m ³
Solvent naphtha, light aliphatic	TWA	^[4]	^[4]			100 ^[5]	400 ^[5]
OSHA TABLE COMMENTS: 1. C = Ceiling 2. S = Skin 3. NL = Not Listed 4. Our supplier has adopted, as Interim Standards, the OSHA PELs that were established in 1989 and later rescinded. 5. In the absence of occupational exposure standards for this product, it is recommended that these values are adopted.							

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

LACQUER WASH THINNER A

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Pungent odor.

APPEARANCE: Clear

COLOR: Colorless.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: < (20°F) TAG CC

AUTOIGNITION TEMPERATURE: Not Available

VAPOR PRESSURE: 82 mmHg @ 20C

BOILING POINT: (133°F) to (247°F)

SOLUBILITY IN WATER: Complete solubility with most hydrocarbon solvents, partial solubility with water.

EVAPORATION RATE: Slower than ether.

DENSITY: 6.88 at (60°F)

SPECIFIC GRAVITY: 0.82 to 0.81 15.5°C/60°F

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under ordinary conditions of use and storage.

POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Prevent vapor accumulation.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE

LACQUER WASH THINNER A

Chemical Name	ORAL LD₅₀ (rat)	DERMAL LD₅₀ (rabbit)	INHALATION LC₅₀ (rat)
Acetone	5800 mg/kg (Rat)		
Solvent naphtha, light aliphatic	> 2000 mg/kg (Rat)	> 2000 mg/kg (rat)	> 5000 ppm / 1 hour (rat)

NOTES: Material may cause eye irritation. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness, swelling and eye damage.

EYE EFFECTS: Irritating to eyes.

GENERAL COMMENTS: None identified.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Readily biodegradable.

ECOTOXICOLOGICAL INFORMATION: Keep out of waterways.

BIOACCUMULATION/ACCUMULATION: Not expected to bioaccumulate significantly.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Paint Related Material

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1263

PACKING GROUP: II

NAERG: 128

REPORTABLE QUANTITY (RQ) UNDER CERCLA: 5,000 pounds

LABEL: Flammable liquid

MARINE POLLUTANT #1: No

LACQUER WASH THINNER A**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable

Liquid

S23: Do not breathe gas/fumes/vapour/spray.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**CERCLA RQ:**

Acetone 5000 lbs

Toluene 1000 lbs

CALIFORNIA PROPOSITION 65: To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

CANADA**WHMIS HAZARD SYMBOL AND CLASSIFICATION**

Flammable

Liquid

S15: Keep away from heat.


GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

REASON FOR ISSUE: Updated SDS information and changed to new format.

LACQUER WASH THINNER A**PREPARED BY:** Compliance**HMIS RATING**

HEALTH		1
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		G

NFPA CODES

NFPA STORAGE CLASSIFICATION: These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

HMIS RATINGS NOTES: Personal protection rating to be supplied by user depending on use conditions.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.