

MATERIAL SAFETY DATA SHEET

BLANKET ROLLER WASH 342

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Tarr, LLC
P.O. Box 12570
Portland, OR 97212

INFORMATION PHONE: (503) 288-5294

EMERGENCY PHONE: CHEMTREC 800-424-9300 (US) Day or night
International Call Collect CHEMTREC 202-483-7616

PRODUCT NAME: BLANKET ROLLER WASH 342

PRODUCT NUMBER: BRW342

UPC NUMBER:

PREPARED BY: Patricia Rodabaugh

DATE PREPARED: 6/17/2004

LAST REVISION: 6/17/2004

SYNONYMS:



Portland, Oregon
Phoenix, Arizona
Auburn, Washington
Vancouver, Washington

Print Date: 10/18/2004

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	Weight %	OSHA PEL	ACGIH TLV	NOTE
Solvent naphtha, light aromatic	64742-95-6	48-55	N/A	N/A	INCLUDING THE NEXT 3 COMPONENTS LISTED BELOW:
Xylenes	1330-20-7	1-2	100 ppm	100 ppm	
Trimethylbenzene, 1,2,4,-	95-63-6	16-22	25 ppm	25 ppm	
Cumene	98-82-8	<2	50 ppm	50 ppm	
Solvent naphtha, medium aliphatic	64742-88-7	33-41	100 ppm*	100 ppm*	
Butoxyethanol, 2-	111-76-2	6-10	25 ppm (skin)	25 ppm (skin)	
Terpene hydrocarbon	5989-27-5	1-3	N/A	N/A	
Ethoxylated nonyl phenol	9016-45-9	<2	1 ppm	10 ppm	

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER! COMBUSTIBLE LIQUID AND VAPOR. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating.

INHALATION: May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

INGESTION: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspir. pneumonitis.

SKIN CONTACT: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SIGNS AND SYMPTOMS OF EXPOSURE:

Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis.

4. FIRST AID MEASURES

- EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation persists, get medical attention.
- INHALATION:** Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention.
- INGESTION:** Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.
- SKIN CONTACT:** Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impaired function from preexisting disorders may be aggravated by exposure to this product.

SUPPLEMENTAL HEALTH INFORMATION:

Refer to Section 16.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 115 F

FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NDA

LEL: 0.007 **UEL:** 0.061

EXTINGUISHING MEDIA:

Use water fog, "alcohol" foam, dry chemical, or CO2.

SPECIAL FIRE FIGHTING PROCEDURES:

DANGER! Combustible Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

COMBUSTION PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Remove all sources of ignition and provide ventilation. Wear protective equipment as given in Section 8. Dike around large spills to prevent spreading. Absorb small spills with inert material (clay, sand). Prevent contamination of surface waters.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respir. or an air-purifying respir. for organic vapors.

VENTILATION:

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PROTECTIVE GLOVES:

Test data indicate the best protection is provided by neoprene, nitrile, and natural rubber gloves.

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

ENGINEERING CONTROLS:

Use this material only in well ventilated areas.

EXPOSURE GUIDELINES:

May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUBILITY IN WATER: Solubility negligible in water

APPEARANCE AND ODOR: Colorless, clear liquid. Mild odor.

BOILING POINT:	310 F	PERCENT VOLATILE:	100
VAPOR PRESSURE:	2	PH:	N/A
EVAPORATION RATE:	Slower than ether	MOLECULAR WEIGHT:	N/A
POUNDS PER GALLON:	6.993	VAPOR DENSITY:	Heavier than air
SPECIFIC GRAVITY:	0.84	OTHER PROPERTIES:	VOCs:6.9928lbs/gal,838.028gm/L
MELTING POINT:	NDA		
FREEZING POINT:	NDA		

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

INCOMPATIBILITY:

Acids and excessive heat.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide, carbon dioxide and other oxides may be generated as products of combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition.

11. TOXICOLOGY INFORMATION

This product may contain benzene (CAS No. 71-43-2) at a concentration less than 10 ppm and ethylene oxide (CAS 75-21-8) at a deminimis concentration up to 0.1ppm. Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have

associated repeated, prolonged overexposure to solvents with permanent brain and nervous system damage.

12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name:	Combustible liquid, n.o.s. (naphtha)	PACKING GROUP:	III
		GUIDE NUMBER:	128
HAZARD CLASS:	Combustible	DOT CLASS:	Combustible Liquid
UN NUMBER:	NA 1993		

15. REGULATORY INFORMATION

Combustible exception: 173.150(f)(1) All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

16. OTHER INFORMATION

HMIS INFORMATION: **HEALTH:** 2 **FLAMMABILITY:** 2 **REACTIVITY:** 0 **PROTECTIVE:** H

SARA Title III Information:

SARA 302: Ethylene oxide is listed.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313: Xylenes (1330-20-7), Trimethylbenzene, 1, 2, 4- (95-63-6), Cumene(98-82-8), ethylene oxide (75-21-8)

Supplemental Health Info.: Exposure of rats by inhalation to 2-butoxyethanol caused hemolysis, hemoglobinuria (blood in the urine) and a slight increase in liver weight. Other species, including man, were much less sensitive to hemolysis. The hemolytic effect seen in rats was transitory and/or reversible and not considered to be relevant to human health.

California Proposition 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer and reproductive harm. BENZENE. ETHYLENE OXIDE.

N/A = Not Applicable

NDA = No Data Available

Disclaimer

This information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.