# MATERIAL SAFETY DATA SHEET

## CY WASH

#### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**MANUFACTURER:** Tarr, Incorporated

P.O. Box 12570

Portland, OR 97212

**INFORMATION PHONE:** (503) 288-5294

EMERGENCY PHONE: CHEMTREC 800-424-9300 (US) Day or night

International Call Collect CHEMTREC 202-483-7616

PRODUCT NAME: CY WASH

PRODUCT NUMBER: CW

**UPC NUMBER:** 

PREPARED BY: Patricia Rodabaugh

**DATE PREPARED:** 7/1/2003 **LAST REVISION:** 9/5/2002

**SYNONYMS:** 

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS # Weight % OSHA PEL ACGIH TLV NOTE

Perchloroethylene 127-18-4 73-77 100 ppm

n-Butanol 71-36-3 23-27 50 ppm 50 ppm

#### 3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Flammable and toxic liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

## POTENTIAL HEALTH EFFECTS

**EYE CONTACT:** Liquid is practically nonirritating to the eyes. High vapor concentrations may cause eye irritation.

**INHALATION:** Vapors may be irritating to the nose, throat, and respiratory tract. High vapor concentrations may cause central

nervous system (CNS) depression.

**INGESTION:** Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product

may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may

Portland, Oregon Phoenix, Arizona

Auburn, Washington

Vancouver, Washington

**Print Date:** 10/28/2004

result in aspir. pneumontis.

**SKIN CONTACT:** Liquid is slightly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin

which may result in skin irritation and dermatitis (rash).

#### SIGNS AND SYMPTOMS OF EXPOSURE:

Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing an cyanosis.

## 4. FIRST AID MEASURES

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation

occurs, get medical attention.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be

administered by qualified personnel. Get medical attention immediately.

CW Page 1 of 4

**INGESTION:** DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep head below hips to prevent

aspiration of liquid into the lungs. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If

irritation occurs, get medical attention. Do not reuse clothing until cleaned.

#### AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.

## SUPPLEMENTAL HEALTH INFORMATION:

Male rats exposed for 90 days by inhalation to vapors of similar solvents showed evidence of kidney damage. The relevance of this effect to humans is unknown. In one of the studies a low grade anemia was also observed.

## 5. FIRE FIGHTING MEASURES

## FLAMMABLE PROPERTIES

FLASH POINT: 156 F FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NDA LEL: 0.014 UEL: 0.112

#### **EXTINGUISHING MEDIA:**

Use foam, dry chemical, or carbon dioxide (CO2).

#### SPECIAL FIRE FIGHTING PROCEDURES:

WARNING. Flammable, toxic Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

## COMBUSTION PRODUCTS:

Carbon monoxide and carbon dioxide may be formed during combustion.

## 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

WARNING. Flammable and Toxic. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

## 7. HANLDING AND STORAGE

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

## **OTHER PRECAUTIONS:**

KEEP OUT OF REACH OF CHILDREN. Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

## RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respir. of an air-purifying respir. for organic vapors.

#### **VENTILATION:**

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Use explosion-proof ventilation as required to control vapor concentrations.

#### **PROTECTIVE GLOVES:**

Test data indicate the best protection is provided by nitrile gloves.

CW Page 2 of 4

#### EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear gloves and protective clothing which are impervious to this product for the duration of anticipated exposure, if there is potential for skin contact.

#### **WORK / HYGENIC PRACTICES:**

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

#### **ENGINEERING CONTROLS:**

Facilities storing or utilizing this material should be equipped with and eyewash facility and a safety shower.

## **EXPOSURE GUIDELINES:**

May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventillation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**SOLUBILITY IN WATER:** Solubile in most organic solvents, slightly miscible with water.

APPEARANCE AND ODOR: Clear, water-white liquid. Mild odor.

**BOILING POINT:** 244 F **PERCENT VOLATILE:** 100

VAPOR PRESSURE: 4.1 PH: N/A

EVAPORATION RATE: Slower than ether MOLECULAR WEIGHT: NDA

POUNDS PER GALLON: 11.47 VAPOR DENSITY: Heavier than air

SPECIFIC GRAVITY: 1.3698 - 137.530 OTHER PROPERTIES: N/A

MELTING POINT: NDA FREEZING POINT: NDA

#### 10. STABILITY AND REACTIVITY

STABILITY: Stable

**CONDITIONS TO AVOID:** Avoid heat, sparks, flame and contact with strong oxidizing agents,

## INCOMPATIBILITY:

Strong acids or bases, oxidizers, alkali metals, and halogens.

#### HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition.

# 11. TOXICOLOGY INFORMATION

Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervouus system damage.

CW Page 3 of 4

## 12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

## 13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

## 14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name: Toxic liquids, organic, n.o.s. PACKING GROUP: Π

(tetrachloroethylene, n-butanol) **GUIDE NUMBER:** 153

**HAZARD CLASS:** 6.1 DOT CLASS: Toxic

**UN NUMBER:** UN2810

## 15. REGULATORY INFORMATION

This product is listed on the EPA/TSCA Inventory of Chemical Substances.

## 16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 2 FLAMMABILITY: 2 **REACTIVITY:** 0 PROTECTIVE: H

**SARA Title III Information:** 

**SARA 302:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**SARA 313:** Perchloroethylene (127-18-4) is listed.

Tetrachloroethylene is listed as a marine pollutant under 49 CFR 172.101, Appendix B. Supplemental Health Info.:

Reportable Quantity (RQ): Tetrachloroethylene: 100 lbs., n-Butyl Alcohol: 5,000 lbs.

NOTE TO PHYSICIAN: If more than 2.0 ml per kg has been ingested and vomiting has not occurred, emisis should be induced with supervision. Keep victim's head below hips to prevent aspiration. If symptoms such as loss of gag reflex, convulsions or

unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

N/A = Not Applicable NDA = No Data Available

## Disclaimer

The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr, Incorporated makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Tarr, Inc. assumes no responsibility for injuries from the use of the product described herein.

CW Page 4 of 4