

MATERIAL SAFETY DATA SHEET



Date Issued: 09/12/2011
MSDS No: 4187

WCI HIXP2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WCI HIXP2

PRODUCT CODE: 4187

MANUFACTURER

Tarr Acquisition, LLC
4115 W. Turney Ave.
Phoenix, AZ 85019
Service Number: 602-233-2000

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: CAUTION! COMBUSTIBLE LIQUID AND VAPOR. Harmful or fatal if swallowed. Can enter lungs and cause damage. May cause eye and skin irritation or injury. Prolonged or repeated skin contact may increase the risk of skin cancer.

POTENTIAL HEALTH EFFECTS

EYES: Liquid or vapor may cause eye irritation.

SKIN: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. Exposure to high vapor concentrations may cause central nervous system (CNS) depression.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing lung or skin conditions may be aggravated by repeated exposure. May cause skin and liver disease, may attack respiratory tract.

COMMENTS HEALTH: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

WCI HIXP2

Chemical Name	Wt.%	CAS	EINECS
Aliphatic Petroleum Distillates	80 - 90	64742-96-7	- -
Alkanes, C10-24-branched	< 5	289711-48-4	
Citrus/Peppermint Fragrance - trade secret	12 - 16		

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

SKIN: Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

INGESTION: DO NOT INDUCE VOMITING. Do not attempt to give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 61°C (124°F) to 232.7°C (145°F) TAG CC

FLAMMABLE LIMITS: 0.8 to 6.0

AUTOIGNITION TEMPERATURE: > 316°C (600°F)

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: Clear fire area of all non-emergency personnel. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus. Containers exposed to intense heat from fires should be cooled with large quantities of water to prevent weakening of container structure which could result in container rupture.

FIRE FIGHTING EQUIPMENT: The use of SCBA is recommended for firefighters. Water spray may be used to cool containers exposed to heat or flame.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Remove all sources of ignition and provide ventilation. Wear protective clothing as given in section 8. Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material with absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal using non-sparking equipment. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for proper disposal.

WCI HIXP2

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

STORAGE TEMPERATURE: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)			
		EXPOSURE LIMITS	
		ACGIH TLV	
Chemical Name		ppm	mg/m ³
Aliphatic Petroleum Distillates	TWA	[1]	[1]
OSHA TABLE COMMENTS: 1. (8 hour TWA)(solvent industry)			

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Impervious gloves such as viton or nitrile should be worn at all times when handling this material. (Consult your safety equipment supplier.) In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

PROTECTIVE CLOTHING: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

WCI HIXP2

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

COMMENTS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Specific Gravity
Aliphatic Petroleum Distillates	0.768

PHYSICAL STATE: Liquid

ODOR: Hydrocarbon and citrus/peppermint odor.

COLOR: Clear, colorless to slightly reddish colored liquid.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

VAPOR DENSITY: Heavier than air.

BOILING POINT: 185°C to 215°C

FREEZING POINT: NDA = no data available.

MELTING POINT: No data available.

FLASHPOINT AND METHOD: 61°C (124°F) to 232.7°C (145°F) TAG CC

SOLUBILITY IN WATER: Soluble in hydrocarbon solvents. Insoluble in water.

EVAPORATION RATE: Slower than ether.

DENSITY: 6.88

SPECIFIC GRAVITY: 0.768 to 0.868

10. STABILITY AND REACTIVITY

STABLE: Yes

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE

DERMAL LD₅₀: > 2000 mg/kg (rat)

SKIN ABSORPTION: Solvent naphtha (Petroleum), medium aliphatic: Expected to be of low toxicity: LD50 greater than 2000 mg/kg, Rat.

ORAL LD₅₀: > 2000 mg/kg (rat)

WCI HIXP2

Notes: Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

NOTES: Low toxicity: LC50 greater than near-saturated vapor concentration. 1 hours, Rat.

EYE EFFECTS: Essentially non-irritating to eyes.

SKIN EFFECTS: May cause moderate irritation to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

CHRONIC: Cardiovascular system: chronic abuse of similar materials has been associated with irregular heart rhythms and cardiac arrest. Central nervous system: repeated exposure affects the nervous system.

CARCINOGENICITY

Notes: Repeated exposure causes skin tumor promotion in experimental animals.

REPEATED DOSE EFFECTS: Repeated Dose Toxicity: Kidney: Caused kidney effects in male rats which are not considered relevant to humans.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Absorbs to soil and has low mobility. Readily biodegradable. Oxidizes rapidly by photo-chemical reactions in air.

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

BIOACCUMULATION/ACCUMULATION: Has potential to bioaccumulate.

DISTRIBUTION: Mobility: Floats on water.

AQUATIC TOXICITY (ACUTE): Acute Toxicity for Solvent Naphtha (Petroleum), Medium Aliphatic:

Fish: Low toxicity: LC/EC/IC50 greater than 1000 mg/l

Aquatic Invertebrates: Low toxicity: LC/EC/IC50 greater than 1000 mg/l

Algae: Low toxicity: LC/EC/IC50 greater than 100 mg/l

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Combustible Liquid, N.O.S.

TECHNICAL NAME: (Naphtha solvent, paraffins)

PRIMARY HAZARD CLASS/DIVISION: Combustible liquid

WCI HIXP2**UN/NA NUMBER:** NA 1993**PACKING GROUP:** III**NAERG:** 128**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: This product contains the following components in concentrations above de minimis levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: Title III: No components were identified.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Aliphatic Petroleum Distillates	64742-96-7
Alkanes, C10-24-branched	289711-48-4

TSCA REGULATORY: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION**PREPARED BY:** COMPLIANCE DEPT.**HMIS RATING**

HEALTH	<input type="text"/>	1
FLAMMABILITY	<input type="text"/>	2
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	G

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered. Personal protection rating to be supplied by user depending on use conditions.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied

WCI HIXP2

regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.