

MATERIAL SAFETY DATA SHEET

BLANKET & ROLLER WASH M

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Tarr Acquisition, LLC
4115 W. Turney Avenue
Phoenix, AZ 85019

INFORMATION PHONE: (602) 233-2000

EMERGENCY PHONE: CHEMTREC 800-424-9300 (US) Day or night
International Call Collect CHEMTREC 202-483-7616

PRODUCT NAME: BLANKET & ROLLER WASH M

PRODUCT NUMBER: 2848

UPC NUMBER:

PREPARED BY: Patricia Rodabaugh

DATE PREPARED: 8/4/2004

LAST REVISION: 8/12/1998

SYNONYMS:



Portland, Oregon
Phoenix, Arizona
Auburn, Washington
Vancouver, Washington

Print Date: 10/14/2004

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	Weight %	OSHA PEL	ACGIH TLV	NOTE
Butoxyethanol, 2-	111-76-2	1-5	50 ppm (skin)	20 ppm (skin)	
D-Limonene	5989-27-5	1-5	n/a	n/a	
Solvent naphtha, light aromatic	64742-95-6	5-11	N/A	N/A	
Trimethylbenzene, 1,2,4,-	95-63-6	1-5	25 ppm	25 ppm	
Solvent naphtha, light aliphatic	64742-89-8	80-90	100 ppm	400 ppm (TWA)	

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Liquid is mildly irritating to the eyes. High vapor concentrations may also be irritating.

INHALATION: Vapors may be irritating to the nose, throat, and respiratory tract. High vapor concentrations may cause central nervous system (CNS) depression.

INGESTION: Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonia.

SKIN CONTACT: Liquid is mildly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SIGNS AND SYMPTOMS OF EXPOSURE:

Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonia may be evidenced by coughing, labored breathing and cyanosis.

4. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation persists, get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention immediately.

INGESTION: Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.* (see note to physician, page 5)

SKIN CONTACT: Remove contaminated clothing/shoes. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

AGGRAVATED MEDICAL CONDITIONS:

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.

SUPPLEMENTAL HEALTH INFORMATION:

Male rats exposed by prolonged and repeated inhalation to high vapor concentrations of similar solvents showed evidence of kidney damage. The relevance of this effect to humans is unknown.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 65 F

FLASH POINT METHOD USED: Tag Closed Cup

AUTOIGNITION: NDA

LEL: 0.007 **UEL:** 0.064

EXTINGUISHING MEDIA:

Use water fog, "alcohol" foam, dry chemical, or CO₂.

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mist or spray may be flammable at temperatures below the flash point.

COMBUSTION PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Remove all sources of ignition and provide ventilation. Wear protective equipment as given in Section 8. Dike around large spills to prevent spreading. Absorb small spills with inert material (clay, sand). Prevent contamination of surface waters.

7. HANLDING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-suppling respir. of an air-purifying respir. for organic vapors.

VENTILATION:

Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PROTECTIVE GLOVES:

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and

boots.

EYE PROTECTION:

Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear gloves and protective clothing which are impervious to this product for the duration of anticipated exposure, if there is potential for skin contact.

WORK / HYGENIC PRACTICES:

Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

ENGINEERING CONTROLS:

Use this material only in well ventilated areas.

EXPOSURE GUIDELINES:

Avoid prolonged or repeated breathing of vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUBILITY IN WATER: Solubility negligible in water

APPEARANCE AND ODOR: Blue colored liquid. Citrus odor.

BOILING POINT:	247 - 310 F	PERCENT VOLATILE:	100
VAPOR PRESSURE:	7.04 mmHg @ 20C	PH:	essentially neutral
EVAPORATION RATE:	Slower than ether	MOLECULAR WEIGHT:	NDA
POUNDS PER GALLON:	6.45	VAPOR DENSITY:	Heavier than air
SPECIFIC GRAVITY:	0.77	OTHER PROPERTIES:	VOC's: 6.451lb/gal,773.0926g/L
MELTING POINT:	NDA		
FREEZING POINT:	NDA		

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents.

INCOMPATIBILITY:

Strong oxidizers.

HAZARDOUS DECOMPOSITION OR BY PRODUCTS:

Carbon monoxide and unidentified organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID: Avoid heat, flame, and other sources of ignition.

11. TOXICOLOGY INFORMATION

This product may contain benzene (CAS No. 71-43-2) at a concentration less than 30 ppm. Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated, prolonged overexposure to solvents with permanent brain and nervous system damage.

12. ECOLOGICAL INFORMATION

Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name:	Flammable liquids, n.o.s., (petroleum distillates, 2-butoxy ethanol)	PACKING GROUP:	III
HAZARD CLASS:	3	GUIDE NUMBER:	128
UN NUMBER:	UN 1993	DOT CLASS:	Flammable Liquid

15. REGULATORY INFORMATION

All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

16. OTHER INFORMATION

HMIS INFORMATION: **HEALTH:** 1 **FLAMMABILITY:** 3 **REACTIVITY:** 0 **PROTECTIVE:** H

SARA Title III Information:

SARA 302: To the best of our knowledge, none of the chemicals in this product are listed as an Extremely Hazardous Substance under Section 302 of SARA Title III nor does this product contain any other such substances.

SARA 311/312: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

SARA 313: 2-Butoxyethanol (CAS 111-76-2) as a Glycol Ether Compound, Trimethylbenzene, 1,2,4- (CAS 95-63-6)

Supplemental Health Info.: Note to Physician: *If more than 2.0 ml per kg has been ingested and vomiting has not occurred, emesis should be induced with supervision. Keep victim's head below hips to prevent aspiration. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

Solvent naphtha (petroleum), light aromatic is a complex stream of predominately C8 to C10 hydrocarbons; the exact composition and concentrations will vary. Contains naphthalene 0.3 - .10% weight

Exposure of rats by inhalation to 2-butoxyethanol (2-BE) caused hemolysis, hemoglobinuria (blood in the urine) and a slight increase in liver weight. Other species, including man, were much less sensitive to hemolysis. The hemolytic effect seen in rats was transitory and/or reversible and not considered to be relevant to human health. Inhalation exposure of pregnant rabbits caused some lethality to the dam and fetus at 200 ppm, but there were no effects at 100 ppm and below. Inhalation exposure to pregnant rats caused irritancy to the dams and related fetotoxicity at 200 ppm and 100 pm, but there were no effects at 50 ppm and below. 2-BE did not cause birth defects in either study.

N/A = Not Applicable

NDA = No Data Available

Disclaimer

This information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.