

MATERIAL SAFETY DATA SHEET

Product Trade Name: ETHYLENE GLYCOL MONOBUTYL ETHER

Revision Date: 04-Dec-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: ETHYLENE GLYCOL MONOBUTYL ETHER
Synonyms: None
Chemical Family: Glycol Ether
Application: Solvent

Manufacturer/Supplier Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Ethylene glycol monobutyl ether	111-76-2	60 - 100%	20 ppm	50 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. May be absorbed through the skin. Repeated overexposure may cause liver and kidney effects. Combustible.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion If swallowed, induce vomiting immediately by giving two glasses of water and sticking fingers down throat; never give anything to an unconscious person. Get medical attention.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	144
Flash Point/Range (C):	62
Flash Point Method:	PMCC
Autoignition Temperature (F):	460
Autoignition Temperature (C):	238
Flammability Limits in Air - Lower (%):	1.1
Flammability Limits in Air - Upper (%):	12.7

Fire Extinguishing Media Carbon Dioxide, Dry Chemicals, Foam.

Special Exposure Hazards Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 2, Reactivity 0

HMIS Ratings: Health 2, Flammability 2, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Organic vapor respirator.

Hand Protection Neoprene gloves. Nitrile gloves. Butyl rubber gloves. Use Viton or 4H gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists. Do NOT wear contact lenses.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear colorless
Odor:	Mild
pH:	Not Determined
Specific Gravity @ 20 C (Water=1):	0.9
Density @ 20 C (lbs./gallon):	7.50
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	340
Boiling Point/Range (C):	171
Freezing Point/Range (F):	-94
Freezing Point/Range (C):	-171
Vapor Pressure @ 20 C (mmHg):	0.8
Vapor Density (Air=1):	4.07
Percent Volatiles:	100
Evaporation Rate (Butyl Acetate=1):	0.07
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	118.18

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers. Strong alkalis. Prolonged contact with aluminum.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.
Skin Contact	May cause skin irritation. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.
Eye Contact	May cause severe eye irritation.
Ingestion	Irritation of the mouth, throat, and stomach. May cause abdominal pain, vomiting, nausea, and diarrhea. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions.
Aggravated Medical Conditions	Skin disorders. Eye ailments. Liver and kidney disorders. Blood disorders. Lung disorders.

Chronic Effects/Carcinogenicity Prolonged or repeated exposure may cause liver, kidney and blood effects.
Prolonged or repeated exposure may cause fetal damage and testicular effects.

Other Information None known.

Toxicity Tests

Oral Toxicity: LD50: 550 mg/kg (Rat)

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

**Reproductive /
Developmental Toxicity:** Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability BOD(28 Day): 60% of COD

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined

Acute Crustaceans Toxicity: Not determined

Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT
Not restricted

Canadian TDG
Not restricted

ADR

Not restricted

Air Transportation**ICAO/IATA**

Not restricted

Sea Transportation**IMDG**

Not restricted

Other Transportation Information

Labels: None

15. REGULATORY INFORMATION**US Regulations****US TSCA Inventory** All components listed on inventory or are exempt.**EPA SARA Title III Extremely Hazardous Substances** Not applicable**EPA SARA (311,312) Hazard Class** Acute Health Hazard
Chronic Health Hazard
Fire Hazard**EPA SARA (313) Chemicals** This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:
Glycol Ethers//111-76-2**EPA CERCLA/Superfund Reportable Spill Quantity** Not applicable.**EPA RCRA Hazardous Waste Classification** If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.**California Proposition 65** All components listed do not apply to the California Proposition 65 Regulation.**MA Right-to-Know Law** One or more components listed.**NJ Right-to-Know Law** One or more components listed.**PA Right-to-Know Law** One or more components listed.**Canadian Regulations****Canadian DSL Inventory** All components listed on inventory or are exempt.**WHMIS Hazard Class** B3 Combustible Liquids
D2B Toxic Materials**16. OTHER INFORMATION****The following sections have been revised since the last issue of this MSDS**

Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****