ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ENVIRON TM/MC MV 46

Product code : ENVMV46P20, ENVMV46IBC, ENVMV46DRM.

ENVMV46DCT, ENVMV46, ENVMV46BLK

Manufacturer or supplier's details

Petro-Canada America Lubricants Inc.

115N Oak Park Avenue #1C Oak Park IL 60301-1366

United States

Emergency telephone

number

Suncor Energy: +1 403-296-3000;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use : ENVIRON MV is designed as heavy duty hydraulic power

transmission fluids for use in equipment, which must operate over a wide range of temperatures. Typically, ENVIRON MV Oils are used in hydraulic systems, machine tools, hydraulic presses, rotary compressors, and centrifugal pumps. The ashless, or zinc-free, additive system used in ENVIRON MV oils makes them especially suitable for use in environmentally

sensitive areas.

Prepared by : Product Safety: +1 905-804-4752

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

30.7	
Appearance	viscous liquid
Colour	Pale, straw-yellow.
Odour	Mild petroleum oil like.

GHS Classification

Not a hazardous substance or mixture.

GHS Label element

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry : Eye contact

Ingestion Inhalation Skin contact

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Aggravated Medical

Condition

: None known.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
lubricating oils (petroleum), C15-30, hydrotreated	72623-86-0	30 - 50 %
neutral oil-based		

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and

delayed

: First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), aldehydes, smoke and irritating vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.
 Ensure adequate ventilation.
 Evacuate personnel to safe areas.
 Material can create slippery conditions.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

Methods and materials for containment and cleaning up

: Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used.

Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Use only with adequate ventilation.

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

No special protective equipment required.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : Pale, straw-yellow.

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -48 °C (-54 °F)

Boiling point/boiling range : No data available

Flash point : 247 °C (477 °F)

Method: Cleveland open cup

Fire Point : No data available

Auto-Ignition Temperature : No data available

Evaporation rate : No data available

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.8526 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 45 cSt (40 °C / 104 °F)

8.2 cSt (100 °C / 212 °F)

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

SECTION 10. STABILITY AND REACTIVITY

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with reducing agents, oxidising agents, alkalis and

acids

Hazardous decomposition

products

: May release COx, H2S, methacrylate monomers, aldehydes,

alkyl mercaptans, sulfides, smoke and irritating vapours when

heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely Eye contact routes of exposure Ingestion

Inhalation Skin contact

Acute toxicity

Product:

Acute oral toxicity Remarks: No data available

Acute inhalation toxicity Remarks: No data available

Acute dermal toxicity Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

No data available

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 9,000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to bacteria : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

ENVIRON TM/MC MV 46



000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

49 CFR

Not regulated as a dangerous good

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : No OSHA Hazards

The components of this product are reported in the following inventories:

DSL On the inventory, or in compliance with the inventory

TSCA All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC On the inventory, or in compliance with the inventory
EINECS On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

ENVIRON TM/MC MV 46




000003001244

Version 2.0 Revision Date 2015/04/22 Print Date 2015/04/22

Further information

NFPA:



HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

For Copy of (M)SDS : Internet: lubricants.petro-canada.ca/msds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.