# MATERIAL SAFETY DATA SHEET

# EURO DIE SEALER / HARDENER

### 1 - IDENTIFICATION

**Distributor:** KerrLab

**Address:** 1717 West Collins Avenue

City, State, Zip: Orange, CA 92867 Telephone: 1-800-KERR-123

24-Hour Emergency: Chemtrec 1-800-424-9300

International 1-703-527-3887

**Date Prepared:** July 18, 2005

### 2 - COMPOSITION INFORMATION

### **Hazardous Ingredients**

	CAS#	<u>PEL</u>	<u>TLV</u>	<u>%</u>
Methyl Ethyl Ketone	78-93-3	200ppm	300ppm	45-75
Butyl Acetate	123-86-4	150ppm	150ppm	1-25

#### 3 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:  $79 \,^{\circ}\text{C} (174 \,^{\circ}\text{F})$ Specific Gravity (H<sub>2</sub>0 = 1): 1.0

Vapor Pressure (mm Hg): 105 @ 20 °C

Vapor Density (AIR = 1): N/D Freezing/Melting Point: N/A Solubility in Water: Non-soluble

Appearance and Odor: Clear liquid with solvent odor.

#### 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 30.2 °F

Flammability Limits: LEL: 11.5 UEL: 1.2

Extinguishing Media: Foam,, CO<sub>2</sub>, dry chemical, water fog; do not

use direct water stream

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus with full facepiece operated in pressure demand or other

positive pressure modes.

Unusual Fire and Explosion Hazards: Keep containers tightly closed. Isolate from heat, sparks, electrical equipment and open flames.

Eruption of containers may occur under fire conditions.

# **5 - REACTIVITY DATA**

Stability: Stable

Conditions to Avoid: Extremely high temperatures Incompatibility (Material to Avoid): Strong oxidizers Hazardous Decomposition Byproducts: Oxides of carbon

Hazardous Polymerization: Will not occur

### 6 - HEALTH HAZARD DATA

**Routes of Entry:** 

Skin: Prolonged contact can cause moderate irritation, defatting, and

dermatitis.

**Eyes:** Can cause severe irritation, redness, tearing, and blurred vision. **Inhalation:** Headache, fatigue, weariness, nausea, vomiting, dizziness,

stupor, disturbed vision, coughing, and unconsciousness.

Ingestion: Gastro-intestinal irritation, nausea, diarrhea, drowsiness,

loss of consciousness, state of shock, weak and rapid.

Carcinogenicity - NTP: No

IARC Monographs: No OSHA Regulated Carcinogen: No

### 7 - EMERGENCY FIRST AID PROCEDURES

**Skin:** Remove product with alcohol. Get medical attention.

Eyes: Flush with water for 10 to 15 minutes. Get medical attention.

Inhalation: Remove to fresh air. Get medical attention.

Ingestion: Do not induce vomiting. Keep victim warm and seek

medical attention

#### 8 - PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be taken in case material is released or spilled:  ${\tt Eliminate}$  all

sources of ignition, and flush small spills with water.

Waste Disposal Method: Incinerate in furnace where permitted or in

accordance with federal, state and local regulations

**Precautions to be taken in handling and storing:** Keep away from heat, sparks, and flame. Avoid breathing vapors or spray. Use

adequate ventilation. Do not expose to direct sunlight.

### 9 - CONTROL MEASURES

Respiratory Protection: Self-breathing apparatus in high

concentrations. **VENTILATION:** 

Local Exhaust: Adequate, local needed if not vented

Mechanical (General): Suitable

Protective Gloves: Neoprene or other gloves resistant to organic

solvents

Eye Protection: Safety glasses

## 10 - TRANSPORTATION INFORMATION

DOT, IATA, IMO:

Proper Shipping Name: Paint-related material

Hazard Class: 3

**Identification Number:** UN1263 **Packaging Group:** II

**Label:** Flammable Liquid

### 11 - SPECIAL INFORMATION

HMIS (Hazardous Material Identification System) Rating:

H2 F4 R0

[HMIS Hazard Index: 4 – Severe Hazard; 3 – Serious Hazard; 2 – Moderate Hazard; 1 – Slight Hazard; 0 – Minimum Hazard]