



MATERIAL SAFETY DATA SHEET

SECTION 1 — PRODUCT IDENTIFICATION

Product identifier: Everblum Spot Lifter

Product Code: 1024

Preparation Date: 9/17/04

Revision Date: April 2008

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Drive
Los Angeles, California
United States
90036
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

SECTION 2 — HAZARDOUS INGREDIENTS & OTHER COMPONENTS

<u>INGREDIENTS</u>	<u>% WEIGHT</u>	<u>EXPOSURE LIMITS</u>		<u>CAS #</u>
		<u>OSHA PEL</u>	<u>ACGIH TLV</u>	
Methyl Acetate	60-65	200 ppm	200 ppm	79-20-9
Acetone	4-7	1000 ppm	500 ppm	67-64-1
Hydrated Amorphous Silica	2-6	10 mg/m ³ (b)	6 mg/m ³ (b)	112926-00-8
Methanol	<2	200 ppm	200 ppm	67-56-1
Propane/n-Butane Blend	23-26	NE	800 ppm	68476-86-8

*NE: Not Established NA: Not Applicable (a): Mist (b): Total Dust (c): Respirable Dust

THIS PRODUCT MAY CONTAIN ONE OR MORE MATERIALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACTS OF 1986 AND OF 40 CFR 372. SEE SECTION 10 FOR SPECIFIC MATERIALS.

SECTION 3 — PHYSICAL DATA

APPEARANCE/ODOR: White liquid, ester-like odor.

SPECIFIC GRAVITY (Water = 1): <1

VAPOR PRESSURE: @ 70° f = 53 psi

VAPOR DENSITY (Air = 1): >1

BOILING POINT: 133° F

EVAPORATION RATE (Ethyl Ether = 1): <1

SOLUBILITY IN WATER: Yes

PERCENT VOLATILE by weight: <95%

SECTION 4 — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: Flammable aerosol. ASTM D-3065-94 Flame Extension Test: 12 inches

FLAMMABLE LIMITS: LEL: 1.0 (Propane/n-Butane) UEL: 16.0 (Methyl Acetate)

FLASH POINT: Concentrate only: <0° F Propellant only: Approx Minus (-) 120° F

SPECIAL FIRE FIGHTING PROCEDURES: Keep aerosol containers cooled with water fog to prevent bursting.

EXTINGUISHING MEDIA: Foam, CO₂, Dry Chemical

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure of aerosol cans to temp above 120° F may cause bursting.

SECTION 5 — HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: INHALATION: Yes DERMAL: Yes INGESTION: Yes

EFFECTS OF OVEREXPOSURE:

SKIN: Redness, irritation and defatting of skin. Dermatitis.

EYES: Redness, irritation and tearing.

INHALATION: Respiratory irritation, dizziness, weakness. Central nervous system depressant. Asphyxiant.

INGESTION: Gastrointestinal irritation, nausea, vomiting. Aspiration hazard if swallowed.

CARCINOGENICITY: NTP: No IARC: No ACGIH: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Pre-existing eye, skin and respiratory disorders.

EMERGENCY AND FIRST AID PROCEDURES:

SKIN: Remove contaminated clothing. Thoroughly wash with soap and water. Consult Physician if irritation persists.

EYES: Flush immediately with water for 15 minutes. Consult Physician if irritation persists.

INHALATION: Move to fresh air. Get medical attention if irritation persists.

INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION 6 — REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 120° F. Ignition sources.

HAZARDOUS DECOMPOSITION BY-PRODUCTS: Oxides of Carbon.

INCOMPATIBILITY: Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 7 — PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Large spills are unlikely due to aerosol packaging. Ventilate area. Soak up with absorbent material and dispose of accordingly.

WASTE DISPOSAL METHOD: When disposing of spent containers, do not puncture or incinerate. Dispose of in accordance with local, state, and federal regulations.

SECTION 8 — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use NIOSH approved self-contained breathing apparatus if TLV is exceeded.

VENTILATION: Sufficient local or mechanical ventilation to maintain vapour concentrations below TLV.

PROTECTIVE GLOVES: Solvent resistant.

EYE PROTECTION: Safety glasses with chemical splash-proof side shields, chemical goggles and/or face shield.

OTHER PROTECTIVE CLOTHING AND EQUIPMENT: Sufficient to prevent skin contact.

SECTION 9 — SPECIAL PRECAUTIONS

Keep out of reach of children. Avoid contact with skin, eyes or clothing. Avoid prolonged or repeated exposure to vapors. Do not store at temperature exceeding 120° F. Do not use or store around sources of heat, sparks or open flames. Do not puncture or incinerate.

SECTION 10 — SUPPLEMENTARY INFORMATION

SARA TITLE III:

Section 302 Extremely Hazardous Substances (40 CFR 355): None

Section 304 CERCLA Hazardous Substances (40 CFR 302): Acetone RQ: 5000 lbs.

Section 311/312 Hazard Class (40 CFR 370):

Immediate (X) Delayed (X) Fire (X) Reactive () Sudden Release of Pressure ()

Section 313 Toxic Chemicals (40 CFR 372): Methanol CAS #67-56-1 2%

VOC: 25%

DOMESTIC TRANSPORTATION INFORMATION: Consumer Commodity ORM-D

SHIPPING NAME: Aerosols, Class 2.1 UN#1950

RATING SCALE: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

HMIS CLASSIFICATION: Health: 2* Flammability: 4 Reactivity: 0

NFPA CLASSIFICATION: Health: 1 Reactivity: 0 Fire: 4

Periodically, user should request new MSDS to assure it matches current formulation. The above information is accurate to the best of our knowledge. However, since data, safety standards and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, no warranty is made either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. User should satisfy himself that he has all current data relevant to his particular use.