

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupation Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY

EZ-GO (120160)

*Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.*

Section I

D.O.T. Hazard Class: CONSUMER COMMODITY - ORM-D

Manufacturer's Name

Beaver Research Company

Emergency Telephone Number

1-800-255-3924 (Chem-Tel)

Address (Number, Street, City, State, and ZIP Code)

3700 E. Kilgore Road Portage, MI 49002

Telephone Number For Information

1-800-544-0133

HMIS RATING: (Based on Aerosol Concentrate): 0-Minimal; 1-Slight;
2-Moderate; 3-Serious; 4-Extreme

HEALTH 3 REACTIVITY 1

Date Prepared

03/21/03

FIRE.....4 Personal Protection: H

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS#	PEL	TWA TLV	313/CHEM	Skin	Carcinogen	% WT
Methylene Chloride	75-09-2	25ppm	25ppm	Yes	No	Yes	40-60
Toluene	108-88-3	100ppm	100ppm	Yes	Yes	No	10-20
Methanol	67-56-1	200ppm	200ppm	Yes	Yes	No	01-05
Liquified Petroleum Gas	68476-85-7	1000ppm	1000ppm	No	No	No	05-10

Section III - Physical/Chemical Characteristics

Boiling Point	96°F	Specific Gravity (H2O = 1) @75°F:	1.130
Vapor Pressure (mm Hg) (psig @70°F):	50	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water Slight	pH N/A	Total VOC % ~45%	

Appearance and Odor

Clear to opaque liquid, mild sweet solvent odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) ~70°F (T.O.C.)	Flammable Limits Extremely Flammable Spray	LEL NA	UEL N/A
---	---	-----------	------------

Extinguishing Media

Foam, CO2, Dry Media

Special Fire Fighting Procedures

Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards

Exposure to temperatures above 120°F may cause bursting.

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid	None
	Stable	X	

Incompatibility (Materials to Avoid)

Avoid contact with strong oxidizing agents, strong acids & bases and selected amines.

Hazardous Decomposition or Byproducts

Carbon Dioxide, Carbon Monoxide, Hydrogen Chloride and Phosgene.

Hazardous	May Occur	Conditions to Avoid	None
Polymerization	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes

Health Hazards (Acute and Chronic)

Eyes: May cause pain. May cause moderate eye irritation. May cause slight corneal injury. Vapors may irritate eyes.**Skin:** Frequent or prolonged contact may cause irritation.**Inhalation:** Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. Minimal toxicity.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NA	NA	NA

Signs and Symptoms of Exposure

NA

Medical Conditions Generally Aggravated by Exposure

NA

Emergency and First Aid Procedure

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open.If irritation persists get medical attention immediately. **Skin:** Wash with soap and water. If irritation persists seekmedical attention. **Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops giveartificial respiration. **Ingestion:** Do not induce vomiting. Seek medical attention immediately.**Section VII - Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

Waste Disposal Method

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

Precautions to be Taken in Handling and Storage

KEEP OUT OF THE REACH OF CHILDREN. For Industrial & Institutional Use Only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F. NFPA Code 30B Rating: Level 1 Aerosol.

Other Precautions

NA

Section VIII - Control Measures

Respiratory Protection (Specify Type)

None needed for proper use in accordance with label directions.

Ventilation	Local Exhaust	Yes	Special	NA
	Mechanical(General)	NA	Other	NA

Protective Gloves

Use chemical resistant gloves if hand contact will be made.

Eye Protection

Wear safety glasses or chemical proof goggles.

Other Protective Clothing or Equipment

N/A

Work/Hygienic Practices

No smoking.

The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

Forms by WindowChem Software (707)864-0845