

# Material Safety Data Sheet



## FM-200®

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : FM-200®  
Tradename/Synonym : FE-227  
2-Hydroperfluoropropane  
Propane, 1,1,1,2,3,3,3-Heptafluoro-  
HFC-227eaHP  
2-Hydroheptafluoropropane  
Heptafluoropropane  
2-H-heptafluoropropane  
1,1,1,2,3,3,3-Heptafluoropropane  
R-227  
R227  
HFC-227ea

MSDS Number : 130000036866

Product Use : Fire extinguishing agent

Manufacturer : DuPont  
1007 Market Street  
Wilmington, DE 19898

Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000)  
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)  
Transport Emergency : CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Misuse or intentional inhalation abuse may lead to death without warning.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
Rapid evaporation of the liquid may cause frostbite.

#### Potential Health Effects

Skin : Contact with liquid or refrigerated gas can cause cold burns and frostbite.



**FM-200®**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

- Eyes : Contact with liquid or refrigerated gas can cause cold burns and frostbite.
- Inhalation : Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.  
Other symptoms potentially related to misuse or inhalation abuse are: Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness.  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

**Carcinogenicity**

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No.	Concentration
1,1,1,2,3,3,3-Heptafluoropropane	431-89-0	100 %

**SECTION 4. FIRST AID MEASURES**

- Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Take off all contaminated clothing immediately. Consult a physician. Wash contaminated clothing before re-use. Treat for frostbite if necessary by gently warming affected area.
- Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician if necessary.
- Inhalation : Remove from exposure, lie down. Move to fresh air. Keep patient warm and at rest. Artificial respiration and/or oxygen may be necessary. Consult a physician.



**FM-200<sup>®</sup>**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

- Ingestion : Is not considered a potential route of exposure.
- General advice : Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.
- Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

**SECTION 5. FIREFIGHTING MEASURES**

- Fire and Explosion Hazard : The product is not flammable. Hazardous decomposition products : Hydrogen fluoride, Carbonyl fluoride
- Suitable extinguishing media : This material is a fire extinguishing agent.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- Safeguards (Personnel) : Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus. Keep upwind of leak - evacuate until gas has dispersed.
- Spill Cleanup : Ventilate area using forced ventilation, especially low or enclosed places where heavy vapors might collect.

**SECTION 7. HANDLING AND STORAGE**

- Handling (Personnel) : Do not breathe gas. Avoid contact with skin, eyes and clothing. Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Wash hands thoroughly after handling. Wash clothing after use. Decomposition will occur when product comes in contact with open flame or electrical heating elements. Handle in accordance with good industrial hygiene and safety practice.

# Material Safety Data Sheet



**FM-200<sup>®</sup>**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

**Storage** : Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Do not drag, slide or roll cylinders. Never attempt to lift cylinder by its cap. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.  
Separate full containers from empty containers. Keep at temperature not exceeding 52°C. Do not store near combustible materials. Keep container tightly closed in a dry and well-ventilated place. Store in original container. Protect from contamination. Avoid area where salt or other corrosive materials are present.

**Storage temperature** : < 52 °C (< 126 °F)

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls** : Use only with adequate ventilation. Keep container tightly closed.

**Personal protective equipment**

**Respiratory protection** : Wear NIOSH approved respiratory protection as appropriate.

**Hand protection** : Additional protection: Impervious gloves

**Eye protection** : Safety glasses with side-shields Additionally wear a face shield where the possibility exists for face contact due to splashing, spraying or airborne contact with this material.

**Skin and body protection** : Where there is potential for skin contact, have available and wear as appropriate, impervious gloves, apron, pants, jacket, hood and boots.

**Protective measures** : Self-contained breathing apparatus (SCBA) is required if a large release occurs.

### Exposure Guidelines

#### Exposure Limit Values

1,1,1,2,3,3,3-Heptafluoropropane

AEL \*

(DUPONT)

1,000 ppm

8 & 12 hr. TWA



**FM-200®**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

\* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Liquefied gas
Odor	: none
Melting point/range	: -131 °C (-204 °F)
Boiling point	: -16.3 °C (2.7 °F)
Vapour Pressure	: 4,547 hPa at 25 °C (77 °F)
Density	: 1.388 g/cm <sup>3</sup> at 25 °C (77 °F) (as liquid)

**SECTION 10. STABILITY AND REACTIVITY**

Stability	: Stable at normal temperatures and storage conditions.
Incompatibility	: Alkali metals Alkaline earth metals, Powdered metals, Powdered metal salts
Hazardous decomposition products	: Hazardous decomposition products , Hydrogen fluoride , Carbonyl fluoride, Carbon monoxide, Carbon dioxide
Hazardous reactions	: Polymerization will not occur.

**SECTION 11. TOXICOLOGICAL INFORMATION**

FM-200®	
Inhalation 4 h LC50	: > 788698 ppm , rat
Inhalation	: dog Cardiac sensitization
Dermal	: not applicable
Oral	: not applicable
Skin irritation	: No skin irritation, Not tested on animals



**FM-200®**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

		Not expected to cause skin irritation based on expert review of the properties of the substance.
Eye irritation	:	No eye irritation, Not tested on animals Not expected to cause eye irritation based on expert review of the properties of the substance.
Sensitisation	:	Does not cause skin sensitization., Not tested on animals Not expected to cause sensitization based on expert review of the properties of the substance.
		Did not cause sensitization on laboratory animals. There are no reports of human respiratory sensitization.
Repeated dose toxicity	:	Inhalation rat No toxicologically significant effects were found.
Carcinogenicity	:	Overall weight of evidence indicates that the substance is not carcinogenic.
Mutagenicity	:	Did not cause genetic damage in animals. Did not cause genetic damage in cultured mammalian cells. Did not cause genetic damage in cultured bacterial cells.
Reproductive toxicity	:	Animal testing showed no reproductive toxicity. Information given is based on data obtained from similar substances.
Teratogenicity	:	Animal testing showed no developmental toxicity.
Further information	:	Cardiac sensitisation threshold limit : 730190 mg/m3

**SECTION 12. ECOLOGICAL INFORMATION**

Aquatic Toxicity  
FM-200®

96 h LC50	:	Danio rerio (zebra fish) > 200 mg/l Information given is based on data obtained from similar substances.
96 h LC50	:	Oncorhynchus mykiss (rainbow trout) > 81.8 mg/l

# Material Safety Data Sheet



**FM-200®**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

Information given is based on data obtained from similar substances.

72 h EC50 : Pseudokirchneriella subcapitata > 114 mg/l  
Information given is based on data obtained from similar substances.

72 h EC50 : Pseudokirchneriella subcapitata > 118 mg/l  
Information given is based on data obtained from similar substances.

48 h EC50 : Daphnia magna (Water flea) > 200 mg/l  
Information given is based on data obtained from similar substances.

48 h EC50 : Daphnia magna (Water flea) > 97.9 mg/l  
Information given is based on data obtained from similar substances.

## Environmental Fate FM-200®

Biodegradability aerobic : 1 % OECD Test Guideline 301  
Not readily biodegradable.

Biodegradability aerobic : 5 % OECD Test Guideline 301  
Not readily biodegradable.

## SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : Can be used after re-conditioning. Recover by distillation or remove to a permitted waste disposal facility. Comply with applicable Federal, State/Provincial and Local Regulations.

Environmental Hazards : Empty pressure vessels should be returned to the supplier.

## SECTION 14. TRANSPORT INFORMATION

DOT UN number : 3296  
Proper shipping name : Heptafluoropropane  
Class : 2.2  
Labelling No. : 2.2  
IATA\_C UN number : 3296

# Material Safety Data Sheet



**FM-200<sup>®</sup>**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

	Proper shipping name	: Heptafluoropropane
	Class	: 2.2
	Labelling No.	: 2.2
IMDG	UN number	: 3296
	Proper shipping name	: Heptafluoropropane
	Class	: 2.2
	Labelling No.	: 2.2

## SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated Chemical(s) : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65 : Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known

## SECTION 16. OTHER INFORMATION

### HMIS

Health	:	1
Flammability	:	0
Reactivity/Physical hazard	:	0
PPE	:	Personal Protection rating to be supplied by user depending on use conditions.

FM-200 is a registered trademark of E. I. du Pont de Nemours and Company

Before use read DuPont's safety information.

For further information contact the local DuPont office or DuPont's nominated distributors.

<sup>®</sup> DuPont's registered trademark

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,



Material Safety Data Sheet



**FM-200®**

Version 2.1

Revision Date 07/11/2011

Ref. 130000036866

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.