

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

1. Identification

Product Identification

Product Identifier: FX-701 (FX701-60, FX701-60P)
Recommended Use: Oven-Dried Graded Silica Filler (Medium)
Use Restrictions: For industrial use only.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

FX-701 is a single component solid product; it has been assessed according to GHS. This Safety Data Sheet covers hazards and responses for the safe use and handling of this product.

GHS Classification



Physical Hazards:	Not Classified	
Health Hazards:	Carcinogenicity STOT, Single Exposure STOT, Repeated Exposure	Category 1A Category 3 (respiratory irritation) Category 2 (Lung)
Environmental Hazards:	Not Classified.	
Signal Word:	DANGER!	
Hazard Statements:	May cause cancer. May cause respiratory irritation. Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).	
Precautionary Statements:		
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust. Use only outdoors or in a well-ventilated area.	
Response:	If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call poison center/doctor if you feel unwell.	
Storage:	Store locked up. Store in a well-ventilated place. Keep cool.	
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.	

Hazards Not Otherwise Classified (HNOC)

Can form explosive air-dust mixtures, avoid creating dust.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

Composition – All concentrations are in percent by weight unless otherwise indicated.

Chemical Name	CAS Number	Weight %
Crystalline Silica, Quartz	14808-60-7	>99
Aluminum Oxide	1344-28-1	< 1
Iron Oxide	1309-37-1	< 0.1
Titanium Dioxide	13463-67-7	< 0.1

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

SIMPSON
Strong-Tie

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact: Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If you experience redness, burning, blurred vision, or swelling **consult a physician immediately.**

Skin Contact: Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. If rash or irritation occurs **consult a physician.**

Ingestion: Rinse mouth immediately. Do not induce vomiting. **Consult a physician.**

Inhalation: Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

Discomfort in the chest, shortness of breath, coughing.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Additional Information: Can form explosive air-dust mixtures, avoid creating dust.

Hazards during Fire-Fighting: During a fire, gases hazardous to health may be formed.

Fire-Fighting Procedures: Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Keep unnecessary personnel away. Avoid generating dust. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of dust. Ensure adequate ventilation. If the concentration of dust exceeds the permissible exposure limit wear a respirator.

Clean-Up Methods

Avoid dry sweeping. Do not use compressed air to clean spilled silica sand. Use water spraying/flushing or ventilated or HEPA filtered vacuum cleaning system. Dispose of in closed containers.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Avoid generating dust. Mechanical ventilation or local exhaust ventilation is recommended. Use all available work practices to control dust exposure, such as water sprays. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Do not breathe dust. Wear a respirator if dust concentrations exceed permissible exposure limits. Do not permit dust to collect and build up on work surfaces, use good housekeeping. Avoid contact with unhardened cement products. Observe good industrial hygiene practices.

Storage

Use dust collection to trap dust produced during loading and unloading. Store in a closed container away from incompatible materials (See Section 10 of the SDS). Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Protect against physical damage.

8. Exposure Controls / Personal Protection

Protective Measure: Wear appropriate personal protective equipment.

Eye Protection: Wear chemical splash goggles or safety glasses with side shield.

Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

- Skin and Body Protection:** Wear long sleeve shirt/long pants and other clothing as required to minimize contact. In case of dust production, dust-proof clothing. Avoid contact with unhardened cement products, if contact occurs wash immediately with soap and water.
- Respirator Protection:** Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of dust are expected to exceed exposure limits.
- General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Quartz (CAS 14808-60-7)	$\frac{10}{\%SiO_2 + 2} \text{ mg}/\text{m}^3$	0.025 mg/m ³ (respirable)	0.05 mg/m ³ (respirable)
Titanium Dioxide (CAS 13463-67-7)	15 mg/m ³ (Total dust)	10 mg/m ³	N/E

9. Physical and Chemical Properties

Physical State:	Solid	Freezing/Melting Point:	N/E
Form:	Powder	Boiling Point:	N/E
Color:	Tan	Flash Point:	N/A
Odor:	Characteristic	Evaporation Rate:	N/A
Odor Threshold:	N/E	Specific Gravity:	2.65
pH:	N/E	VOC:	0 g/L
Flammability:	N/A	U/L Flammability:	N/A
Vapor Pressure:	N/A	Vapor Density:	N/A
Solubility:	Insoluble	Kow:	N/A
Decomposition:	N/E	Viscosity:	N/A

10. Stability and Reactivity

Reactivity:	Stable and non-reactive under normal conditions of use and storage.
Chemical Stability:	Stable and non-reactive under normal conditions of use and storage.
Condition to Avoid:	Conditions which generate dust.
Substances to Avoid:	Hydrofluoric acid, fluorine, chlorine trifluoride, or oxygen difluoride.
Hazardous Reactions:	The product is stable if stored and handled as prescribed/indicated.
Decomposition Products:	None.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Expected to be a low ingestion hazard.
Inhalation:	Irritation to nose and respiratory tract.
Skin contact:	May cause mild skin irritation.
Eye contact:	Particles can cause corneal abrasion.

Information on Toxicological Effects

Acute toxicity:	Occupational exposure to the substance or mixture may cause adverse effects.
Skin corrosion/irritation:	Possible mild skin irritation.
Eye damage/eye irritation:	Direct contact may cause temporary eye irritation.
Respiratory sensitization:	Not a respiratory sensitizer.
Skin sensitization:	Not a skin sensitizer.
Germ cell mutagenicity:	No data available.

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

SIMPSON

Strong-Tie

Carcinogenicity:

May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7)

1 Carcinogenic to humans.

Titanium Dioxide (CAS13463-67-7)

2B Possibly Carcinogenic to Humans

NTP Report on Carcinogens

Quartz (CAS 14808-60-7)

Known To Be Human Carcinogen

Reproductive toxicity:

No data available.

Aspiration hazard:

No data available.

Specific target organ toxicity:

Single Exposure

No data available.

Repeated Exposure

Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation). Repeated or prolonged exposure to respirable silica dust will cause lung damage in the form of silicosis. Symptoms include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. This material is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Supporting Data

Persistence and degradability:

Not readily biodegradable.

Bioaccumulative potential:

Not expected to bioaccumulate.

Mobility in soil:

No data available.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Considerations

Waste Disposal of Substance:

Do not allow material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal:

Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transportation Information

FX-701 is not regulated for transport by the United States Department of Transportation (DOT), the International Air Transportation Association (IATA), or the International Maritime Dangerous Goods Code (IMDG).

Additional Information

Special precautions for user:

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Not applicable.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No
SARA 311/312 Hazardous chemical: Yes
SARA 313 (TRI reporting): Not regulated.

US State Right-To-Know Lists

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Rhode Island RTK
Quartz (14808-60-7)	Listed	Listed	Listed	
Titanium dioxide (CAS 13463-67-7)	Listed	Listed	Listed	

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or reproductive harm.

Component	Regulation	% In Blend (approx.)	Remark
Quartz (14808-60-7)	ACGIH	>99	Carcinogenic
Titanium Dioxide (13463-67-7)	ACGIH	< 0.1	Carcinogenic

Canada

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

WHMIS Classification


Class D-2A: Material Causing other toxic effects

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

International Inventories

Country	Inventory	On Inventory?
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States	Toxic Substances Control Act (TSCA) Inventory	Yes

"Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

"No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

FX-701 Oven-Dried Graded Silica Filler (Medium)

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

16. Other Information

Date Prepared or Revised:

December 2014


Supersedes:

September 2013

Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Additional Classifications

NFPA Ratings



HMIS Rating

HEALTH	2	PHYSICAL	0
FLAMMABILITY	0	PPE	B

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
CPR:	Controlled Product Regulations (Canada)
EPA:	Environmental Protection Agency (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2014 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

NSR