



M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : FPPF 3 MULTI PURPOSE SOLVENT

IDENTIFICATION NUMBER: **00130, 90130**

DATE PRINTED: 03/15/2014

PRODUCT USE/CLASS : MULTI PURPOSE SOLVENT

MANUFACTURED FOR:

FPPF CHEMICAL CORP.

117 WEST TUPPER STREET

BUFFALO, NY 14201

INFORMATION: 716 856-9607

FAX: 716 856-0750

EMERGENCY TELEPHONE: 800 424-9300
24 HOURS

EMERGENCY AGENCY: CHEMTREC
1-800-424-9300 (24 HOURS)

PREPARER: CUSTOMER SERVICE, PHONE: , PREPARE DATE: 3/15/2014

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WEIGHT %
01	HEXANES	64742-49-0	70-80
02	ISOPROPYL ALCOHOL	67-63-0	10-20
03	CARBON DIOXIDE	124-38-9	1-10

EXPOSURE LIMITS						
ACGIH		OSHA		COMPANY		SKIN
ITEM	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
01	50 PPM	N.E.	500 PPM		N.E.	YES
02	400 PPM	500 PPM	400 PPM	N.E.	N.E.	NO
03	5000 PPM	30000 PPM	5000 PPM	N.E.	N.E.	YES

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***: Causes eye irritation. Extremely flammable liquid and vapor. Vapors may cause flash fire or explosion. Aspiration

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION

hazard. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. MAY ENTER LUNGS AND CAUSE DAMAGE.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes. Causes irritation, redness, and pain

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: INHALING LARGE QUANTITIES OF MIST OR VAPORS MAY CAUSE SOME IRRITATION TO NOSE, THROAT, LUNGS. Headache. Dizziness.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. Aspiration hazard. Depression of the central nervous system can occur. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Repeated contact with skin may irritate pre-existing skin conditions.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION
INGESTION EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. Holding eyelids open, flush eyes with running water. Remove contact lenses if wearing and flush open eyes with running water for at least 15 minutes. Seek medical attention.

FIRST AID - SKIN CONTACT: Wash with soap and large amounts of water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash contaminated clothing before re-use.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Call physician immediately. If swallowed, call a physician or poison control

(Continued on Page 3)

SECTION 4 - FIRST AID MEASURES

center immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: -15 F
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT: 12.0 %

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Keep containers and surroundings cool with water spray. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use recommended personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Do not flush into surface water or sanitary sewer system.

SECTION 7 - HANDLING AND STORAGE

AEROSOL LEVEL: 3

HANDLING: Wash thoroughly after handling. Ensure all equipment is electrically grounded before beginning transfer operations.

(Continued on Page 4)

SECTION 7 - HANDLING AND STORAGE

STORAGE: Keep away from heat, sparks and flame. Keep from freezing. Keep container closed when not in use. KEEP OUT OF THE REACH OF CHILDREN!

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Impervious gloves and chemical splash goggles should be used when handling liquid. Wear impervious protective clothing, including boots, gloves, protective apron or coveralls to prevent skin contact.

EYE PROTECTION: Wear safety glasses with side shields or goggles when using this product.

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: 151 - 181 F	VAPOR DENSITY	: Is heavier than air
ODOR	: SOLVENT	ODOR THRESHOLD	: ND
APPEARANCE	: CLEAR	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O	: NEGLIGIBLE		

(Continued on Page 5)

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

FREEZE POINT : ND SPECIFIC GRAVITY: 0.7024
VAPOR PRESSURE : ND pH @ 0.0 % : NA
PHYSICAL STATE : AEROSOL VISCOSITY : ND
COEFFICIENT OF WATER/OIL DISTRIBUTION: ND
VOLATILE ORGANIC COMPOUNDS (VOCS): 5.63 lbs/gal, 674 grams/ltr

VOC, % (wt): 93.99%

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: AVOID OPEN FLAMES AND HIGH TEMPERATURES. Avoid contact with strong oxidizing agents. ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: Strong mineral acids and strong oxidizing agents. Halogens.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, ALDEHYDES, HYDROCARBONS. SMOKE, FUMES, OXIDES OF CARBON, NITROGEN, SILICA, AND VARIOUS METAL OXIDES ARE POSSIBLE DECOMPOSITION PRODUCTS.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT LD50: 5045 mg/kg

PRODUCT LC50: 72600 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	----- LD50 -----	----- LC50 -----
HEXANES	12705 MG/KG/RAT	150000 MG/M3/MOUSE
ISOPROPYL ALCOHOL	5045 MG/KG/RAT	72600 MG/M3/RAT
CARBON DIOXIDE	NE	NE

(Continued on Page 6)

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not evaluated.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT TECHNICAL NAME:

DOT HAZARD CLASS: ORM-D

HAZARD SUBCLASS:

DOT UN/NA NUMBER:

PACKING GROUP:

RESP. GUIDE PAGE:

DOT EXEMPTIONS:

DOT SPECIAL INSTRUCTIONS:

IMDG SHIPPING INFORMATION: UN1950

IMDG PROPER SHIPPING NAME: AEROSOLS

IMDG TECHNICAL NAME:

IMDG HAZARD CLASS: 2.1

HAZARD SUBCLASS:

PACKING GROUP:

FLASH POINT, C: -26

IMDG EXEMPTIONS: LIMITED QUANTITY

IMDG SPECIAL INSTRUCTIONS:

MARINE POLLUTANT (YES/NO): N

IATA SHIPPING INFORMATION: UN1950

(Continued on Page 7)

SECTION 14 - TRANSPORTATION INFORMATION

IATA PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE

IATA TECHNICAL NAME:

IATA HAZARD CLASS: 2.1

HAZARD SUBCLASS:

PACKING GROUP:

IATA EXEMPTIONS: LIMITED QUANTITY

IATA SPECIAL INSTRUCTIONS:

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
HEXANES	64742-49-0	70-80

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
No information is available.	

U.S. STATE REGULATIONS: AS FOLLOWS -

(Continued on Page 8)

SECTION 15 - REGULATORY INFORMATION

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
---------------------------	------------

No non-hazardous materials are among the top five ingredients.

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
---------------------------	------------

No non-hazardous ingredients are present at greater than 3%.

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
---------------------------	------------

No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: A, B5, D2B

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 07/17/06

REASON FOR REVISION: UPDATE PHYSICAL CHARACTERISTICS, AEROSOL LEVEL, TRANSPORTATION INFORMATION.

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

*** THIS MSDS IS NOT FOR REPRODUCTION OR DISTRIBUTION ***

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

<END OF MSDS>