MSDS Information

Section 1. CHEMICAL PRODUCT SECTION

Product Name: FD ELECTRONIC CLEANER 100% Freon TF

Product Number: DIS 1638 Aerosol

General Use:

Product Description:

MANUFACTURER: Tech Spray, Inc. For Chemical Emergency, Spill, Leak, Fire

P.O. Box 949 Exposure, or Accident Call CHEMTREC

Amarillo, TX 79105-0949 DAY OR NIGHT 1-800-424-9300.

PHONE: 806/372-8523 FAX: 806/372-8750

Section 2.	COMPOSITION /	′	INFORMATION	ON	INGREDIENTS		
CHEMICAL					C.A.S. Number	Weight	. %
1,1,2-Trichlor	otrifluoroethane				76-13-1	80	
(Freon TF)							
Chlorodifluoro	methane				75-45-6	18	
Carbon Dioxide					124-38-9	< 2	

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

Exposure Limits 8 Hours TWA (PPM)

OSHA PEL ACGIH TLV Supplier

1,1,2-Trichlorotrifluoroethane OSHA PEL 1000ppm

(Freon TF) ACGIH TLV 1000ppm

(STEL 1250ppm)

Chlorodifluoromethane OSHA TWA 1000ppm

ACGIH TLV 1000ppm

Carbon Dioxide OSHA PEL 10,000ppm

ACGIH TLV 5000ppm

Section 3. HAZARD IDENTIFICATION

Emergency Overview:

Potential Health Effects:

INHALATION: Major route of exposure. Vapor is heavier than air and can cause suffocation by reducing the available oxygen for breathing. Breathing high concentrations of vapor may cause light-headedness, giddiness, shortness of breath, confusion, and may lead to narcosis, cardiac irregularities,

unconsciousness or even death.

EYES: Liquid can cause slight, temporary irritation with slight temporary corneal injury. Vapors can irritate eyes.

SKIN: Not a corrosive or irritant; however, repeated or prolonged exposure can cause defatting of skin.

INGESTION: Single dose toxicity is low to moderate. If vomiting occurs the liquid can be aspirated into lungs, which can cause chemical pneumonia and systemic effects. Human psychotropic, gastrointestinal, and central nervous system effects possible.

Section 4.

FIRST AID MEASURES

Inhalation:

Move to fresh air in case of accidental inhalation of vapors. If victim has stopped breathing, give artificial respiration. Call for prompt medical attention.

Eye Contact:

Flush eyes with large amounts of water for 15 minutes or until irritation subsides. If irritation persist, get medical attention.

Skin Contact:

Remove Contaminated clothing (including shoes) and wash before reuse. Flush with large amounts of water. Use soap if available. If irritation persist, seek medical attention.

Ingestion:

Do not induce vomiting unless directed by a physician. If conscious and alert, give two glasses of water. Seek medical attention immediately.

Section 5. FIRE FIGHTING MEASURES

Flash Point & Method: None TCC Method

Flammable Limits: LEL: NA UEL: NA

Autoignition Temperature:

GENERAL HAZARD:

Aerosol cans may erupt with force at temperatures above 120 degrees F. FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear self contained, positive-pressure breathing apparatus and avoid skin contact.

FIRE FIGHTING EQUIPMENT:

Water, foam, dry chemical, carbon dioxide. HAZARDOUS COMBUSTION PRODUCTS:

Smoke, fumes and oxides of carbon.

______ Section 6. ACCIDENTAL RELEASE MEASURES LAND SPILL: Evacuate area. Ventilate area well and avoid breathing vapors. Vapor concentration will be highest along floor and in low lying areas. Pick up liquid on suitable absorbent and store in sealed containers. WATER SPILL: ______ Section 7. HANDLING AND STORAGE STORAGE TEMPERATURE: Ambient STORAGE PRESSURE: Atmospheric **GENERAL:** Keep container closed when not in use. Store in cool, well ventilated place out of direct sunlight and away from incompatible materials. (See STABILITY AND REACTIVITY Section 10.) Follow all MSD Sheet and Label warnings even after container is emptied. ______ EXPOSURE CONTROL / PERSONAL PROTECTION Section 8. Engineering Controls: Local Exhaust ventilation acceptable. (X) Mechanical ventilation recommended. () Use explosion-proof ventilation equipment. Do not use in confined spaces without mechanical ventilation equipment. See section 2 for component exposure guidelines.

Personal Protection:

RESPIRATOR:

If concentrations are over the exposure limit and are known, air purifying respirator with Organic Vapor Cartridges may be acceptable. Refer to cartridges for acceptable levels. If concentrations are over exposure limit and are unknown, use a supplied air respirator.

HAND PROTECTION:

(X)	Gloves recommended	d				
	(X) Solvex	() Neoprene				
	() Butyl	() Buna				
	() Natural Latex	() Cotton/Jerse	έY			
EYE PROT	rection:					
(X) Sa	afety Glasses ()	Chemical Goggles	() Fu	ll Face	Shield

OTHER RECOMMENDATIONS:

OTHER RECOMMENDATIONS:	
() Rubber Boots () Splash-r	proof chemical resistant suit/apron
(, 51	
Section 9. PHYSICAL AND CHEMIC	
Density NIF	-
Boiling Point 47C / 116F	
_	% Solids 0
Vapor Density (Air=1): 6.5	Evaporation Rate (H2O=1) NIF
Solubility in Water 0	Viscosity N/A
	Physical State LIQUID
Non-Exempt VOC (g/l) NIF	OdorNIF
Appearance: Clear water-white mobile li	quid with slight ethereal odor.
	:======================================
Section 10. STABILITY AND RE	EACTIVITY
GENERAL:	
STABLE	
INCOMPATIBLE MATERIALS AND CONDITIONS	TO AVOID:
Contact with open flame, heat.	
Reactive alkali metals, strong aci	ds & bases.
HAZARDOUS DECOMPOSITION:	
Hydrogen chloride, phosgene, chlorine,	carbon dioxide, and carbon monoxide.
Section 11. TOXICOLOGICAL I	NFORMATION
RESULTS OF COMPONENT TOXICITY TEST PER	RFORMED:
Information not available.	
HUMAN EXPERIENCE:	
Information not available.	
Section 12. ECOLOGICAL INF	ORMATION
Section 12. ECOLOGICAL INF	
FURTHER INFORMATION:	
FURTHER INFORMATION:	
FURTHER INFORMATION:	FORMATION
FURTHER INFORMATION: Information not available.	FORMATION
FURTHER INFORMATION: Information not available. Section 13. RCRA 40 CFR 261 Classification:	FORMATION ERATIONS
FURTHER INFORMATION: Information not available. Section 13. RCRA 40 CFR 261 Classification: Federal, State, and Local laws governing	FORMATION ETERMINIS Ing disposal of materials can differ.
FURTHER INFORMATION: Information not available. Section 13. RCRA 40 CFR 261 Classification:	FORMATION ETERMINIS Ing disposal of materials can differ.
FURTHER INFORMATION: Information not available. Section 13. RCRA 40 CFR 261 Classification: Federal, State, and Local laws governing	FORMATION ETERMINIS Ing disposal of materials can differ.
FURTHER INFORMATION: Information not available. Section 13. DISPOSAL CONSIDE RCRA 40 CFR 261 Classification: Federal, State, and Local laws governing Ensure proper disposal compliance with	FORMATION ERATIONS Ing disposal of materials can differ. In proper authorities before disposal.
FURTHER INFORMATION:	FORMATION ERATIONS Ing disposal of materials can differ. In proper authorities before disposal.
FURTHER INFORMATION:	FORMATION ERATIONS Ing disposal of materials can differ. In proper authorities before disposal.
FURTHER INFORMATION:	FORMATION ERATIONS Ing disposal of materials can differ. In proper authorities before disposal.

Hazard Class:

```
Packaging Group:
         UN Number:
         Limitations:
     IATA
         Proper Shipping Name:
         Hazard Class:
         Packing Group:
         UN Number:
         Limitations:
    IMO
         Proper Shipping Name:
         Class:
         UN Number:
         Packaging Group:
         EMS:
         MFAG:
         Marine Pollutant:
         Canadian TDG:
______
Section 15.
                         REGULATORY INFORMATION
UNITED STATES FEDERAL REGULATIONS:
    MSDS complies with OSHAs Hazard Communication Rule, 29 CFR 1910.1200.
    CERCLA/SUPERFUND, 40 CFR 117, 302:
       --- None of the chemicals are Superfund hazards ---
    SARA SUPERFUND AND REAUTHORIZATION ACT OF 1986
    TITLE III Sections 302, 311, 312 and 313:
        Section 302 - Extremely hazardous substances (40 CFR 355):
            --- None of the chemicals are Section 302 hazards ---
        Section 311/312 - Material Safety Data Sheet Requirements (40 CFR 370)
            ( ) By our hazard evaluation, this product is non-hazardous.
            (X) By our hazard evaluation, this product is hazardous.
                should be reported under the following EPA hazard.
                ( ) Immediate (acute) health hazard
                ( ) Delayed (chronic) chronic health hazard
                ( ) Sudden release of pressure hazard
                ( ) Reactive hazard
        Section 313 - List of Toxic Chemicals (40 CFC 372)
            This product contains the following chemicals (at levels of 1% or
            greater) which are found on the 313 list of Toxic Chemicals.
                                                C.A.S. NUMBER
            CHEMICAL
                                                                WEIGHT %
               --- None of the chemicals are 313 Toxic Chemicals ---
    TOXIC SUBSTANCE CONTROL ACT (TSCA): All substances are TSCA Listed.
```

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA 40 CFR 261) Subpart C & D: Refer to Section 11. for RCRA classification.

FEDERAL WATER POLLUTION CONTROL ACT, CLEAN WATER ACT, 40 CFR 401.15 (FORMERLY SECTION 307), 40 CFR 116 (FORMERLY SECTION 311)

This product contains the following chemicals which are listed: C.A.S. NUMBER WEIGHT %

CLEAN AIR ACT: --- No Information ---

STATE REGULATIONS:

CALIFORNIA PROPOSITION 65:

This product contains the following ingredients which appear on the California proposition 65 list:

CHEMICAL

C.A.S. NUMBER WEIGHT %

--- None of the chemicals are on the Proposition 65 list ---

INTERNATIONAL REGULATIONS:

CANADA WHIMS: NIF

EUROPE EINECS NUMBERS: NIF

Section 16.

OTHER INFORMATION

LABEL INFORMATION:

European risk and Safety Phrases: NIF

European Symbols Needed: NIF Canadian WHIMS Symbols: NIF

NFPA HAZARD RATING:

() Fire () Health () Reactivity

REVISION DATES, SECTIONS, REVISED BY:

27-JLY-94, CONVERTED TO ANSI STANDARD, B. RIFFEL

ABBREVIATIONS USED IN THIS DOCUMENT:

NE - Not Established, NA - Not Applicable, NIF - No Information Found

REFERENCES:

Code of Federal Regulations (CFR)

The Sigma-Aldrich Library of Regulatory and Safety Data Chemical Guide and OSHA Hazard Communication Standard Various Federal, State & Local Regulations

To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, Inc. or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information

contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.