Date Printed 3/19/08

JET CLEANER Page 1

## F. W. DUNN COMPANY MATERIAL SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME (as it appears on label) Fresh Start 2000 Jet Cleaner

NPCA/HMIS Ratings: Health 2; Flammability 0; Reactivity 0 NFPA Ratings: Health 2; Flammability 0; Reactivity 0

DISTRIBUTED BY:

FWDUNN COMPANY Manufactured by M & P Industries, Inc. EMERGENCY TELEPHONE: 1-304-736-4046 (plant) 1-800-535-5053 (INFOTRAC 24 HOUR EMERGENCY NUMBER)

ADDRESS (NUMBER, STREET, CITY, STATE, & ZIP CODE)

6144 Little Seven Mile Road, Huntington, WV. 25702

HAZARDOUS MATERIAL DESCRIPTION:

PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO., PACKING GROUP

Sodium hydroxide solution, 8, UN1824 II

ADDITIONAL HAZARD CLASSES (AS APPLICABLE)

CHEMICAL FAMILY

**FORMULA** 

Not applicable

Not applicable

Mixture

### SECTION II - PRODUCT IDENTIFICATION

- Table Z-1-A -

STEL CEILING CARCINOGEN TWA

mg/M3mg/M3 mg/M3

1310-73-2

**CHEMICAL NAME** CAS REGISTRY NO. %W Sodium hydroxide

111-76-2\*

1-2 2-Butoxyethanol 5-6

no

120 пô

\*This substance is subject to the separting equinaments of Section 212 of the Emergency Planning and Community Right-to-Know Act of 1986 (SARA) and of 40 CFR 372.

#### SECTION III -- PHYSICAL DATA

**BOILING POINT** 

PERCENT SOLID BY WEIGHT

SPECIFIC GRAVITY (H20=1)

1.050 @ 25° C

VAPOR PRESSURE

**EVAPORATION RATE** 

Unknown

211 Deg. F

Unknown

**VAPOR DENSITY** 

Butvl Acetate = 1: <1

**SOLUBILITY IN WATER** 

PH

APPEARANCE AND ODOR

Complete

12.8 - 13.2

Fluorescent green Liquid, slight butyl odor

#### SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: Not applicable METHOD: ASTM - D92

FLAMMABLE LIMITS: Not applicable LEL: Not applicable UEL: Not applicable

**EXTINGUISHING DATA:** Water fog, carbon dioxide, foam, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Cool containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known - This product is water based and presents no unusual fire bazards.

Date Printed 3/19/08

**JET CLEANER Page 2** 

# F. W. DUNN COMPANY MATERIAL SAFETY DATA SHEET

SECTION V – HEALTH HAZARD DATA	
Litation Clain contact may cause dryin	duct is a corrosive material. Airborne mists may cause respiratory tract g (product is a defatter) and dermatitis. Eye contact may result in s. Butoxyethanol is absorbed through the skin which may affect the liver,
THRESHOLD LIMIT VALUE: Not esta	blished.
PRIMARY ROUTES OF ENTRY: IN	HALATION X SKIN CONTACT X OTHER (SPECIFY)
CONDITIONS AGGRAVATED BY US	E. None known.
If irritation or redness occurs get medical artificial respiration should be started. Gmilk. Do not induce vomiting. Get medical	Skin contact - Wash with soap and water. Remove contaminated clothing. I attention. Inhalation - Remove to fresh air. If breathing has stopped let medical attention. Ingestion - If conscious, give two glasses of water or cal attention immediately.  CTION VI - REACTIVITY DATA
STABILITY: UNSTABLE X	CONDITIONS TO AVOID: Not Applicable
INCOMPATABILITY (MATERIALS T	O AVOID): Strong acids / strong oxidizers
HAZARDOUS DECOMPOSITION PR	ODUCTS: None
HAZARDOUS POYMERIZATION:	May occur Will not occur. X
SECTION VII – SPILL OR LEAK PROCEDURES	

STEPS TO BE TAKEN IN CASE MASTERIAL IS RELEASED OR SPILLED: Stop leaks and contain spills. Remove as much material as possible and then flush remaining material with a large amount of water and drain to sanitary sewer. Alternative method is to use absorbents such as pads, socks, or dry chemical adsorbents. Put adsorbed material into proper waste disposal container with lid tightly closed. Larger spills may be taken up with dikes, pump or vacuum and finished off with dry chemical absorbent after free liquid is recovered.

**DISPOSAL METHODS:** This material is water-soluble and water-dilutable. Surfactants used are biodegradable. High pH of product could cause fish kills when high local concentrations exist momentarily but no long-term injurious effects to waterways will result. Follow all local, state, and federal regulations.