



MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Friction Material, Brake Lining	Manufacturer: Federal Mogul Corporation 26555 Northwestern Highway Southfield, MI 48033
Product Number: No. 0236	24hr Emerg # (Infotrac): 1-800-535-5053
MPV2002, MVP2007, MVP2008, MVP2009, MVP2011, MVP 2012	International: 001-352-323-3500
	Non-Emerg #: 248-354-9844

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Although several of the ingredients used to formulate this product may be hazardous in their raw state, the manufacturing process results in a solid, infusible form, binding or otherwise rendering the mixture inert. We have identified below those hazardous constituents present in quantities greater than 1% (0.1% for carcinogens) that may be released from the product by overheating, burning, machining, or abrading.

Ingredient*	CAS No.:	% Weight	OSHA PEL	ACGIH TLV (2004)
Acrylic Fibers	24980-62-9	>1	None Established	1 fiber/cc ^a
Acrylic Fibers	25014-41-9	>1	None Established	1 fiber/cc ^a
Alumina	1344-28-1	>1	15 mg/m ³ ^{b, c}	10 mg/m ³
Antimony trisulfide	1345-04-6	>1	None Established	None Established
Aramid Fiber	26125-61-1	>1	1 fiber/cc ^a	1 fiber/cc ^a
Barytes	7727-43-7	>1	15 mg/m ³ ^c	10 mg/m ³
Brass fiber	None	>1	None Established	None Established
Butyl Rubber (ground)	9010-85-9	>1	None Established	None Established
Calcium carbonate (limestone)	1317-65-3	>1	15 mg/m ³ ^c	10 mg/m ³
Calcium hydroxide (hydrated lime)	1305-62-0	>1	15 mg/m ³ ^c	5 mg/m ³
Carbon (purified)	7440-44-0	>1	None Established	None Established
Cashew Nut Shell	69012-00-6	>1	None Established	None Established
Friction Dust (filler)	68647-81-4	>1	None Established	None Established
Friction Dust (filler)	68333-94-8	>1	None Established	None Established
Cellulose	9004-34-6	>1	15 mg/m ³ ^c	10 mg/m ³
Coal, sea	68409-95-0	>1	None Established	None Established
Coke (petroleum)	64743-05-1	>1	None Established	None Established
Copper (fiber)	7440-50-8	>1	1 mg/m ³	1 mg/m ³
Graphite	7782-42-5	>1	15 mppcf ^d	2 mg/m ³ (respirable fraction)
Iron Powder (as Iron)	7439-89-6	>1	None Established	None Established
Iron Pyrite (as Iron)	1317-37-9	>1	None Established	None Established
Linseed oil – 100% solids	67746-08-1	>1	None Established	None Established
Limestone	546-93-0	>1	15 mg/m ³ ^c	10 mg/m ³
Magnesium oxide	1309-48-4	>1	15 mg/m ³ ^c	10 mg/m ³
Magnesium oxide (fused silica)	60676-86-0	>1	10 mg/m ³ (respirable % SiO ₂ + 2 fraction)	0.1 mg/m ³ (respirable fraction)
Mica	12001-26-2	>1	20 mmpcf, <1% silica	3 mg/m ³ (respirable fraction)
Mineral Fibers	65997-17-3	>1	1 fiber/cc ^a	1 fiber/cc ^a
Mineral Fiber	287922-11-6	>1	None Established	None Established
Mineral Fiber	194718-72-4	>1	None Established	None Established
Molybdenum disulfide	1317-33-5	>1	None Established	None Established
Mullite	1302-93-8	>1	None Established	None Established
Mullite	7631-86-9	>1	None Established	None Established
Nitrile Rubber (crumb)	9003-18-3	>1	None Established	None Established
Potassium titanate	12056-51-8	>1	None Established	None Established
Potassium oxide	12136-45-7	>1	None Established	None Established
Resin, powdered novalac	9003-35-4	>1	None Established	None Established
Silica, Crystalline Quartz	14808-60-7	>1	10 mg/m ³ (respirable % SiO ₂ + 2 fraction)	0.1 mg/m ³ (respirable fraction) (A2)
Steel Fiber	65997-19-5	>1	None Established	None Established
Sulfur	7704-34-9	>1	None Established	None Established
Tires, ground peel	139497-04-4	>1	None Established	None Established

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS (continued)

Titanium dioxide	13463-67-7	>1	15 mg/m ^{3 c}	10 mg/m ³
Vermiculite	1318-00-9	>1	None Established	None Established
Wollastonite	13983-17-0	>1	None Established	None Established
Zinc powder	7440-66-6	>1	None Established	None Established
Zirconium oxide	1314-23-4	>1	5 mg/m ³ (as zirconium)	5 mg/m ³ (as zirconium)
Zircon sand	14940-68-2	>1	5 mg/m ³ (as zirconium)	5 mg/m ³ (as zirconium)

- *: The products listed in Section 1 do not contain all of the ingredients listed above
a.: As synthetic vitreous fibers per cubic centimeter of sampled air
b.: Milligrams of compound per cubic meter of sampled air, on a weight-to-volume basis
c.: As total particulate (not otherwise regulated)
A2: ACGIH has classified the compound as a suspected human carcinogen.
d.: Millions of particles per cubic foot of sampled air

OSHA Regulatory Status: This product is classified as hazardous under OSHA regulations.

SECTION 3: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Shipped friction materials are not considered hazardous, but operations (overheating, burning, machining, abrading, or riveting) that can create airborne dust should be avoided. Such operations could cause exposures in excess of permissible exposure limits for the respective ingredients and should be considered hazardous.

Prolonged or repeated exposure may cause lung injury, including silicosis. This product may contain crystalline silica. Crystalline silica has been classified by IARC as a known human carcinogen. Some human studies indicate potential for lung cancer from crystalline silica exposure. Risk of injury depends on duration and level of exposure. Long-term exposures that result in silicosis may result in additional health effects.

POTENTIAL HEALTH EFFECTS

Inhalation: Dust may cause irritation. Fume produced at high temperatures may cause metal fume fever, a 24-to 48-hour "flu-like" illness. Repeated inhalation of dust may affect a variety of organs (See Chronic Section below).

Skin: May cause irritation. Prolonged skin contact may cause skin sensitization and/or dermatitis.

Eye: Dust may cause irritation and redness. Particles may scratch the eye.

Ingestion: Ingestion may cause irritation, nausea, vomiting, and diarrhea.

Chronic: Repeated inhalation of dust may cause fibrotic lung disease and increased risk of sinus and respiratory cancer. Long-term dust inhalation may also harm the nervous, gastrointestinal, renal (kidneys), and hematological (blood) systems.

Carcinogenicity:

	COMPONENT NTP IARC OSHA
Silica (Crystalline)	Yes 1 Yes
Mineral Fibers (respirable)	No 2B No
Mineral Wool/Fiber*	Yes 3 No
Acrylic Fiber, Aramid Fiber, Antimony sulfide	No 3 No
Titanium dioxide	No 3 No
	COMPONENT NTP IARC OSHA
Alumina, Barytes, Brass, Butyl Rubber, Calcium carbonate, Cashew Resin-Cured, Cashew Resin (filler), Cellulose, Coal, Coke, Copper, Graphite, Ground tire peel, Hydrated Lime, Iron Powder, Iron pyrite, Linseed Oil, Magnesite (limestone), Magnesium oxide, Mica, Molybdenum sulfide, Mullite, Nitrile Rubber, Resin-powdered novalac, Potassium titanate, Potassium oxide, Steel Fiber, Sulfur, Vermiculite, Wollastonite, Zinc, Zirconium oxide, Zircon sand	
	No
	No
	No
* The mineral fiber used has been classified as biosoluble and exonerated under ECC directive 97/69/EC, Note Q. The IARC has recently changed the classification of Mineral Fibers to Group 3 "unclassifiable" from Group 2 "possible carcinogen."	
Signs and Symptoms: Skin may become red and itchy with repeated contact. Metal fume fever is characterized by chills, fever, muscle aches, and metallic taste. Anemia may cause dizziness and fatigue. Muscle weakness, fatigue, irritability, poor memory, and headache may indicate neurological effects. Gastrointestinal effects may result in nausea, abdominal pain, diarrhea, constipation, nausea and vomiting.	
Medical Conditions Aggravated by Exposure: Overexposure may aggravate pre-existing skin, respiratory, kidney, blood, gastrointestinal and nervous system disorders.	
Target Organs: Skin, eyes, lungs, gastrointestinal system.	

POTENTIAL HEALTH EFFECTS
Symptoms and Effects of Exposure to Selected Individual Components

ACRYLIC FIBERS

Inhalation hazards – Overexposure to respirable fibers by inhalation may cause mild and temporary upper respiratory irritation with discomfort or cough. The toxicological properties of this material have not been fully investigated. The oral and dermal animal testing LD₅₀ values were greater than 5.0 g/kg and 2.0 g/kg, respectively.

Other hazards – Skin sensitization has not been observed in human tests. The mechanical action of fibers may cause slight skin irritation at clothing binding points and mild irritation of the eyes and nasal passages.

ALUMINA

Inhalation hazards – Exposure to alumina may cause coughing and shortness of breath.

Chronic: Prolonged exposure may affect breathing capacity.

Other hazards – Ingestion is not recommended, but adverse effects have not been reported. Alumina is not absorbed through the skin, but contact may cause abrasion. Dust may irritate eyes.

ANTIMONY COMPOUNDS

Inhalation hazards – There are no reported serious health risks from exposure other than a possible change in blood pressure. Prolonged exposure may cause irritation of the nose, throat, and mouth.

Other hazards – Skin or eye contact may result in coughing, dizziness, headache, nausea, vomiting, diarrhea, stomach cramps, and insomnia.

ARAMID FIBERS

Inhalation hazards – Overexposure to respirable fibers by inhalation may cause mild temporary upper respiratory irritation, with discomfort or cough. Based on animal testing, prolonged and repeated exposure to excessive concentrations of respirable fibers may cause permanent lung injury.

Other hazards – Skin sensitization has not been observed in human tests. The mechanical action of fibers may cause slight skin irritation at clothing points and mild irritation of the eyes and nasal passages.

Symptoms and Effects of Exposure to Selected Individual Components (continued)

BARYTES

Inhalation hazards – Should be treated as a nuisance dust. Exposure to barium sulfate may cause paroxysmal coughing, wheezing, difficult breathing, and upper respiratory tract irritation.

Other hazards – Adverse effects have not been reported from ingestion. Eye contact may cause temporary discomfort and irritation.

BRASS AND COPPER

Inhalation hazards – Acute: may produce irritation of the nose and/or trachea. May produce acute gastroenteric symptoms resulting in vomiting or inflammation and may cause metal fume fever.

Chronic: prolonged exposure may cause injury to liver, kidneys or spleen; anemia may develop.

Chronic toxicity is reportedly confined to those persons suffering from pre-existing Wilson's disease.

Other hazards – Copper dusts and mists are eye and mucous membrane irritants and skin sensitizers.

Acute exposure may cause metallic taste and nasal ulceration and perforation. Prolonged skin contact may produce sensitization dermatitis. Exposure may result in discoloration of the skin and hair. Ingestion of copper compounds may cause vomiting and collapse. Hemolysis, jaundice, anuria, hypertension and convulsions characterize acute poisoning.

BUTYL RUBBER

A reclaimed material that encapsulates various chemicals in a fully cured butyl rubber matrix.

Inhalation hazards – May cause mild irritation of the respiratory tract.

Other hazards – Eyes – may cause mild transient eye irritation.

CALCIUM CARBONATE

A white, finely pulverized powder with no odor.

Inhalation hazards – Limestone dust is considered a nuisance dust. Prolonged exposure may cause irritation to throat and lungs. Silica content is not considered high enough to cause silicosis unless exposures are extremely high and prolonged.

Other hazards – Eyes – may cause mild transient eye irritation.

CASHEW NUT SHELL

Inhalation hazards – Cured cashew particles are generally considered to be a nuisance dust, but prolonged exposure may cause irritation of nasal and respiratory tracts leading to sensitization. In the unlikely event of formalin vapors and/or uncured cashew liquid being present, this may cause dermatitis and could lead to a form of nasal cancer.

CELLULOSE

A non-toxic, fibrous flock, practically odorless.

Inhalation hazard – Acute: dryness of nose, eye irritation, and nasal obstruction. Chronic: no data available.

COAL

Inhalation hazards – May irritate mucous membranes by mechanical or chemical means. May cause lung inflammation.

Other hazards – May cause slight to moderate eye irritation. May cause skin irritation.

COKE, CALCINED

Inhalation hazards – May irritate mucous membranes by mechanical or chemical means. May cause lung inflammation.

Other hazards – May cause slight to moderate eye irritation. May cause skin irritation.

GRAPHITE

Inhalation hazards – Acute: exposure may result in cough, dyspnea, black sputum, and fibrosis. Chronic: Prolonged exposure may cause pneumoconiosis. It is reported that diseases of the respiratory and cardiovascular system may be aggravated by exposure.

Symptoms and Effects of Exposure to Selected Individual Components (continued)**CALCIUM HYDROXIDE (HYDRATED LIME)**

Inhalation hazards – Dust may cause irritation of nasal and respiratory passages.

Other hazards – Lime is a strong eye irritant, and may cause corrosive damage and blindness. Exposure to dust may cause severe skin irritation, drying and burning, particularly to damaged skin. Swallowing excessive amounts may damage mucous membranes and the digestive system. There are no known chronic hazards.

IRON DUST (IRON OXIDE)

Inhalation hazards – Repeated or prolonged exposures to iron dust may cause a form of benign pneumoconiosis called siderosis. Exposure is generally not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis-producing materials such as silica.

Other hazards – Contact may cause skin and eye irritation.

IRON PYRITE (IRON DISULFIDE)

Iron pyrite is classified as a nuisance particulate.

Inhalation hazards – Excessive inhalation of respirable dust may produce pleuritis, and/or fatal pneumonia. Acute – irritation of the eyes, skin, nose, throat and respiratory system. Chronic – exposure to high concentrations of dust and fume containing iron compounds (at least 6-10 years) may produce siderosis with changes visible on chest X-rays.

LINSEED OIL

Inhalation hazard – No known adverse health effects.

Other hazards – Eye contact may cause redness or irritation.

LIMESTONE

A white, finely pulverized powder with no odor.

Inhalation hazards – Limestone dust is considered a nuisance dust. Prolonged exposure may cause irritation to throat and lungs. Silica content is not considered high enough to cause silicosis unless exposures are extremely high and prolonged.

Other hazards – **Eyes** – may cause mild transient eye irritation.

MAGNESIUM OXIDE

Inhalation hazard – Inhalation of fume may cause metal fume fever.

Other hazards – Serious hazard from burns. Overexposure may result in eye, skin or respiratory irritation over a long period of time.

MAN-MADE MINERAL FIBERS – (SYNTHETIC VITREOUS FIBERS)

Inhalation hazards – Exposure to respirable fibers by inhalation may cause temporary upper respiratory irritation, with discomfort and cough. Prolonged exposure may cause chronic lung disease. IARC classifies man-made mineral fibers (diameter <1 µm) as Group 2B, possibly carcinogenic to humans. ACGIH classifies synthetic vitreous fibers as A3, an animal carcinogen with unknown relevance to humans.

Other hazards – The mechanical action of fibers may cause skin irritation and irritation of the eyes and nasal passages. Ingestion may cause gastrointestinal irritation, vomiting, and diarrhea.

Note: The emergence of “biosoluble” forms of man-made fibers has allowed these fiber types to be omitted from classification as a carcinogen according to Note Q in EU Commission Directive 97/69/EC.

MICA/VERMICULITE

Thin amber flakes that are odorless.

Inhalation hazard – Long-term exposure to a respirable airborne concentration exceeding the TLV may lead to pneumoconiosis, but usually no functional lung impairment. The symptoms most frequently reported are chronic cough and dyspnea. May contain naturally occurring trace amounts of crystalline silica.

MOLYBDENUM SULFIDE

Inhalation hazards – Causes lung irritation, chest pain, difficult breathing and coughing.

Other hazards – Nausea, stomach irritation, vomiting and minor irritation to skin. Can cause abrasive damage to outer eye surface.

Symptoms and Effects of Exposure to Selected Individual Components (continued)**MULLITE**

A mixture of bauxitic kaolin and amorphous glass. May contain naturally occurring trace amounts of crystalline silica.

Inhalation hazards – Dust may cause irritation of nasal and respiratory tracts. Long-term exposure may aggravate pre-existing respiratory conditions and may cause pneumoconiosis (kaolinosi).

Other hazards – May cause irritation to the skin and eyes. Can cause abrasive damage to outer eye surface. Non-toxic if ingested.

GROUND TIRE PEEL

Inhalation hazards - Gases and fumes from thermal processing or decomposition of this product may cause irritation of respiratory tract, skin, and eyes.

Other hazards – Eyes – may cause eye irritation if material is introduced into the eye. Eyes may feel scratchy, become red, and tear.

POTASSIUM OXIDE

Inhalation hazards – May cause sore throat, cough, burning sensation. Shortness of breath. Symptoms may be delayed.

Other hazards – May be irritating to skin and eyes.

POTASSIUM TITANATE

Inhalation hazards – May cause irritation of respiratory system. May contain naturally occurring trace amounts of naturally occurring crystalline silica.

Other hazards – May be abrasive to skin and eyes.

Note: The potassium titanates used here are of the non-acicular forms.

RESIN – POWDERED NOVALAC

Inhalation hazards – Dust may cause irritation of nasal and respiratory tracts. Product is fully cured, so formalin vapor should not be present. If formaldehyde is present, inhalation may cause a form of nasal cancer.

Other hazards – Prolonged exposure can cause irritation, redness, tearing of the eyes, and may lead to sensitization of the skin and dermatitis.

RUBBER (POWDERED)

Inhalation hazards – May cause mild irritation of the respiratory tract. Repeated and prolonged inhalation of dust may lead to a benign pneumoconiosis. This condition may cause lung function impairment, but is reversible with reduced exposure.

Other hazards – Eyes – may cause mild transient eye irritation.

SILICA DUST

Inhalation hazards – Acute: Exposure to silica dust may cause paroxysmal coughing, wheezing, dyspnea and upper respiratory tract irritation. Chronic: Prolonged exposure to silica dust may cause silicosis. Crystalline silica has been classified by IARC as, Group 1, carcinogenic to humans. ACGIH classifies crystalline silica as A2, suspected human carcinogen.

Other hazards – Eye or skin contact can cause temporary discomfort and irritation.

Symptoms and Effects of Exposure to Selected Individual Components (continued)**STEEL FIBER**

Inhalation hazards – Acute: Metal fume fever with symptoms of chills, fever, cough, muscle aches, and difficulty in breathing from manganese; silicon can cause respiratory tract irritation; copper can cause irritation of eyes, nose, throat and lungs with a possibility of metal fume fever, chills, nausea, fever, dry throat, cough, and metallic taste. Chronic: Repeated exposure to iron over time may cause lung changes and benign pneumoconiosis; cumulative central nervous system and lung damage may occur with manganese as well as insomnia, and malaise; may cause irritation of the lungs and discoloration of the skin and hair.

Other hazards – May cause mechanical damage to skin and eyes.

SULFUR

Inhalation hazards – Exposure may cause irritation to mucous membranes and upper respiratory tract. Symptoms include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting.

Other hazards – May also irritate by ingestion and skin absorption.

TITANIUM DIOXIDE

Inhalation hazards – May cause irritation of the respiratory system. Extreme exposures have been reported to lead to granulomatous lesions.

Other hazards – Causes irritation to the eyes and skin. Considered a potential occupational carcinogen by NIOSH, but the IARC considers titanium dioxide to be Group 3, unclassifiable.

WOLLASTONITE

A non-metallic mineral powder, white in color with a faint odor.

Inhalation hazards – long-term cumulative inhalation of high concentrations may cause restriction of the large airways.

Other hazards – May cause minor skin irritation.

ZINC

Inhalation hazards – Exposure to zinc oxide can cause a flu-like illness called metal fume fever, with symptoms of metallic taste in the mouth, headaches, cough, shortness of breath, aches and chills, upset stomach and chest pain.

Other hazards – Zinc oxide may be absorbed through the skin to produce the above symptoms. Repeated high exposure may cause ulcer symptoms and affect liver function.

ZIRCONIUM COMPOUNDS

Inhalation hazards – Avoid inhalation of zirconium-containing aerosols, which can cause lung granulomas.

Other hazards – Most zirconium compounds in common use are insoluble and are considered inert. Can cause damage to outer eye surface.

SECTION 4: FIRST AID MEASURES

Ingestion: Seek medical attention.

Inhalation: Move to fresh air. Seek medical attention.

Eye Contact: Flush with water to remove particulate. Seek medical attention.

Skin Contact: Wash thoroughly with soap and water. If persistent irritation develops, seek medical attention.

SECTION 5: FIRE FIGHTING MEASURES**Flashpoint:** N/A**LEL:** N/A**UEL:** N/A**Autoignition Temperature:** This product is inherently flame resistant, but may ignite at temperatures exceeding 1,112°F (600°C) in an oxygen-enriched atmosphere.**Extinguishing Media:** Use media suitable for surrounding fire.**Unusual Fire and Explosion Hazards:** None**Special Fire Fighting Procedures:** Heating to very high temperatures may result in toxic decomposition products (See Section 10).**SECTION 6: ACCIDENTAL RELEASE MEASURES**

If a release of dust occurs during machining, abrading, or riveting, remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust in the workplace.

SECTION 7: HANDLING AND STORAGE

Store in a dry place. Shipping and storage may result in accumulation of dust in shipping containers. If this occurs, dispose of the container in an airtight polyethylene bag (see disposal instructions below) or remove dust by vacuuming or wet mopping. Vacuums used for this purpose should be equipped with HEPA filters. Do not use compressed air to blow dust from storage containers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Ventilation Protection:** Any operation which may produce dust, including machining, grinding, riveting, or abrading this product, should be adequately exhausted to prevent inhalation of dust.**Respiratory Protection:** Use a NIOSH-approved respirator if there is a potential for exposure to dust, vapor, or fume exceeding PELs or TLVs. (See 29 CFR 1910.134, respiratory protection standard).**Skin Protection:** If skin irritation occurs, gloves and other protective garments may be worn.**Eyes:** Wear safety glasses or goggles, as necessary, if dust exposure is possible.**Other:** None known.**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (as lead)****Boiling Point:**

N/A

Vapor Pressure:

N/A

Melting Point:

N/A

Vapor Density (air = 1):

N/A

pH:

N/A

% Volatile:

N/A

Specific Gravity:

2.00 – 3.70 g/cc

Evaporation Rate:

N/A

Water Solubility:

Insoluble

Appearance and Odor:

Solid, phenolic

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Incompatibility (Materials/Conditions to Avoid): None.

Hazardous Polymerization: Will not polymerize. This product is fully cured in the manufacturing process.

Decomposition Products: Oxides of carbon, nitrogen and sulfur; hydrocarbons; ammonia; and other trace organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Inhalation: Refer to Section 3

Skin: Refer to Section 3

Eye: Refer to Section 3

Ingestion: Refer to Section 3

Acute: Skin and eye irritation may occur with repeated contact to dust.

Chronic: This product is a mixture of chemicals physically bonded together. Therefore, in the "as supplied" state, this product is considered non-hazardous. If dust is generated, some of the ingredients can have acute and chronic effects (See Section 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

Soluble copper is known to be an ecotoxin. A study conducted by the Santa Clara Valley Authority identified copper from disc brake pad wear debris as a major contributor to the high level of copper in San Francisco Bay. These findings have been disputed and are currently under review by the Brake Manufacturers Council PEC Committee, Santa Clara Valley Authority, MEMA, and the International Copper Association.

SECTION 13: DISPOSAL CONSIDERATIONS

Federal and state law regulates disposal of solid waste. Waste should be placed in airtight containers. Disposal must be in accordance with 49CFR261, 40CFR262, and applicable state and local regulations.

SECTION 14: TRANSPORTATION INFORMATION

Proper Shipping Name:	Not regulated
Hazard Class:	None
Identification Number:	None
Packing Group:	N/A
Shipping Label:	None
Additional Marking Requirement:	None

SECTION 15: REGULATORY INFORMATION

U.S. TSCA: All chemicals used in the manufacture of this product are listed on the U.S. Toxic Substances Control Act (TSCA) Inventory

California Proposition 65: This product contains ingredients known to the State of California to cause cancer, birth defects or other reproductive effects.

SARA Title III – Section 313 Supplier Notification: This product contains the following chemicals subject to SARA Title III/CERCLA “reportable quantities” (RQs) and/or “threshold planning quantities” (TPQs) and/or are classified as “Toxic Chemicals” under the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR 372:

Ingredient:	CAS Number	% Weight
Antimony and Compounds	1345-04-6	>1
Copper and Compounds	7440-50-8	>1
Zinc and Compounds	1314-13-2, 1314-98-3, 1314-23-4	>1

RCRA Hazardous Waste Code: Not Available

CERCLA Hazardous Substances: Not Available

OSHA: Not Available

WHMIS Classification: Not Available

SECTION 16: OTHER INFORMATION

Abbreviations:

CAS #:	Chemical Abstract Services Number
OSHA PEL:	U.S. Occupational Safety and Health Administration Permissible Exposure Limits
ACGIH TLV:	American Conference of Governmental Industrial Hygienists Threshold Limit Value (2004)
fibers/cc:	Fibers per cubic centimeter of sampled air
mg/m ³ :	Milligrams of constituent per cubic meter of sampled air, on a weight-to-volume basis
N/A:	Not Applicable
NIOSH:	National Institute for Occupational Safety and Health
IARC:	International Agency for Research on Cancer
NTP:	National Toxicology Program
HEPA:	High-efficiency particulate air

This product does not contain any deliberate addition of asbestos.

The information provided on this data sheet was abstracted from a supplier MSDS and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information provided is, however, as of the date below, true and accurate to the best of Federal-Mogul's knowledge.