

# Safety Data Sheet

Revision Date: 10-14-2015  
Product Code: 1510-089

## 1. IDENTIFICATION

Product Name	STANTEST 3.5 ENAMEL BRIGHT RED
Product Code	1510-089
Document ID	G1510-089
Revision Number	1
Prior Version Date	None
Intended Use	Shop Application Coating
Restrictions On Use	For Industrial Use Only
Chemical Family	Alkyd Enamel
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



### GHS Classification

Skin Sensitisation Category 1  
Flammable Liquid Category 2  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2  
Carcinogenicity Category 2  
Acute Toxicity - Inhalation Vapour Category 4

### Signal Word

Danger

### Hazard Statements

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer.

### Precautionary Statements

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

# Safety Data Sheet

Revision Date: 10-14-2015

Product Code: 1510-089

<b>Response</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
<b>Storage</b>	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards Not Otherwise Classified (HNOC)** Not applicable

## Additional Information

Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Chemical Component</b>	<b>CAS #</b>	<b>%</b>
Light aromatic solvent naphtha	64742-95-6	10 - 30
Acetone	67-64-1	7 - 13
Xylene	1330-20-7	5 - 10
1,2,4-Trimethylbenzene	95-63-6	3 - 7
Ethylbenzene	100-41-4	0.5 - 1.5
Titanium dioxide	13463-67-7	0.1 - 1
Cumene	98-82-8	0.1 - 1
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST-AID MEASURES

<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
<b>Eye Contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Wash with soap and water. Get medical attention if irritation develops or persists.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
<b>Most Important Acute Symptoms and Effects</b>	Not Available
<b>Most Important Delayed Symptoms and Effects</b>	Not Available
<b>Special treatment needed:</b>	No additional first aid information available

# Safety Data Sheet

Revision Date: 10-14-2015  
Product Code: 1510-089

## 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.
<b>Unsuitable Extinguishing Media</b>	No data available
<b>Fire and/or Explosion Hazards</b>	Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.
<b>Hazardous Combustion Products</b>	Carbon dioxide, Carbon monoxide, Sulfur containing gases
<b>Special Protective Equipment and Precautions for Fire-Fighters</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions, Protective Equipment and Emergency Procedures</b>	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
<b>Methods and Material for Containment and Cleaning Up</b>	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

## 7. HANDLING AND STORAGE

<b>Precautions for Safe Handling</b>	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use spark-proof tools and explosion-proof equipment. Follow all protective equipment recommendations provided in Section VIII.
<b>Conditions for Safe Storage</b>	Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.
<b>Materials to Avoid/Chemical Incompatibility</b>	Oxidizing agents, Acids

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Acetone	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA	500 ppm TWA; 1188 mg/m <sup>3</sup> TWA	750 ppm STEL; 1782 mg/m <sup>3</sup> STEL

# Safety Data Sheet

Revision Date: 10-14-2015

Product Code: 1510-089

Xylene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	150 ppm STEL; 651 mg/m <sup>3</sup> STEL
Limestone	15 mg/m <sup>3</sup> (total dust); 5 mg/m <sup>3</sup> (respirable fraction)		
1,2,4-Trimethylbenzene		25ppm; 123mg/m <sup>3</sup> TWA	
Ethylbenzene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	125 ppm STEL; 543 mg/m <sup>3</sup> STEL
Titanium dioxide	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Cumene	50 ppm TWA; 245 mg/m <sup>3</sup> TWA	50 ppm TWA; 246 mg/m <sup>3</sup> TWA	

## Appropriate Engineering Controls Respiratory Protection

Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure.

General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure.

Follow respirator manufacturer's directions for respirator use.

## Eye Protection

Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

## Skin Protection

Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.

## Other Protective Equipment General Hygiene Conditions

Nitrile Neoprene Impervious rubber

As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use spark-proof tools and explosion-proof equipment. Follow all protective equipment recommendations provided in Section VIII.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

#### Physical State

Liquid

#### Color

Red

### Odor

No data available

### Odor Threshold

No data available

### pH

No data available

### Melting Point/Freezing Point (°F/°C)

No data available / No data available

### Initial Boiling Point and Boiling Range

#### Low (°F)

132.0

#### High (°F)

335.0

### Flash Point (°F/°C)

4 / -16

### Evaporation Rate

7.70

### Flammability (solid, gas)

No data available

### Upper Flammable/Explosive Limit

7.0

### Lower Flammable/Explosive Limit

1.0

### Vapor Pressure

185.00

### Vapor Density

4.15 (air = 1)

### Relative Density

1.000

### Solubility in Water

Minimal; 1-9%

### Partition coefficient: n-octanol/water

No data available

# Safety Data Sheet

Revision Date: 10-14-2015  
Product Code: 1510-089

Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	20 - 25 Z3
Volatiles, % by volume	54.91
Volatiles, % by weight	44.66
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	401.96
(Actual, Calculated)	338.34
Density	8.57 - 8.77 lbs./Gal

## 10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.
Incompatible Materials	Oxidizing agents, Acids
Hazardous Decomposition Products	Carbon dioxide, Carbon monoxide, Sulfur containing gases

## 11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Ingestion Skin contact Eye contact Skin absorption
--------------------	---

### Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Inhalation Toxicity	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact	Causes skin irritation.
Skin Absorption	May be harmful if absorbed through skin.
Eye Contact	Can cause moderate irritation, tearing and reddening.
Ingestion Toxicity	Harmful or fatal if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Long-Term (Chronic) Health Effects

Carcinogenicity	Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.) Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals.
Reproductive and Developmental Toxicity	Xylene may cause adverse reproductive and/or developmental effects. Pregnant women may be at an increased risk from exposure.
Mutagenicity	Xylene has been shown to be positive in mutagenicity assays.
Inhalation	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

### Product Toxicology Data

Dermal Acute Toxicity Estimate (ATE)	7,063.88 mg/kg
--------------------------------------	----------------

# Safety Data Sheet

Revision Date: 10-14-2015  
Product Code: 1510-089

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Light aromatic solvent naphtha	Oral LD50 Rat 8400 mg/kg	Dermal LD50 Rat > 2000 mg/kg	Inhalation LC50 (4h) Rat 5.60 mg/L
Acetone	Oral LD50 Rat 5800 mg/kg	Dermal LD50 Rabbit > 16 g/kg	Inhalation LC50 (4h) Rat 76.00 mg/L
Xylene	Oral LD50 Rat 3523 mg/kg	Dermal LD50 Rabbit 1100 mg/kg	Inhalation LC50 (4h) Rat 11.00 mg/L
Limestone	Oral LD50 Rat 6450 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.00 mg/L
1,2,4-Trimethylbenzene	Oral LD50 Rat 6000 mg/kg	Dermal LD50 Rat > 3440 mg/kg	Inhalation LC50 (4h) Rat 10.20 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Cumene	Oral LD50 Rat 1400 mg/kg	Dermal LD50 Rabbit > 3160 mg/kg	Inhalation LC50 (4h) Rat 8,000.00 ppm

## Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Ethylbenzene	2B		
Titanium dioxide	2B		
Cumene	2B		

## 12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)	No data available
Mobility in soil	No data available

## 13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste	Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.
------------------------	---

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description:	Paint
Hazard Class:	3
UN Number:	UN1263
Packing Group:	II
Other:	This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

IATA Air Shipping Name:	Paint
IATA Hazard Class:	3
IATA UN Number:	UN1263
IATA Packing Group:	II

IMO Shipping Name:	Paint
--------------------	-------

# Safety Data Sheet

Revision Date: 10-14-2015  
Product Code: 1510-089

IMO Hazard Class: 3  
IMO UN Number: UN1263  
IMO Packing Group: II

Marine Pollutant: N

## 15. REGULATORY INFORMATION

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### Regulated Components

#### SARA EHS Chemicals

Not applicable

#### CAS #

#### %

#### CERCLA

Acetone	67-64-1	7 - 13
Xylene (mixed isomers)	1330-20-7	5 - 10
Ethyl Benzene	100-41-4	0.5 - 1.5
Cumene	98-82-8	0.1 - 1

#### SARA 313

Xylene (mixed isomers)	1330-20-7	5 - 10
1,2,4-Trimethylbenzene	95-63-6	3 - 7
Ethylbenzene	100-41-4	0.5 - 1.5
Cumene	98-82-8	0.1 - 1

#### SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	Y
Pressure:	N
Reactivity:	N

### U. S. State Regulations:

#### California Prop 65 Chemicals

##### **Cancer**

#### CAS #

#### %

Ethyl Benzene	100-41-4	0.5 - 1.5
Titanium dioxide	13463-67-7	0.1 - 1
Cumene	98-82-8	0.1 - 1
Crystalline Silica	14808-60-7	0.01 - 0.1
Benzene	71-43-2	0.01 - 0.1

##### **Reproductive**

Toluene	108-88-3	0.01 - 0.1
Benzene	71-43-2	0.01 - 0.1
Methyl Alcohol	67-56-1	< 10 ppm

### Canadian Regulations:

#### **CEPA DSL:**

The components of this product ARE listed on the Canadian Domestic Substances List.

**WHMIS Hazard Class:** B2 D2A

## 16. OTHER INFORMATION

**Revision Date** 10-14-2015

**Disclaimer** This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of

# Safety Data Sheet

**Revision Date:** 10-14-2015

**Product Code:** 1510-089

safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.