

Safety Data Sheet

Revision Date: 01-26-2016
Product Code: 1560-032

1. IDENTIFICATION

Product Name	STANTEST MULTI-PURPOSE ALKYD PRIMER GRAY
Product Code	1560-032
Document ID	G1560-032
Revision Number	2
Prior Version Date	08-11-2015
Intended Use	Industrial Maintenance Primer
Restrictions On Use	For Industrial Use Only
Chemical Family	Phenolic Alkyd Primer
Chemical Manufacturer / Importer	Hempel (USA), Inc. Jones-Blair Division 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification

Skin Sensitisation Category 1
Carcinogenicity Category 1A
Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Reproductive Toxicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly after handling. Contaminated work clothing should not

Safety Data Sheet

Revision Date: 01-26-2016

Product Code: 1560-032

	be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.
Response	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS #	%
Light aliphatic solvent naphtha	64742-89-8	7 - 13
Titanium dioxide	13463-67-7	3 - 7
Stoddard solvent	8052-41-3	1 - 5
Quartz (Silica-Crystalline)	14808-60-7	0.1 - 1
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
Most Important Acute Symptoms and Effects	Not Available
Most Important Delayed Symptoms and Effects	Not Available
Special treatment needed:	No additional first aid information available

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use alcohol resistant foam, carbon dioxide, or dry chemical
------------------------------	---

Safety Data Sheet

Revision Date: 01-26-2016

Product Code: 1560-032

Unsuitable Extinguishing Media Fire and/or Explosion Hazards

extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.

No data available

Hazardous Combustion Products

Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

Special Protective Equipment and Precautions for Fire-Fighters

Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons, Toxic gases

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and Material for Containment and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

Materials to Avoid/Chemical Incompatibility

Oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Limestone	15 mg/m ³ (total dust); 5 mg/m ³ (respirable fraction)		
Talc	2mg/m ³ (Respirable	20 mppcf TWA	

Safety Data Sheet

Revision Date: 01-26-2016
Product Code: 1560-032

	Dust)		
Titanium dioxide	15 mg/m ³ TWA (total dust)	10 mg/m ³ TWA	
tert-butyl acetate	200ppm; 950mg/m ³ TWA	200ppm TWA	
Stoddard solvent	500 ppm TWA; 2900 mg/m ³ TWA	100 ppm TWA; 572 mg/m ³ TWA	
Kaolin	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	2 mg/m ³ TWA (respirable dust)	
Quartz (Silica-Crystalline)	see Table Z-3	0.05 mg/m ³ TWA (respirable fraction)	
Ethylbenzene	100 ppm TWA; 435 mg/m ³ TWA	100 ppm TWA; 434 mg/m ³ TWA	125 ppm STEL; 543 mg/m ³ STEL
Carbon black	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	

Appropriate Engineering Controls	Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.
Respiratory Protection	General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.
Eye Protection	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
Skin Protection	Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
General Hygiene Conditions	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State	Liquid
Color	Grey
Odor	Aromatic
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (°F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	245.0
High (°F)	302.0
Flash Point (°F/°C)	40 / 4
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	7.0
Lower Flammable/Explosive Limit	1.0
Vapor Pressure	< 10.00 (mm Hg @ 68°F / 20° C)
Vapor Density	3.50
Relative Density	1.400
Solubility in Water	Minimal; 1-9%
Partition coefficient: n-octanol/water	No data available

Safety Data Sheet

Revision Date: 01-26-2016
Product Code: 1560-032

Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	30 - 40 Z3
Volatiles, % by volume	43.83
Volatiles, % by weight	24.14
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	304.65
(Actual, Calculated)	286.67
Density	11.48 - 11.88 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.
Incompatible Materials	Oxidizing agents
Hazardous Decomposition Products	Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons, Toxic gases

11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Ingestion Skin contact Eye contact
--------------------	--

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Causes nose and throat irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Inhalation Toxicity	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact	Causes skin irritation.
Eye Contact	Causes eye irritation.
Ingestion Toxicity	Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Long-Term (Chronic) Health Effects

Carcinogenicity	Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces or spray mists. Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.) Possible cancer hazard. Contains carbon black which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)
Inhalation	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Overexposure may cause lung damage.

Product Toxicology Data

Safety Data Sheet

Revision Date: 01-26-2016
Product Code: 1560-032

Inhalation Vapor Acute Toxicity Estimate 439.70 mg/L
(ATE)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	Oral LD50 Rat 6450 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.00 mg/L
Light aliphatic solvent naphtha	Oral LD50 Rat 5840 mg/kg	Dermal LD50 Rat 2920 mg/kg	
Talc	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Distillates, Petroleum, Hydrotreated Light	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.20 mg/L
tert-butyl acetate	Oral LD50 Rat 4100 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 4,000.00 ppm
Stoddard solvent	Oral LD50 Rat > 15,000 mg/kg	Dermal LD50 Rabbit > 3400 mg/kg	Inhalation LC50 Rat > 13.10 mg/L
Kaolin	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rat > 5000 mg/kg	Inhalation LC50 Rat 36.00 mg/L
Quartz	Oral LD50 Rat > 22,500 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L
Carbon black	Oral LD50 Rat > 8000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	

Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Talc	2B		
Titanium dioxide	2B		
Quartz	1		1
Ethylbenzene	2B		
Carbon black	2B		

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available)	No data available
Mobility in soil	No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste	Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.
------------------------	---

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint
Hazard Class: 3
UN Number: UN1263

Safety Data Sheet

Revision Date: 01-26-2016

Product Code: 1560-032

Packing Group: II
Other: This product qualifies for a limited quantity exception per CFR173.150(b)(2) and 172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

Regulated Components

SARA EHS Chemicals

Not applicable

CERCLA

tert-Butyl acetate

540-88-5

1 - 5

Ethyl Benzene

100-41-4

0.1 - 1

SARA 313

Ethylbenzene

100-41-4

0.1 - 1

SARA 311/312

Health (Acute): Y

Health (chronic): Y

Fire (Flammable): Y

Pressure: N

Reactivity: N

U. S. State Regulations:

California Prop 65 Chemicals

Cancer

Titanium dioxide

CAS #
13463-67-7

%
3 - 7

Crystalline Silica

14808-60-7

0.1 - 1

Ethyl Benzene

100-41-4

0.1 - 1

Carbon Black

1333-86-4

0.1 - 1

Benzene

71-43-2

< 1 ppm

Reproductive

Hexanoic acid, 2-ethyl-

149-57-5

0.01 - 0.1

Toluene

108-88-3

0.001- 0.01

Benzene

71-43-2

< 1 ppm

Canadian Regulations:

CEPA DSL:

The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class:

B2 D2A

16. OTHER INFORMATION

Revision Date 01-26-2016

Disclaimer

This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.

Safety Data Sheet

Revision Date: 01-26-2016
Product Code: 1560-032