Revision Date: 07-13-2015 Product Code: 25-A-24A

1. IDENTIFICATION

Product Name ANTI-RUST BLUE COMPOUND

 Product Code
 25-A-24A

 Document ID
 G25-A-24A

 Revision Number
 1

Prior Version Date None

Intended Use Coating, OEM

Restrictions On Use For Industrial Use Only

Chemical Family Alkyd Enamel

Chemical Manufacturer / Importer JONES-BLAIR® Company, LLC

2728 Empire Central Dallas, TX 75235 1-214-353-1600

Emergency Telephone Number: ChemTrec Center 1-800-424-9300

International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms







GHS Classification Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure

Category 1

Aspiration Hazard Category 1
Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Reproductive Toxicity Category 2

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Acute Toxicity - Inhalation Vapour Category 4

Signal Word Danger

Hazard Statements Highly flammable liquid and vapour. May be fatal if swallowed and enters

airways. Causes skin irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated

exposure.

Precautionary Statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Keep away from heat, sparks, open flames

and hot surfaces. No smoking. Ground/bond container and receiving

equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, mist, vapours or spray. Wash thoroughly

Revision Date: 07-13-2015 Product Code: 25-A-24A

after handling. Do no eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment

as required.

Response IF SWALLOWED: Immediately call a POISON CENTER or physician. IF ON

SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.

Storage Store locked up. Store in a cool, well-ventilated place. Keep container tightly

closed.

Disposal Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazards Not Otherwise Classified (HNOC)

Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS#	<u>%</u>	
Light aliphatic solvent naphtha	64742-89-8	15 - 40	
Solvent naphtha (petroleum) medium aliphatic	64742-88-7	10 - 30	
Stoddard solvent	8052-41-3	5 - 10	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen.

Eye Contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin Contact Wash with soap and water. Remove contaminated clothing and launder. Get medical

attention if irritation develops or persists.

Ingestion If swallowed, do not induce vomiting. Get medical attention immediately. Induce

vomiting as a last measure. Induced vomiting may lead to aspiration of the material

into the lungs potentially causing chemical pneumonitis that may be fatal.

Most Important Acute Symptoms

Not Available

and Effects

Most Important Delayed Symptoms

Not Available

and Effects

Special treatment needed:No additional first aid information available

5. FIRE-FIGHTING MEASURES

extinguishing agents. Water spray or fog may also be effective for

Revision Date: 07-13-2015 Product Code: 25-A-24A

extinguishing if swept across the base of the fire. Water can also be

used to absorb heat and minimize fire damage.

Unsuitable Extinguishing Media Fire and/or Explosion Hazards

No data available

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.

Hazardous Combustion Products Special Protective Equipment and **Precautions for Fire-Fighters**

Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material.

Methods and Material for Containment and Cleaning Up

Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

Conditions for Safe Storage

Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.

Materials to Avoid/Chemical Incompatibility

Oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Stoddard solvent	500 ppm TWA; 2900 mg/m³ TWA	100 ppm TWA; 572 mg/m³ TWA	

Appropriate Engineering Controls Use local exhaust ventilation or other engineering controls to minimize exposure. Engineering controls must be designed to meet the OSHA chemical specific standard in

29 CFR 1910. Explosion proof exhaust ventilation should be used.

General or local exhaust ventilation is the preferred means of protection. In cases where **Respiratory Protection**

Revision Date: 07-13-2015 Product Code: 25-A-24A

ventilation is inadequate, respiratory protection may be required to avoid overexposure.

Follow respirator manufacturer's directions for respirator use.

Eye Protection Wear safety glasses with side shields when handling this product. Wear additional eye

protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

Skin Protection Where use can result in skin contact, practice good personal hygiene. Wash hands and

other exposed areas with mild soap and water before eating, drinking, and when leaving

work. Clothing suitable to prevent skin contact.

General Hygiene Conditions

As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical State Liquid Color Blue

Odor Hydrocarbon
Odor Threshold No data available
pH No data available

Melting Point/Freezing Point (℉/℃) No data available / No data available

Initial Boiling Point and Boiling Range

 Low (₹)
 310.0

 High (₹)
 400.0

 Flash Point (₹/℃)
 62 / 17

 Evaporation Rate
 1.00

Flammability (solid, gas) No data available

Upper Flammable/Explosive Limit 7.0 Lower Flammable/Explosive Limit 0.7

Vapor Pressure < 10.00 (mm Hg @ 68°F / 20° C)

Vapor Density
Relative Density
Solubility in Water
Partition coefficient: n-octanol/water
Auto-ignition Temperature
Decomposition Temperature:
Viscosity

3.50
0.760
Minimal; 1-9%
No data available
No data available
No data available

Viscosity 12 - 16 Volatiles, % by volume 68.42 Volatiles, % by weight 58.80

Volatile Organic Chemicals (g/L)

(Regulatory, Calculated) 512.45 (Actual, Calculated) 512.45

Density 7.17 - 7.37 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions No data available

Conditions to Avoid Sparks, open flame, other ignition sources, and elevated

temperatures. Contamination.

Incompatible Materials Oxidizing agents

Hazardous Decomposition Products

Carbon monoxide, Toxic fumes, Carbon dioxide, Hydrocarbons

11. TOXICOLOGICAL INFORMATION

Routes of Exposure Inhalation

Revision Date: 07-13-2015 Product Code: 25-A-24A

Ingestion Skin contact Eye contact

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Toxicity Vapor harmful. May affect the brain or nervous system causing dizziness,

headache or nausea.

Skin Contact Can cause moderate skin irritation.

Eye Contact Causes eye irritation.

Ingestion Toxicity Aspiration of material into the lungs can cause chemical pneumonitis which

can be fatal.

Long-Term (Chronic) Health Effects

Inhalation NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the

contents may be harmful or fatal.

Product Toxicology Data

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Light aliphatic solvent naphtha	Oral LD50 Rat 5840 mg/kg	Dermal LD50 Rat 2920	
		mg/kg	
Solvent naphtha (petroleum)	Oral LD50 Rat > 6500	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
medium aliphatic	mg/kg	3000 mg/kg	14.00 mg/L
Stoddard solvent	Oral LD50 Rat > 5 g/kg		Inhalation LC50 Rat > 6.10
Stoddard Solverit			mg/L

Carcinogen Information

Chemical Name IARC Carcinogen OSHA Carcinogen NTP Carcinogen

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and

No data available

terrestrial, where available) Mobility in soil

No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste Refer to other sections of this SDS to determine the toxicity and physical

characteristics of the material to determine the proper waste

identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint
Hazard Class: 3
UN Number: UN1263
Packing Group: ||

Other: This product qualifies for a limited quantity exception per CFR173.150(b)(2) and

172.102 Special Provision 149 for inner containers <= 1.3 gallons (5L) and total gross

Revision Date: 07-13-2015 Product Code: 25-A-24A

package wt <= 66 lbs (30kg).

Marine Pollutant: No

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the

inventory notification requirements.

Regulated Components

SARA EHS Chemicals CAS # %

Not applicable

CERCLA

Not applicable

SARA 313

Not applicable

SARA 311/312

Health (Acute): Y
Health (chronic): Y
Fire (Flammable): Y
Pressure: N
Reactivity: N

U. S. State Regulations:

California Prop 65 Chemicals

 Cancer
 CAS #
 %

 Naphthalene
 91-20-3
 0.01 - 0.1

 Cumene
 98-82-8
 0.01 - 0.1

 Ethyl Benzene
 100-41-4
 0.01 - 0.1

Reproductive Not applicable

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances

List.

WHMIS Hazard Class: B2

16. OTHER INFORMATION

Revision Date 07-13-2015

Disclaimer This SDS has been prepared in accordance with the OSHA Hazard Communication

Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This

information is furnished without warranty, expressed or implied.