

# Safety Data Sheet

Revision Date: 07-21-2015  
Product Code: 33511

## 1. IDENTIFICATION

Product Name	CHEM-O-PON Q.D. EPOXY PRIMER
Product Code	33511
Document ID	G33511
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Primer
Restrictions On Use	For Industrial Use Only
Chemical Family	Epoxy Coating
Chemical Manufacturer / Importer	JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

## 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### Hazard Pictograms



### GHS Classification

Skin Sensitisation Category 1  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2  
Carcinogenicity Category 2  
Flammable Liquid Category 3  
Acute Toxicity - Inhalation Vapour Category 4

### Signal Word

Warning

### Hazard Statements

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of causing cancer.

### Precautionary Statements

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required.

# Safety Data Sheet

Revision Date: 07-21-2015

Product Code: 33511

Response	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing and wash before reuse. In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray for extinction.
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable
Additional Information	Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS #	%
Polymer of Epoxy Resin and bisphenol A	25036-25-3	10 - 30
Titanium dioxide	13463-67-7	5 - 10
Xylene	1330-20-7	5 - 10
4-Methyl-2-pentanone	108-10-1	1 - 5
Methyl Amyl Ketone	110-43-0	1 - 5
Epoxidized Alkyl Phenol	68413-24-1	1 - 5
Ethylene glycol mono-n-butyl ether	111-76-2	1 - 5
Light aromatic solvent naphtha	64742-95-6	1 - 5
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5
Ethylbenzene	100-41-4	0.5 - 1.5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST-AID MEASURES

Inhalation	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Thoroughly wash or discard clothing and shoes before reuse.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.
Most Important Acute Symptoms and Effects	Not Available

# Safety Data Sheet

Revision Date: 07-21-2015  
Product Code: 33511

Most Important Delayed Symptoms and Effects Not Available

Special treatment needed: No additional first aid information available

## 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and minimize fire damage.
<b>Unsuitable Extinguishing Media</b>	No data available
<b>Fire and/or Explosion Hazards</b>	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Container may explode in heat of fire.
<b>Hazardous Combustion Products</b>	Carbon dioxide, Carbon monoxide, Sulfur containing gases, Toxic gases, Toxic fumes
<b>Special Protective Equipment and Precautions for Fire-Fighters</b>	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions, Protective Equipment and Emergency Procedures</b>	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
<b>Methods and Material for Containment and Cleaning Up</b>	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

## 7. HANDLING AND STORAGE

<b>Precautions for Safe Handling</b>	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Follow all protective equipment recommendations provided in Section VIII.
<b>Conditions for Safe Storage</b>	Store in a cool dry place. Keep container(s) closed. Keep away from sources of ignition.
<b>Materials to Avoid/Chemical Incompatibility</b>	Oxidizing agents, Caustics (bases, alkalis)

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
---------------------------	-----------------	----------------------	-------------------

# Safety Data Sheet

Revision Date: 07-21-2015

Product Code: 33511

Calcium Metasilicate (Particles Not Otherwise Classified)	50 mppcf (15mg/m <sup>3</sup> ) TWA Total Dust; 15 mppcf (5mg/m <sup>3</sup> ) TWA Respirable fraction		
Talc	2mg/m <sup>3</sup> (Respirable Dust)	20 mppcf TWA	
Titanium dioxide	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	
Xylene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	150 ppm STEL; 651 mg/m <sup>3</sup> STEL
Methyl Isobutyl Ketone	100 ppm TWA; 410 mg/m <sup>3</sup> TWA	50 ppm TWA; 205 mg/m <sup>3</sup> TWA	75 ppm STEL; 307 mg/m <sup>3</sup> STEL
Methyl Amyl Ketone	100ppm; 465mg/m <sup>3</sup> (TWA)	50ppm; 233mg/m <sup>3</sup> TWA	
Butoxy Ethanol	50 ppm TWA; 240 mg/m <sup>3</sup> TWA	20 ppm TWA; 97 mg/m <sup>3</sup> TWA	
1,2,4-Trimethylbenzene		25ppm; 123mg/m <sup>3</sup> TWA	
Ethylbenzene	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 434 mg/m <sup>3</sup> TWA	125 ppm STEL; 543 mg/m <sup>3</sup> STEL

## Appropriate Engineering Controls

Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Explosion proof exhaust ventilation should be used.

## Respiratory Protection

General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use.

## Eye Protection

Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

## Skin Protection

Where use can result in skin contact, practice good personal hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.

## Other Protective Equipment

Nitrile

## General Hygiene Conditions

As with all chemicals, good industrial hygiene practices should be followed when handling this material. Follow all protective equipment recommendations provided in Section VIII.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Physical State  
Color

Liquid  
Grey

Odor

No data available

Odor Threshold

No data available

pH

No data available

Melting Point/Freezing Point (°F/°C)

No data available / No data available

Initial Boiling Point and Boiling Range

Low (°F)

282.0

High (°F)

286.0

Flash Point (°F/°C)

85 / 29

Evaporation Rate

0.60

Flammability (solid, gas)

No data available

# Safety Data Sheet

Revision Date: 07-21-2015  
Product Code: 33511

Upper Flammable/Explosive Limit	7.0
Lower Flammable/Explosive Limit	1.1
Vapor Pressure	77°F 1.06 kPA
Vapor Density	3.70 (air = 1)
Relative Density	2.750
Solubility in Water	Minimal; 1-9%
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	2,500 - 3,500 CPS
Volatiles, % by volume	41.55
Volatiles, % by weight	24.25
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	344.07
(Actual, Calculated)	339.03
Density	12.00 - 12.20 lbs./Gal

## 10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination.
Incompatible Materials	Oxidizing agents, Caustics (bases, alkalis)
Hazardous Decomposition Products	Carbon dioxide, Carbon monoxide, Sulfur containing gases, Toxic gases, Toxic fumes

## 11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Skin contact Eye contact Ingestion Skin absorption
--------------------	---

### Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Causes lung irritation. Causes nose and throat irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.
Inhalation Toxicity	Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.
Skin Contact	Causes skin irritation. May cause allergic skin reaction.
Skin Absorption	May be harmful if absorbed through skin.
Eye Contact	Causes eye irritation.
Ingestion Toxicity	Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

### Long-Term (Chronic) Health Effects

Carcinogenicity	Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Possible cancer hazard. Contains ethylbenzene which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)
Reproductive and Developmental Toxicity	Xylene may cause adverse reproductive and/or developmental effects. Pregnant women may be at an increased risk from exposure. Contains butoxy ethanol which has been shown to cause harm to the fetus in laboratory animal studies. The relevance of these findings to humans is

# Safety Data Sheet

Revision Date: 07-21-2015

Product Code: 33511

## Mutagenicity

### Inhalation

uncertain.

Xylene has been shown to be positive in mutagenicity assays.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

## Skin Contact

### Skin Absorption

Prolonged contact may cause an allergic skin reaction.

Upon prolonged or repeated exposure, harmful if absorbed through the skin.

## Product Toxicology Data

### Oral Acute Toxicity Estimate (ATE)

7,031.27 mg/kg

### Dermal Acute Toxicity Estimate (ATE)

15,431.49 mg/kg

## Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Polymer of Epoxy Resin and bisphenol A	Oral LD50 > 2000 mg/kg	Dermal LD50 Rat > 2000 mg/kg	
Calcium Metasilicate	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Talc	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Xylene	Oral LD50 Rat 3523 mg/kg	Dermal LD50 Rabbit 1100 mg/kg	Inhalation LC50 (4h) Rat 11.00 mg/L
4-Methyl-2-pentanone	Oral LD50 Rat 2080 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat 8.20 - 16.40 mg/L
Methyl Amyl Ketone	Oral LD50 Rat 1600 mg/kg	Dermal LD50 Rabbit 10,206 mg/kg	Inhalation LC50 (4h) Rat > 16.70 mg/L
Ethylene glycol mono-n-butyl ether	Oral LD50 Rat 1300 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (6h) Rat > 500.00 ppm
Light aromatic solvent naphtha	Oral LD50 Rat 8400 mg/kg	Dermal LD50 Rat > 2000 mg/kg	Inhalation LC50 (4h) Rat 5.60 mg/L
1,2,4-Trimethylbenzene	Oral LD50 Rat 6000 mg/kg	Dermal LD50 Rat > 3440 mg/kg	Inhalation LC50 (4h) Rat 10.20 mg/L
Ethylbenzene	Oral LD50 Rat 3500 mg/kg	Dermal LD50 Rabbit 5510 mg/kg	Inhalation LC50 (4h) Rat 17.00 mg/L

## Carcinogen Information

### Chemical Name

### IARC Carcinogen

### OSHA Carcinogen

### NTP Carcinogen

Talc

2B

Titanium dioxide

2B

4-Methyl-2-pentanone

2B

Ethylbenzene

2B

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity (aquatic and terrestrial, where available)

No data available

### Mobility in soil

No data available

## 13. DISPOSAL CONSIDERATIONS

### Safe Handling of Waste

Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

# Safety Data Sheet

Revision Date: 07-21-2015

Product Code: 33511

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

**DOT Basic Description:** Paint  
**Hazard Class:** 3  
**UN Number:** UN1263  
**Packing Group:** III  
**Other:** This product qualifies for a limited quantity exception per CFR173.150(b)(3) for inner containers <= 1.3 gallons (5L) and total gross package wt <= 66 lbs (30kg).

**Marine Pollutant:** No

## 15. REGULATORY INFORMATION

**TSCA Status** All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### Regulated Components

#### SARA EHS Chemicals

Not applicable

#### CERCLA

	<u>CAS #</u>	<u>%</u>
Xylene (mixed isomers)	1330-20-7	5 - 10
Methyl Isobutyl Ketone	108-10-1	1 - 5
Ethyl Benzene	100-41-4	0.5 - 1.5

#### SARA 313

Xylene (mixed isomers)	1330-20-7	5 - 10
Methyl Isobutyl Ketone	108-10-1	1 - 5
Ethylene glycol mono-n-butyl ether	111-76-2	1 - 5
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5
Ethylbenzene	100-41-4	0.5 - 1.5

#### SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	Y
Pressure:	N
Reactivity:	N

### U. S. State Regulations:

#### California Prop 65 Chemicals

##### **Cancer**

	<u>CAS #</u>	<u>%</u>
Titanium dioxide	13463-67-7	5 - 10
Ethyl Benzene	100-41-4	0.5 - 1.5
Cumene	98-82-8	0.01 - 0.1
Carbon Black	1333-86-4	0.01 - 0.1
Benzene	71-43-2	0.001- 0.01

##### **Reproductive**

Methyl Isobutyl Ketone	108-10-1	1 - 5
Toluene	108-88-3	0.01 - 0.1
Benzene	71-43-2	0.001- 0.01

# Safety Data Sheet

**Revision Date:** 07-21-2015  
**Product Code:** 33511

Methyl Alcohol

67-56-1

< 1 ppm

## **Canadian Regulations:**

### **CEPA DSL:**

The components of this product ARE listed on the Canadian Domestic Substances List.

### **WHMIS Hazard Class:**

B2 D2A

## **16. OTHER INFORMATION**

### **Revision Date**

07-21-2015

### **Disclaimer**

This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.