SAFETY DATA SHEET



Date of issue/Date of revision 1 May 2016 Version 3

Section 1. Identification				
Product name	: GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3			
Product code	: 00372273			
Other means of identification	: Not available.			
Product type	: Liquid.			
Relevant identified uses of	the substance or mixture and uses advised against			
Product use	: Industrial applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Not applicable.			
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272			
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)			
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)			

Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 30.9%
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.

Date of issue 1 May 2016

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 2. Hazards identification

	Photosensitive agents : In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Ingredient name	%	CAS number
3-iodo-2-propynyl butylcarbamate	<1.0	55406-53-6

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

United States	Page: 2/11
---------------	------------

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 4. First aid measures

Potential acute health effe	<u>ets</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	utoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 6. Accidental release measures

Personal	precautions,	protective	equip	oment a	nd em	nergenc	V	procedures

For non-emergency personnel	ction shall be taken involving any personal risk or without suitable train cuate surrounding areas. Keep unnecessary and unprotected personn ring. Do not touch or walk through spilled material. Put on appropriate active equipment.	el from
For emergency responders	ecialized clothing is required to deal with the spillage, take note of any ion 8 on suitable and unsuitable materials. See also the information in rgency personnel".	
Environmental precautions	d dispersal of spilled material and runoff and contact with soil, waterwa sewers. Inform the relevant authorities if the product has caused envir tion (sewers, waterways, soil or air).	
Methods and materials for co	ant and cleaning up	
Small spill	leak if without risk. Move containers from spill area. Dilute with water ter-soluble. Alternatively, or if water-insoluble, absorb with an inert dry e in an appropriate waste disposal container. Dispose of via a licensed osal contractor.	material and
Large spill	leak if without risk. Move containers from spill area. Prevent entry int r courses, basements or confined areas. Wash spillages into an efflue or proceed as follows. Contain and collect spillage with non-combust rbent material e.g. sand, earth, vermiculite or diatomaceous earth and ainer for disposal according to local regulations (see Section 13). Disp sed waste disposal contractor. Note: see Section 1 for emergency cor mation and Section 13 for waste disposal.	ent treatment ible, place in ose of via a

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	: Put on appropriate personal protective equipment (see Section 8).	
Special precautions	If this material is part of a multiple component system, read the Safety Data Sheet the other component or components before blending as the resulting mixture may the hazards of all of its parts.	
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eat drinking and smoking. Remove contaminated clothing and protective equipment the entering eating areas. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance wi local regulations. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials (see Section 10) and f and drink. Keep container tightly closed and sealed until ready for use. Container have been opened must be carefully resealed and kept upright to prevent leakage not store in unlabeled containers. Use appropriate containment to avoid environm contamination.	y, cool ood rs that e. Do
	United States Page: 4	4/11

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Expo	osure limits
3-iodo-2-propynyl butylcarba	nate	None	9.
	Key to abbreviation	IS	
C = Ceiling Limit F = Fume IPEL = Internal Permissible Expo OSHA = Occupational Safety and R = Respirable Z = OSHA 29 CFR 1910.120	Governmental Industrial Hygienists. osure Limit Health Administration. 0 Subpart Z - Toxic and Hazardous Substance	S SR SS STEL TD TLV TWA S	 Potential skin absorption Respiratory sensitization Skin sensitization Short term Exposure limit values Total dust Threshold Limit Value Time Weighted Average
Consult local authorities for a	acceptable exposure limits.		
Recommended monitoring procedures	the ventilation or other control me	ng may be re asures and/o should be m ocuments for	equired to determine the effectiveness of or the necessity to use respiratory ade to appropriate monitoring standards.
Appropriate engineering controls	: Good general ventilation should b contaminants.	e sufficient to	o control worker exposure to airborne
Environmental exposure controls	they comply with the requirements	s of environm	uipment should be checked to ensure nental protection legislation. In some nodifications to the process equipment ptable levels.
Individual protection measure	<u>es</u>		
Hygiene measures	eating, smoking and using the lav Appropriate techniques should be Wash contaminated clothing befo showers are close to the workstat	atory and at t used to remo re reusing.	ter handling chemical products, before the end of the working period. ove potentially contaminated clothing. Ensure that eyewash stations and safety
Eye/face protection Skin protection	: Safety glasses with side shields.		
Hand protection			ng with an approved standard should be ucts if a risk assessment indicates this is
Gloves	: polyethylene		
Body protection	 Personal protective equipment for performed and the risks involved handling this product. 		ould be selected based on the task being e approved by a specialist before
Other skin protection	: Appropriate footwear and any add	d and the risl	rotection measures should be selected ks involved and should be approved by a

Date of issue 1 May 2016

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the
	hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Physical state:Liquid.Color:Not available.Odor:Characteristic.Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Pecomposition temperature:Not available.Flammability (solid, gas):Not available.Evaporation rate:Not available.Vapor density:Not available.Vapor density:Not available.Pensity (lbs / gal):Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Soluble in the following materials: cold water.Viscosity::Soluble.Volatility::Soluble.Volatility:::Viscosity:::Wiscolid. (w/w):::% Solid. (w/w)::% Solid. (w/w)::% Solid. (w/w)::% Solid. (w/w)::::::::::::::::::::::::::: </th <th><u>Appearance</u></th> <th></th> <th></th>	<u>Appearance</u>		
Odor: Characteristic.Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: 100°C (212°F)Flash point: Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Evaporation rate: Upper: 0%(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Relative density: 1.04Density (lbs / gal): Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Physical state	Liquid.	
Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Upper: 0%Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:1.04Density (lbs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility::67% (v/v), 64.68% (w/w)	Color	Not available.	
pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Upper: 0%Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.04Density (lbs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:67% (v/v), 64.68% (w/w)	Odor	Characteristic.	
Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Upper: 0%(flammable) limits:Upper: 0%Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.04Density (lbs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:67% (v/v), 64.68% (w/w)	Odor threshold	Not available.	
Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Upper: 0%(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.04Density (Ibs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:67% (v/v), 64.68% (w/w)	рН	Not available.	
Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Upper: 0%Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.04Density (lbs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:67% (v/v), 64.68% (w/w)	Melting point	Not available.	
Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Upper: 0%Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.04Density (lbs / gal):8.68Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:67% (v/v), 64.68% (w/w)	Boiling point	100°C (212°F)	
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Upper: 0%(flammable) limits: Upper: 0%Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Flash point	Closed cup: Not applicable. [Product does not sustain combustion	n.]
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Upper: 0%Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Auto-ignition temperature	Not available.	
Lower and upper explosive (flammable) limits: Upper: 0%Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Decomposition temperature	Not available.	
(flammable) limitsEvaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Flammability (solid, gas)	Not available.	
Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)		Upper: 0%	
Vapor density: Not available.Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Evaporation rate	Not available.	
Relative density: 1.04Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Vapor pressure	Not available.	
Density (lbs / gal): 8.68Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Vapor density	Not available.	
Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Relative density	1.04	
Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 67% (v/v), 64.68% (w/w)	Density(lbs / gal)	8.68	
octanol/water Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt) Volatility : 67% (v/v), 64.68% (w/w)	Solubility	Soluble in the following materials: cold water.	
Volatility : 67% (v/v), 64.68% (w/w)		Not available.	
	Viscosity	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)	
		67% (v/v), 64.68% (w/w)	

Section 10. Stability and reactivity

	United States Page: 6/11
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Date of issue 1 May 2016

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 10. Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl	LD50 Dermal	Rabbit	>2 g/kg	-
butylcarbamate	LD50 Oral	Rat	1470 mg/kg	-
Conclusion/Summary	: There are no data available of	n the mixture itse	elf.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available or	n the mixture itse	elf.	
Eyes	: There are no data available or	n the mixture itse	elf.	
Respiratory	: There are no data available of	n the mixture itse	elf.	
Sensitization				
Conclusion/Summary				
Skin	: There are no data available or	n the mixture itse	elf.	
Respiratory	: There are no data available or	n the mixture itse	elf.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data available or	n the mixture itse	elf.	
Carcinogenicity				
Conclusion/Summary	: There are no data available of	n the mixture itse	elf.	
Reproductive toxicity				
Conclusion/Summary	: There are no data available on	the mixture itse	lf.	
Teratogenicity				
Conclusion/Summary	: There are no data available on	the mixture itse	lf.	
Specific target organ toxicity	<u>y (single exposure)</u>			
Not available.				

Specific target organ toxicity (repeated exposure)

Name	Category
3-iodo-2-propynyl butylcarbamate	Category 1

Aspiration hazard

Not available.

United States	Page: 7/11

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 11. Toxicological information

		J		
Information on the likely rout	tes	of exposure		
Potential acute health effect	<u>ts</u>			
Eye contact	:	No known significant effects or critical h	azards.	
Inhalation	1	No known significant effects or critical hazards.		
Skin contact	1	No known significant effects or critical h	azards.	
Ingestion	4	No known significant effects or critical h	azards.	
Over-exposure signs/sympt	on	<u>15</u>		
Eye contact	4	No specific data.		
Inhalation	4	No specific data.		
Skin contact	1	No specific data.		
Ingestion	1	No specific data.		
Delayed and immediate effect	ts	and also chronic effects from short ar	<u>id long term exposure</u>	
Conclusion/Summary		have irritating properties. Prolonged or membrane may result in irritation sympt May cause allergic skin reactions with re droplets or aerosols may cause irritation nausea, weakness and central nervous liquid may cause irritation and reversible known, delayed and immediate effects a	ure itself. Acrylate components of the mixture repeated contact with skin or mucous oms, such as redness, blistering, dermatitis etc. epeated exposure. The inhalation of airborne n of the respiratory tract. Ingestion may cause system effects. If splashed in the eyes, the e damage. This takes into account, where and also chronic effects of components from oral, inhalation and dermal routes of exposure	
Short term exposure				
Potential immediate effects	:	There are no data available on the mixtu	ure itself.	
Potential delayed effects	1	There are no data available on the mixtu	ure itself.	
<u>Long term exposure</u>				
Potential immediate effects	1	There are no data available on the mixture itself.		
Potential delayed effects	al delayed effects : There are no data available on the mixture itself.			
Potential chronic health effe	cts			
General	:	No known significant effects or critical h	azards.	
Carcinogenicity	:	No known significant effects or critical hazards.		
Mutagenicity	1	No known significant effects or critical hazards.		
Teratogenicity	1	No known significant effects or critical hazards.		
Developmental effects	1	: No known significant effects or critical hazards.		
Fertility effects				
Numerical measures of toxic	<u>ity</u>			
Acute toxicity estimates				
Route			ATE value	
Oral			169235.7 mg/kg	
<u>k</u>			۱ ــــــــــــــــــــــــــــــــــــ	

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and
	sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information				
	DOT	IMDG	ΙΑΤΑ	
UN number	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	
Transport hazard class (es)	-	-	-	
Packing group	-	-	-	
Environmental hazards	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	

United States	Page: 9/11
---------------	------------

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

14. Transport information

Additional information

- **DOT** : None identified.
- **IMDG** : None identified.
- IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

United States - TSCA 5(e) - Substances consent order: partially fluorinated alcohol, reaction products	Listed
United States - TSCA 5(a)2 - Proposed significant new use rules: partially fluorinated alcohol, reaction products	Listed

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

Name	hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
3-iodo-2-propynyl butylcarbamate	Yes.	No.	No.	Yes.	Yes.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 Flammability : 0 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Version 3

Product name GC13013 GLIDDEN COLOR 2in1 INTERIOR/EXTERIOR SEMI-GLOSS-BASE 3

Section 16. Other information

Health : 1 Flammal	bility : 0 Instability : 0
Date of previous issue	: 6/30/2015
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.