SAFETY DATA SHEET



Date of issue/Date of revision28 April 2016Version 7

Section 1. Identification			
Product name	: GLOSS ALKYD INT/EXT DEEP BASE		
Product code	: 6-1630		
Other means of identification	: Not available.		
Product type	: Liquid.		
Relevant identified uses of	the substance or mixture and uses advised against		
Product use	: Industrial applications.		
Use of the substance/ mixture	: Coating. Paints. Painting-related materials.		
Uses advised against	: Not applicable.		
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272		
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)		
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)		

Section 2. Hazards identification

	United States Page: 1/12
Hazard statements	: Suspected of damaging fertility or the unborn child. Suspected of causing cancer.
Signal word	: Warning
GHS label elements Hazard pictograms	:
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 25.6%
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2
OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 2. Hazards identification

Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing.
Response	: IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER- FILLED METAL CONTAINER.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Product name	:	GLOSS ALKYD INT/EXT DEEP BASE

Ingredient name	%	CAS number
titanium dioxide	≥1.0 - ≤5.0	13463-67-7
2-ethylhexanoic acid, cobalt salt	<1.0	13586-82-8
2-ethylhexanoic acid, zirconium salt	≤1.0	22464-99-9
3-iodo-2-propynyl butylcarbamate	<1.0	55406-53-6

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Section 4. First aid measures

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health ef	fects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	nptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate n	nedical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Our a stift a day a function of a	

- **Specific treatments** : No specific treatment.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
	United States Page: 3/12

Product name GLOSS ALKYD INT/EXT DEEP BASE

Section 5. Fire-fighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	1	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated

absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Product name GLOSS ALKYD INT/EXT DEEP BASE

Section 7. Handling and storage

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Ingestion of product or cured coating may be harmful. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
titanium dioxide	OSHA PEL (United States, 2/2013).	
	TWA: 15 mg/m ³ 8 hours. Form: Total dust	
	ACGIH TLV (United States, 3/2015).	
	TWA: 10 mg/m ³ 8 hours.	
2-ethylhexanoic acid, cobalt salt	ACGIH TLV (United States, 3/2015).	
	TWA: 0.02 mg/m ³ , (as Co) 8 hours.	
2-ethylhexanoic acid, zirconium salt	ACGIH TLV (United States, 3/2015).	
	STEL: 10 mg/m ³ , (as Zr) 15 minutes.	
	TWA: 5 mg/m³, (as Zr) 8 hours.	
	OSHA PEL (United States, 2/2013).	
	TWA: 5 mg/m ³ , (as Zr) 8 hours.	
3-iodo-2-propynyl butylcarbamate	None.	
Key to abbreviation	ns	
A = Acceptable Maximum Peak	S = Potential skin absorption	
CGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization	

United States	Page: 5/12
---------------	------------

= Skin sensitization

= Threshold Limit Value

= Time Weighted Average

= Total dust

= Short term Exposure limit values

SS

STEL

TD

TLV

TWA

Product name GLOSS ALKYD INT/EXT DEEP BASE

Section 8. Exposure controls/personal protection

С =	Ceiling	Limit
-----	---------	-------

- F = Fume
- IPEL = Internal Permissible Exposure Limit
- = Occupational Safety and Health Administration. OSHA
 - R = Respirable Ζ
 - = OSHA 29 CFR 1910.1200 Subpart Z Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Consult local authorities for a	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state: Liquid.Color: Not available.Odor: Not available.Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: Not available.Boiling point: S37.78°C (>100°F)Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 34.64			
OdoriNot available.Odor thresholdiNot available.pHiNot available.Melting pointiNot available.Boiling pointi>37.78°C (>100°F)Flash pointiClosed cup: >93.33°C (>200°F)Auto-ignition temperatureiNot available.Decomposition temperatureiNot available.Flammability (solid, gas)iNot available.Portifich coefficient: n- octanol/wateriNot available.ViscosityiNot available.ViscosityiKinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatilityi70% (v/v), 65.36% (w/w)	Physical state	:	Liquid.
Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: >37.78°C (>100°F)Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Flammability (solid, gas): Not available.Evaporation temperature: Not available.flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Color	:	Not available.
pH:Not available.Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.5 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.06Density (lbs / gal):8.85Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:70% (v/v), 65.36% (w/w)	Odor	:	Not available.
Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.5 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.06Density (lbs / gal):8.85Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:70% (v/v), 65.36% (w/w)	Odor threshold	:	Not available.
Boiling point:>37.78°C (>100°F)Flash point:Closed cup: >93.33°C (>200°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Evapor and upper explosive (flammable) limits:Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.5 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.06Density (Ibs / gal):8.85Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:70% (v/v), 65.36% (w/w)	рН	1	Not available.
Flash point: Closed cup: >93.33°C (>200°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Melting point	1	Not available.
Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Not available.Evaporation rate:0.35 (butyl acetate = 1)Vapor pressure:2.3 kPa (17.5 mm Hg) [room temperature]Vapor density:Not available.Relative density:1.06Density (lbs / gal):8.85Solubility:Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.Viscosity:Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility:70% (v/v), 65.36% (w/w)	Boiling point	:	>37.78°C (>100°F)
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.(flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Flash point	1	Closed cup: >93.33°C (>200°F)
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Auto-ignition temperature	1	Not available.
Lower and upper explosive (flammable) limits: Not available.Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Decomposition temperature	1	Not available.
(flammable) limitsEvaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	Flammability (solid, gas)	:	Not available.
Evaporation rate: 0.35 (butyl acetate = 1)Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)		:	Not available.
Vapor pressure: 2.3 kPa (17.5 mm Hg) [room temperature]Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)			0.25 (but d exected = 1)
Vapor density: Not available.Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)			
Relative density: 1.06Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)		÷	
Density (lbs / gal): 8.85Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)		÷	
Solubility: Insoluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)	· · · · · · · · · · · · · · · · · · ·	÷	
Partition coefficient: n- octanol/water: Not available.Viscosity: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)Volatility: 70% (v/v), 65.36% (w/w)		÷	
octanol/water Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt) Volatility : 70% (v/v), 65.36% (w/w)	Solubility	1	Insoluble in the following materials: cold water.
Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt) Volatility : 70% (v/v), 65.36% (w/w)		1	Not available.
Volatility : 70% (v/v), 65.36% (w/w)			1/(1-2) = 1/(1
		÷	
% Solid. (w/w) : 34.64		÷	
	% Solid. (w/w)	4	34.64

Section 10. Stability and reactivity

	United States Page: 7/12
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure
M anium dioxide	LD50 Oral			Rat	>11 g/kg	-
2-ethylhexanoic acid,	LD50 Dern	nal		Rabbit	>5 g/kg	-
zirconium salt						
	LD50 Oral			Rat	>5 g/kg	-
3-iodo-2-propynyl	LD50 Dern	nal		Rabbit	>2 g/kg	-
butylcarbamate	LD50 Oral			Rat	1470 mg/kg	-
Conclusion/Summary	: There are	e no data a	vailable on th	e mixture itse		
rritation/Corrosion						
Conclusion/Summary						
Skin	: There are	: There are no data available on the mixture itself.				
Eyes	: There are	: There are no data available on the mixture itself.				
Respiratory	: There are no data available on the mixture itself.					
Sensitization						
Conclusion/Summary						
Skin	: There are	e no data a	vailable on th	e mixture itsel	lf.	
Respiratory	: There are	There are no data available on the mixture itself.				
<u>Mutagenicity</u>						
Conclusion/Summary	: There are no data available on the mixture itself.					
Carcinogenicity						
Conclusion/Summary	mmary : There are no data available on the mixture itself.					
Classification						
Product/ingredient name	OSHA	IARC	NTP			
titanium dioxide	-	2B	-			
2-ethylhexanoic acid, cobalt	-	2B	-			

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

salt

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product name GLOSS ALKYD INT/EXT DEEP BASE

Section 11. Toxicological information

Name		Category
3-iodo-2-propynyl butylcarba	mate	Category 1
Target organs	: Contains material which may cause damage to the followin tract.	ng organs: upper respiratory
Aspiration hazard		
Not available.		
nformation on the likely rou	tes of exposure	
Potential acute health effec	t <u>s</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/symp	-	
Eye contact	: No specific data.	
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Delayed and immediate effect	cts and also chronic effects from short and long term expo	<u>sure</u>
Conclusion/Summary	: There are no data available on the mixture itself. If splash cause irritation and reversible damage. Ingestion may cau vomiting. This takes into account, where known, delayed a also chronic effects of components from short-term and low inhalation and dermal routes of exposure and eye contact.	use nausea, diarrhea and and immediate effects and ng-term exposure by oral,
<u>Short term exposure</u>		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Long term exposure		
Potential immediate effects	: There are no data available on the mixture itself.	
Potential delayed effects	: There are no data available on the mixture itself.	
Potential chronic health effe		
General	: No known significant effects or critical hazards.	
Carcinogenicity	 Suspected of causing cancer. Risk of cancer depends on exposure. 	duration and level of
		ed States Page: 9/12

Section 11. Toxicological information

- Mutagenicity: No known significant effects or critical hazards.Teratogenicity: Suspected of damaging the unborn child.Developmental effects: No known significant effects or critical hazards.
 - Fertility effects
- : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT	: None identified.
IMDG	: None identified.
IATA	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

2

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

U.S. Federal regulations

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
titanium dioxide	No.	No.	No.	No.	Yes.
2-ethylhexanoic acid, cobalt salt	No.	No.	No.	Yes.	Yes.
2-ethylhexanoic acid, zirconium salt	Yes.	No.	No.	No.	Yes.
3-iodo-2-propynyl butylcarbamate	Yes.	No.	No.	Yes.	Yes.

United States	Page: 11/12
---------------	-------------

CAS number

13586-82-8

Concentration

0.1 - 1

Product name GLOSS ALKYD INT/EXT DEEP BASE

Section 15. Regulatory information

<u>SARA 313</u>

Supplier notification

Chemical name

: 2-ethylhexanoic acid, cobalt salt

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Ass	ociation (U.S.A.)
Health : 1 Flamma	i <mark>bility: 1 Instability</mark> : 0
Date of previous issue	: 12/1/2015
Organization that prepared the MSDS	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.