

BEBBINGTON INDUSTRIES MATERIAL SAFETY DATA SHEET - GARAGE FLOOR CLEANER

SECTION 1: PRODUCT IDENTIFICATION.

PRODUCT NAME : GARAGE FLOOR CLEANER
INTENDED USE: DEGREASER
TDG SHIPPING NAME: CORROSIVE LIQUIDS N.O.S. (SODIUM HYDROXIDE SOL)
TDG CLASSIFICATION: CLASS 8, UN 1760, PG II
WHMIS CLASSIFICATION: CLASS E CORROSIVE
MANUFACTURER: BEBBINGTON INDUSTRIES
44 WRIGHT AVENUE, DARTMOUTH, NOVA SCOTIA, B3B 1G6
TELEPHONE: 902 468-8180 FAX: 902 468-8559
EMERGENCY TELEPHONE : 613 996 6666

SECTION 2: HAZARDOUS INGREDIENTS.

NON IONIC SURFACTANTS, (ALKYL, POLYOXYETHYLENES)
BLEND OF CAS NO'S 68551-13-3, 68439-46-3, 66455-14-9
TLV, LD50, LC50 NOT AVAILABLE
SODIUM SILICATE - CAS NO. 1344-09-8 LD 50 ORAL RAT 1280 MG/KG 1 - 10 %
2 - 7 %
SODIUM PHOSPHATE - CAS NO. 7558-99-4 LD 50 ORAL RAT 7400 MG/KG 1 - 5 %
SODIUM HYDROXIDE - CAS NO. 1310-73-2 LD 50 ORAL RAT 1350 MG/KG 1 - 5 %

SECTION 3: PHYSICAL DATA.

A CLEAR COLOURLESS AQUEOUS SOLUTION WITH A PH BETWEEN 12.4 AND 13.50.
PRODUCT IS MISCIBLE WITH WATER.

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

NO FIRE OR EXPLOSION HAZARD. MAY REACT VIOLENTLY IF MIXED WITH CONCENTRATED ACIDS.

SECTION 5: HEALTH HAZARD DATA.

SWALLOWING - MAY CAUSE BURNS OF THE MOUTH, THROAT AND STOMACH.
INHALATION - MISTS ARE IRRITANTS TO RESPIRATORY TRACT.
SKIN CONTACT - CAN BE CORROSIVE TO SKIN. MAY CAUSE IRRITATION.
EYE CONTACT - CORROSIVE TO EYE TISSUES, CAN CAUSE BURNS.
PROLONGED CONTACT CAN DEHYDRATE AND REMOVE OILS FROM SKIN.

SECTION 6: FIRST AID PROCEDURES

INHALATION OF MIST - REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IMMEDIATELY.
SWALLOWING - IF SWALLOWED **DO NOT INDUCE VOMITING.** GIVE LARGE

QUANTITIES OF WATER OR MILK IF AVAILABLE. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SKIN CONTACT - WASH SKIN WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. WASH CLOTHES BEFORE REUSE.

EYE CONTACT - RINSE EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, AND LIFT LOWER AND UPPER EYE LIDS OCCASIONALLY. SEEK MEDICAL ATTENTION.

SECTION 7: REACTIVITY DATA

STABILITY - PRODUCT IS STABLE UNDER NORMAL CONDITIONS OF USE AND STORAGE. THIS PRODUCT IS INCOMPATIBLE WITH ACIDS. MAY PRODUCE A VIOLENT REACTION IF MIXED WITH CONCENTRATED ACID.

SECTION 8: SPILL OR LEAK PROCEDURES

VENTILATE AREA OF LEAK OR SPILL. CLEAN UP PERSONNEL REQUIRE PROTECTIVE CLOTHING. CONTAIN AND RECOVER LIQUID WHERE POSSIBLE - FOR SPILLS TO DRAINS, FLUSH DRAIN WITH LARGE VOLUMES OF WATER.

SECTION 9: SPECIAL PROTECTION INFORMATION.

PROTECTIVE GLOVES - USE PROTECTIVE GLOVES SUCH AS VINYL OR NITRILE
EYE PROTECTION - THE USE OF SAFETY GOGGLES OR GLASSES IS RECOMMENDED
RESPIRATORY PROTECTION - NOT NORMALLY REQUIRED

SECTION 10: SPECIAL PRECAUTIONS.

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH HANDS AFTER USE.

SECTION 11: PREPARATION DATA.

PREPARED BY - BEBBINGTON INDUSTRIES DATE - FEBRUARY 2015
FOR FURTHER INFORMATION CONTACT BEBBINGTON INDUSTRIES 902-468-8180

DISCLAIMER:

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. BEBBINGTON INDUSTRIES SHALL NOT BE HELD LIABLE FOR ANY DAMAGE OF INJURY RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT. ALL PERSONS USING THIS PRODUCT SHOULD BE TRAINED ACCORDING TO WHMIS REQUIREMENTS.