HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: GasPerm 1000™

Revision Date: 24-Jul-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: GasPerm 1000™

Synonyms:NoneChemical Family:BlendApplication:Surfactant

Manufacturer/Supplier Halliburton Energy Services, Inc.

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Citrus, extract	94266-47-4	10 - 30%	Not applicable	Not applicable
Terpenes and Terpenoids, sweet orange-oil	68647-72-3	10 - 30%	Not applicable	Not applicable
Terpene	Proprietary	5 - 10%	Not applicable	Not applicable
Isopropanol	67-63-0	10 - 30%	TWA: 200 ppm STEL: 400 ppm	400 ppm
Polyoxyalkylenes	Proprietary	10 - 30%	Not applicable	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness,

and other central nervous system effects. May be harmful if swallowed. May be absorbed through the skin. Repeated overexposure may cause liver and kidney

effects. May cause allergic skin reaction. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least

15 minutes. Get medical attention. Remove contaminated clothing and launder

before reuse.

Eyes Check for and remove contact lenses if present. In case of contact, or suspected

contact, immediately flush eyes with plenty of water for at least 15 minutes and get

medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person. Get medical attention! If vomiting occurs, keep head lower than hips to prevent

aspiration.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F): 82.3
Flash Point/Range (C): 28
Flash Point Method: PMCC

Autoignition Temperature (F):Not DeterminedAutoignition Temperature (C):Not Determined

Flammability Limits in Air - Lower (%): 2
Flammability Limits in Air - Upper (%): 12.7

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed

surfaces. Closed containers may explode in fire. Decomposition in fire may

produce toxic gases.

Special Protective Equipment

for Fire-Fighters

Full protective clothing and approved self-contained breathing apparatus required

for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 3, Reactivity 0

HMIS Ratings: Health 2, Flammability 3, Physical Hazard 0, PPE: H

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary

Measures

Use appropriate protective equipment. Wear self-contained breathing apparatus in

enclosed areas.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and

remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Avoid breathing

mist. Wash hands after use. Launder contaminated clothing before reuse. Ground

and bond containers when transferring from one container to another.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep

container closed when not in use. Terpene containing products should be stored in

phenolic-lined metal, stainless steel, PET, or fluorinated plastic containers.

Product has a shelf life of 24 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering ControlsUse in a well ventilated area. Local exhaust ventilation should be used in areas

without good cross ventilation.

occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified

professional.

Organic vapor respirator.

In high concentrations, supplied air respirator or a self-contained breathing

apparatus.

Hand Protection Impervious rubber gloves. Nitrile gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Color:

Citrus

pH:

Specific Gravity @ 20 C (Water=1):

Density @ 20 C (lbs./gallon):

Liquid

Light amber

Citrus

8.7

0.926

7.65

Bulk Density @ 20 C (lbs/ft3): Not Determined

Boiling Point/Range (F): 310
Boiling Point/Range (C): 154
Freezing Point/Range (F): < 0
Freezing Point/Range (C): < -17.8

Vapor Pressure @ 20 C (mmHg):

Vapor Density (Air=1):

Not Determined

Not Determined

Percent Volatiles: 50-75

Evaporation Rate (Butyl Acetate=1): Not Determined Solubility in Water (g/100ml): Partially soluble Solubility in Solvents (g/100ml): Not Determined VOCs (lbs./gallon): Not Determined Viscosity, Dynamic @ 20 C (centipoise): Not Determined Viscosity, Kinematic @ 20 C (centistokes): Not Determined Partition Coefficient/n-Octanol/Water: Not Determined Molecular Weight (g/mole): Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid Keep away from heat, sparks and flame.

Incompatibility (Materials to

Avoid)

Strong oxidizers. Iodine pentafluorethylene Strong acids. Strong alkalis.

Hazardous Decomposition

Products

Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Sympotoms related to exposure

Acute Toxicity

Inhalation May cause respiratory irritation. May cause central nervous system depression including

headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech,

giddiness and unconsciousness.

Eye Contact May cause severe eye irritation.

Skin Contact May cause mild skin irritation. May cause skin defatting with prolonged exposure. May

cause an allergic skin reaction. May be absorbed through the skin and produce effects

similar to those caused by inhalation and/or ingestion.

Ingestion Irritation of the mouth, throat, and stomach. May cause abdominal pain, vomiting, nausea,

and diarrhea. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up

blood and pneumonia, which can be fatal.

Chronic Effects/Carcinogenicity Repeated overexposure may cause liver and kidney effects.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Citrus, extract	94266-47-4	> 5000 mg/kg	No data available	No data available
Terpenes and Terpenoids, sweet orange-oil	68647-72-3	No data available	No data available	No data available
Terpene	Proprietary	No data available	No data available	No data available
Isopropanol	67-63-0	4396 mg/kg(Rat) 3600 mg/kg (mouse)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Polyoxyalkylenes	Proprietary	No data available	No data available	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: May be toxic to aquatic life.

Acute Crustaceans Toxicity: May be toxic to aquatic life.

Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Citrus, extract	94266-47-4	EC50: 20.41 mg/l	LC50: >1000 mg/l	No information available	LC50: 34.73 mg/l (Acartia
		(Skeletonema costatum)	(Scophthalmus maximus)		tonsa)

Terpenes and Terpenoids, sweet orange-oil	68647-72-3	No information available	No information available	No information available	No information available
Terpene	Proprietary	No information available	TLM96: 550 mg/l (Pimephales promelas)	No information available	No information available
Isopropanol	67-63-0	EC50: > 1000 mg/l(Desmodesmus subspicatus)	LC50: 9640 mg/l (Pimephales promelas)	No information available	EC50: 13299 mg/l (Daphnia magna)
Polyoxyalkylenes	Proprietary	No information available	No information available	No information available	No information available

12.2 Persistence and degradability

No information available

12.3 Bioaccumulative potential

Bioaccumulative potential

Substances	Log Pow
Citrus, extract	4.23

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Incineration recommended in approved incinerator according to federal, state, and

local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1993, Flammable Liquid, N.O.S. (Contains Isopropanol, Terpene Hydrocarbons), 3, III, (28 C) NAERG 128

Canadian TDG

Flammable Liquid, N.O.S. (Contains Isopropanol, Terpene Hydrocarbons), 3, UN1993, III, (28 C)

ADR

UN1993, Flammable Liquid, N.O.S (Contains Isopropanol, Terpene Hydrocarbons), 3, III

Air Transportation

ICAO/IATA

UN1993, Flammable Liquid, N.O.S , 3 , III (Contains Isopropanol, Terpene Hydrocarbons)

Sea Transportation

IMDG

UN1993, Flammable Liquid, N.O.S (Contains Isopropanol, Terpene Hydrocarbons) , 3 , III , (28 C) EmS F-E, S-E

Other Transportation Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard Chronic Health Hazard

Fire Hazard

EPA SARA (313) Chemicals

This product contains toxic chemical(s) listed below which is(are) subject to the

reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Isopropanol//67-63-0

EPA CERCLA/Superfund Reportable Spill Quantity

nd Not applicable.

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does meet the criteria of a hazardous waste as

defined by the US EPA, because of:

Ignitability D001

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class B2 Flammable Liquids

D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS Not applicable

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

END OF MSDS