

Common Name: LOW VOC HH FLAT BLACK 9803817, V2178

Manufacturer: RUST-OLEUM

SDS Revision Date: 4/19/2001

SDS Format: No Format Specified

Item Number(s): 2FP66

Manufacturer Model Number(s): V2178

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION](#)

[SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS](#)

[SECTION 3 - HAZARDS IDENTIFICATION](#)

[SECTION 4 - FIRST AID MEASURES](#)

[SECTION 5 - FIRE FIGHTING MEASURES](#)

[SECTION 6 - ACCIDENTAL RELEASE MEASURES](#)

[SECTION 7 - HANDLING AND STORAGE](#)

[SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION](#)

[SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES](#)

[SECTION 10 - STABILITY AND REACTIVITY](#)

[SECTION 11 - TOXICOLOGICAL PROPERTIES](#)

[SECTION 12 - ECOLOGICAL INFORMATION](#)

[SECTION 13 - DISPOSAL CONSIDERATIONS](#)

[SECTION 14 - TRANSPORTATION INFORMATION](#)

[SECTION 15 - REGULATORY INFORMATION](#)

[SECTION 16 - OTHER INFORMATION](#)

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION



PRODUCT NAME: LOW VOC HH FLAT BLACK 9803817

IDENTIFICATION NUMBER: V2178 838

DATE PRINTED: 04/19/01

PRODUCT USE/CLASS: HARD HAT. AEROSOL PAINT

SUPPLIER:

RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, ILLINOIS
60061 USA

(847) 367-7700 RUST-OLEUM CORP.
8:00 AM-4:30 PM/24-HR EMER. ASSIST

MANUFACTURER:

RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY
VERNON HILLS, ILLINOIS
60061 USA

(847) 367-7700 RUST-OLEUM CORP.
8:00 AM-4:30 PM/24-HR EMER. ASSIST

PREPARER: MTM
PHONE: 847-816-2445
PREPARE DATE: 04/19/01

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS



ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT %	
			LESS THAN	
01	LIQUIFIED PETROLEUM GAS	68476-85-7	30.0%	
02	XYLENE	1330-20-7	25.0%	
03	ACETONE	67-64-1	20.0%	
04	MAGNESIUM SILICATE HYDRATE-TALC	14807-96-6	15.0%	
05	ETHYLBENZENE	100-41-4	10.0%	
06	AROMATIC HYDROCARBON	64742-95-6	5.0%	
07	CARBON BLACK	1333-86-4	5.0%	

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		MEXICAN	SKIN
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
01	1000 PPM	N.E.	1000 PPM	N.E.	N.E.	NO
02	100 PPM	150 PPM	100 PPM	N.E.	100 PPM	YES
03	750 PPM	1000 PPM	750 PPM	N.E.	N.E.	NO
04	10 MG/M3	N.E.	15 MG/M3	N.E.	N.E.	NO
05	100 PPM	125 PPM	100 PPM	N.E.	N.E.	YES
06	N.E.	N.E.	N.E.	N.E.	N.E.	YES
07	3.5 MG/M3	N.E.	3.5 MG/M3	N.E.	N.E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 3 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW:

HARMFUL IF INHALED. HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. HARMFUL IF INHALED. MAY EFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CONTENTS UNDER PRESSURE.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE - INHALATION:
HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING VAPORS OR MISTS. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS.

EFFECTS OF OVEREXPOSURE - INGESTION:
SUBSTANCE MAY BE HARMFUL IF SWALLOWED. ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. CONTAINS CARBON BLACK. CHRONIC INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMPSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO OCCUPATIONAL EXPOSURE TO CARBON BLACK. CARBON BLACK IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4-"NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

PRIMARY ROUTE(S) OF ENTRY: SKIN ABSORPTION, INHALATION, EYE CONTACT

SECTION 4 - FIRST AID MEASURES



FIRST AID - EYE CONTACT:

HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:

ASPIRATION HAZARD: DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 5 - FIRE FIGHTING MEASURES



FLASH POINT: -99 F

LOWER EXPLOSIVE LIMIT: 1.0%
UPPER EXPLOSIVE LIMIT: 12.8%

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR! WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

SPECIAL FIREFIGHTING PROCEDURES:
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

SECTION 6 - ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
EVACUATE THE AREA, REMOVE ALL SOURCES OF IGNITION AND VENTILATE WELL.
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS
SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE
WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL,
STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED
CONTAINERS.

SECTION 7 - HANDLING AND STORAGE



HANDLING:
WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A
WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER
IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR
MIST.

STORAGE:
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT,
SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I
FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE
ABOVE 120 DEGREES F.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION



ENGINEERING CONTROLS:
USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING
CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE
EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING
ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

RESPIRATORY PROTECTION:
A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2
REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A
RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN
ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN
CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE
LIMITS. PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A
POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN
UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER
CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE
PROTECTION.

SKIN PROTECTION:
USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS
MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE
SKIN PROTECTION.

EYE PROTECTION:
USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:
REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION

REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES



BOILING RANGE: -34 - 338 F

ODOR: SOLVENT

APPEARANCE: LIQUID

SOLUBILITY IN H2O: SLIGHT

FREEZE POINT: ND

VAPOR PRESSURE: ND

PHYSICAL STATE: LIQUID

VAPOR DENSITY: IS HEAVIER THAN AIR

ODOR THRESHOLD: ND

EVAPORATION RATE: IS FASTER THAN ETHER

SPECIFIC GRAVITY: 1.2309

pH @ 0.0%: ND

VISCOSITY: ND

COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 - STABILITY AND REACTIVITY



CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEGREES F. AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION PRODUCTS:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION IT EMITS ACRID SMOKE AND IRRITATING FUMES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION 11 - TOXICOLOGICAL PROPERTIES



COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME	LD50	LC50
LIQUIFIED PETROLEUM GAS	N.E.	N.E.

XYLENE	RAT 4300 MG/KG	RAT 5000 PPM 4HR
ACETONE	RAT 5800 MG/KG	RAT 50100 MG/M3 8H
MAGNESIUM SILICATE HYDRATE-TALC	NONE	NONE
ETHYLBENZENE	RAT 3500 MG/KG	N.A.
AROMATIC HYDROCARBON	4900 MG/KG (RAT)	N.E.
CARBON BLACK	N.A.	N.A.

SECTION 12 - ECOLOGICAL INFORMATION



ECOLOGICAL INFORMATION:

PRODUCT IS A MIXTURE OF LISTED COMPONENTS. ACCORDING TO OUR RAW MATERIAL SUPPLIERS, ALL COMPONENTS ARE LISTED ON THE TSCA INVENTORY AS REQUIRED OR MEET THE POLYMER EXEMPTION AS DEFINED IN SECTION 5.5.2 OF THE TOXIC SUBSTANCES CONTROL ACT.

SECTION 13 - DISPOSAL CONSIDERATIONS



DISPOSAL METHOD:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION



DOT PROPER SHIPPING NAME: AEROSOL

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2

HAZARD SUBCLASS: 1

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

RESP. GUIDE PAGE: 126

SECTION 15 - REGULATORY INFORMATION



U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA:

HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN
---------------	------------	----------------------

XYLENE	1330-20-7	25.0%
ETHYLBENZENE	100-41-4	10.0%

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT:

CHEMICAL NAME	CAS NUMBER
ALKYD RESIN SOLUTION	68552-41-0

PENNSYLVANIA RIGHT-TO-KNOW:

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3 %:

CHEMICAL NAME	CAS NUMBER
ALKYD RESIN SOLUTION	68552-41-0

CALIFORNIA PROPOSITION 65:

WARNING!

THE CHEMICAL(S) NOTED BELOW AND CONTAINED IN THIS PRODUCT, ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM:

CHEMICAL NAME	CAS NUMBER
---------------	------------

ACCORDING TO OUR RAW MATERIAL SUPPLIERS NO PROPOSITION 65 CHEMICALS EXIST IN THIS PRODUCT ABOVE OSHA DE MINIMUS LEVELS. ALL PRODUCTS COMPLY WITH LABEL PROVISIONS OF PROPOSITION 65.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS:

THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: A, B5, D2A, D2B

SECTION 16 - OTHER INFORMATION



HMIS RATINGS:

HEALTH : 2*
FLAMMABILITY: 4
REACTIVITY : 0

PREVIOUS MSDS REVISION DATE: 06/28/00

REASON FOR REVISION: TRANSPORTATION INFORMATION

LEGEND:

N.A.: NOT APPLICABLE
N.E.: NOT ESTABLISHED
N.D.: NOT DETERMINED
: NO INFORMATION.

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

PRODUCT: V2178 838
PREPARATION DATE: 04/19/01

