HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: HALAD® 344L (AQUEOUS) CEMENT ADDITIVE

Revision Date: 03-Jan-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: HALAD® 344L (AQUEOUS) CEMENT ADDITIVE

Synonyms: None Chemical Family: Blend

Application: Fluid Loss Additive

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431 Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Modified acrylamide copolymer		5 - 10%	Not applicable	Not applicable
Sodium hydroxide	1310-73-2	1 - 5%	2 mg/m ³	2 mg/m ³

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye and skin burns. May cause respiratory irritation. May be harmful if

swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation

develops or if breathing becomes difficult.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15

minutes. Get medical attention.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Not Determined

Flammability Limits in Air - Lower (%):

Not Determined

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media All standard firefighting media.

Special Exposure Hazards Decomposition in fire may produce toxic gases.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

NFPA Ratings: Health 1, Flammability 0, Reactivity 0
HMIS Ratings: Health 1, Flammability 0, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate spill and stop leak where safe. Contain spill with sand or other inert materials.

Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Wash hands after use. Launder

contaminated clothing before reuse.

Storage Information Store away from acids. Store in a cool, dry location.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area.

Respiratory ProtectionNot normally needed. But if significant exposures are possible then the following

respirator is recommended: Dust/mist respirator. (95%)

Hand Protection Impervious rubber gloves.

Skin Protection Normal work coveralls.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Color:

Odor:

Odorless
pH:

Liquid

White

Odorless

HALAD® 344L (AQUEOUS) CEMENT ADDITIVE Page 2 of 6

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity @ 20 C (Water=1): 1.04
Density @ 20 C (lbs./gallon): 8.66

Bulk Density @ 20 C (lbs/ft3): Not Determined **Boiling Point/Range (F):** Not Determined **Boiling Point/Range (C):** Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined **Percent Volatiles:** Not Determined **Evaporation Rate (Butyl Acetate=1):** Not Determined

Solubility in Water (g/100ml): Soluble

Solubility in Solvents (g/100ml): Not Determined

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistrokes):

Partition Coefficient/n-Octanol/Water:

Molecular Weight (g/mole):

Not Determined

Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None known.

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong acids.

Hazardous Decomposition

Products

Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye and skin contact.

Inhalation Causes severe respiratory irritation.

Skin Contact Causes severe skin irritation. May cause skin burns.

Eye Contact May cause eye burns.

Ingestion Causes burns of the mouth, throat and stomach.

Aggravated Medical Conditions None known.

Chronic Effects/Carcinogenicity No data available to indicate product or components present at greater than 1% are

chronic health hazards.

Other Information None known.

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

HALAD® 344L (AQUEOUS) CEMENT ADDITIVE Page 3 of 6

Primary Irritation Effect: Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive / Developmental Toxicity:

Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal MethodDisposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

Not restricted

Canadian TDG

Not restricted

ADR

Not restricted

Air Transportation

ICAO/IATA

Not restricted

Sea Transportation

IMDG

Not restricted

Other Transportation Information

Labels: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard

EPA SARA (313) Chemicals

This product contains toxic chemical(s) listed below which is(are) subject to the

reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Sodium Hydroxide//1310-73-2

EPA CERCLA/Superfund Reportable Spill Quantity

EPA Reportable Spill Quantity is 9165 Gallons based on Sodium hydroxide (CAS:

1310-73-2).

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class Un-Controlled

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer StatementThis information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

END OF MSDS

HALAD® 344L (AQUEOUS) CEMENT ADDITIVE Page 5 of 6