

**MATERIAL SAFETY DATA SHEET****Product Trade Name:** HALLIBURTON STIMULATION FLUID - 501**Revision Date:** 02-Jan-2013**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Trade Name:** HALLIBURTON STIMULATION FLUID - 501  
**Synonyms:** None  
**Chemical Family:** Blend  
**Application:** Acid

**Manufacturer/Supplier** Halliburton Energy Services  
P.O. Box 1431  
Duncan, Oklahoma 73536-0431  
Emergency Telephone: (281) 575-5000

**Prepared By** Chemical Compliance  
Telephone: 1-580-251-4335  
e-mail: fdunexchem@halliburton.com

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Toluene	108-88-3	10 - 30%	20 ppm	200 ppm
Hydrochloric acid	7647-01-0	10 - 30%	2 ppm	5 ppm

**3. HAZARDS IDENTIFICATION**

**Hazard Overview** May cause eye and skin burns. May cause respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. Repeated overexposure may cause liver and kidney effects. Flammable.

**4. FIRST AID MEASURES**

**Inhalation** If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

**Skin** In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

**Eyes** In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

**Ingestion** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Notes to Physician** Not Applicable

## 5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	Not Determined
Flash Point/Range (C):	Not Determined
Flash Point Method:	Not Determined
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

**Fire Extinguishing Media** Water fog, carbon dioxide, foam, dry chemical.

**Special Exposure Hazards** May form explosive mixtures with strong alkalis. Decomposition in fire may produce toxic gases. Reaction with steel and certain other metals generates flammable hydrogen gas. Do not allow runoff to enter waterways.

**Special Protective Equipment for Fire-Fighters** Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

**NFPA Ratings:** Health 2, Flammability 3, Reactivity 0  
**HMS Ratings:** Health 2, Flammability 3, Reactivity 0

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautionary Measures** Use appropriate protective equipment.

**Environmental Precautionary Measures** Prevent from entering sewers, waterways, or low areas.

**Procedure for Cleaning / Absorption** Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Neutralize to pH of 6-8. Scoop up and remove.

## 7. HANDLING AND STORAGE

**Handling Precautions** Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another.

**Storage Information** Store away from alkalis. Store away from oxidizers. Store in a cool well ventilated area. Keep from heat, sparks, and open flames. Keep container closed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls** Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

**Respiratory Protection** Organic vapor/acid gas respirator with a dust/mist filter.

**Hand Protection** Impervious rubber gloves.

**Skin Protection** Full protective chemical resistant clothing. Rubber boots.

**Eye Protection** Chemical goggles; also wear a face shield if splashing hazard exists.

**Other Precautions** Eyewash fountains and safety showers must be easily accessible.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Clear colorless
Odor:	Pungent acrid
pH:	0.8
Specific Gravity @ 20 C (Water=1):	1.02
Density @ 20 C (lbs./gallon):	8.50
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Miscible
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

## 10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers. Strong alkalis.
Hazardous Decomposition Products	Flammable hydrogen gas. Chlorine. Hydrogen sulfide. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

## 11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	Causes severe respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.
Skin Contact	Causes severe burns. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.
Eye Contact	Causes severe eye irritation May cause eye burns.
Ingestion	Causes burns of the mouth, throat and stomach. May cause abdominal pain, vomiting, nausea, and diarrhea. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. Aspiration can be a hazard if this material is swallowed.

<b>Aggravated Medical Conditions</b>	Skin disorders. Lung disorders.
<b>Chronic Effects/Carcinogenicity</b>	Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart, central nervous system and spleen damage. Prolonged, excessive exposure may cause erosion of the teeth. Prolonged or repeated exposure may cause embryo and fetus toxicity.
<b>Other Information</b>	None known.
<b>Toxicity Tests</b>	
<b>Oral Toxicity:</b>	Not determined
<b>Dermal Toxicity:</b>	Not determined
<b>Inhalation Toxicity:</b>	Not determined
<b>Primary Irritation Effect:</b>	Not determined
<b>Carcinogenicity</b>	Not determined
<b>Genotoxicity:</b>	Not determined
<b>Reproductive / Developmental Toxicity:</b>	Not determined

## 12. ECOLOGICAL INFORMATION

<b>Mobility (Water/Soil/Air)</b>	Not determined
<b>Persistence/Degradability</b>	Not determined
<b>Bio-accumulation</b>	Not determined

### Ecotoxicological Information

<b>Acute Fish Toxicity:</b>	Not determined
<b>Acute Crustaceans Toxicity:</b>	Not determined
<b>Acute Algae Toxicity:</b>	Not determined
<b>Chemical Fate Information</b>	Not determined
<b>Other Information</b>	Not applicable

## 13. DISPOSAL CONSIDERATIONS

<b>Disposal Method</b>	Disposal should be made in accordance with federal, state, and local regulations.
<b>Contaminated Packaging</b>	Follow all applicable national or local regulations.

## 14. TRANSPORT INFORMATION

### Land Transportation

#### DOT

UN2924, Flammable Liquid, Corrosive, N.O.S. (Contains Toluene, Hydrochloric Acid), 3, (8), II, (4.4 C)  
 RQ (Toluene - 1816 kg.)  
 NAERG 132

**Canadian TDG**

Flammable Liquid, Corrosive, N.O.S.(Contains Toluene, Hydrochloric Acid), 3, (8), UN2924, II, (4.4 C)

**ADR**

UN2924, Flammable Liquid, Corrosive, N.O.S.(Contains Toluene, Hydrochloric Acid), 3, (8), II

**Air Transportation****ICAO/IATA**

UN2924, Flammable Liquid, Corrosive, N.O.S., 3, (8), II  
(Contains Toluene, Hydrochloric Acid)  
RQ (Toluene - 1816 kg.)

**Sea Transportation****IMDG**

UN2924, Flammable Liquid, Corrosive, N.O.S.(Contains Toluene, Hydrochloric Acid), 3, (8), II, (4.4 C)  
RQ (Toluene - 1816 kg.)  
EmS F-E, S-C

**Other Transportation Information**

**Labels:** Flammable Liquid

**15. REGULATORY INFORMATION****US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely Hazardous Substances** Not applicable

**EPA SARA (311,312) Hazard Class** Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

**EPA SARA (313) Chemicals** This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:  
Toluene//108-88-3

**EPA CERCLA/Superfund Reportable Spill Quantity** EPA Reportable Spill Quantity is 490 Gallons based on Toluene (CAS: 108-88-3).

**EPA RCRA Hazardous Waste Classification** If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:  
  
Ignitability D001

**California Proposition 65** The California Proposition 65 regulations apply to this product.

**MA Right-to-Know Law** One or more components listed.

<b>NJ Right-to-Know Law</b>	One or more components listed.
<b>PA Right-to-Know Law</b>	One or more components listed.
<b>Canadian Regulations</b>	
<b>Canadian DSL Inventory</b>	All components listed on inventory or are exempt.
<b>WHMIS Hazard Class</b>	B2 Flammable Liquids E Corrosive Material D2B Toxic Materials

## **16. OTHER INFORMATION**

### **The following sections have been revised since the last issue of this MSDS**

Not applicable

**Additional Information** For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement** This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

**\*\*\*END OF MSDS\*\*\***