2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

DATE: PRODUCT NAME: **EzFlow High Definition - Clear Powder** 11/17/2005

FORMULA: 30-2048 REV.

Section 1. Material Identification and Information

Hazardous Ingredients:

Component	CAS#	%	TOXICOLOGICAL DATA
Acrylates Copolymer	25685-29-4	60-100%	ACGIH TLV/TWA:
			10mg/m ³
			OSHA PEL/TWA:
			15mg/m ³
Benzoyl Peroxide	94-36-0	0-1%	ACGIH TLV/TWA:
			5mg/m ³
			OSHA PEL/TWA:
			5mg/m ³

Section 2. Physical / Chemical Characteristics

Boiling Point: N/A Specific Gravity: N/A

(@ 25°C) Vapor Pressure: Not Determined

(mm Hg and Temperature)

Melting Point: Vapor Density: Not Determined **Evaporation Rate: N/A**

(Air = 1)(BuAc = 1)

Solubility in Water: Insoluble Appearance: Fine, white powder

Odor: Faint odor in bulk

Section 3. Fire and Explosion Hazard Data

304°C, 580°F Flash Point and Method Used:

Auto-Ignition Temperature: N/A

Flammability Limits in Air % by Volume: LEL: N/A

UEL: N/A

Extinguisher Media: Water, carbon dioxide, or dry chemical

Special Fire Fighting Procedures: Avoid extinguishing methods which may generate dust clouds. Water

> stream can disperse bust into air, producing a fire hazard and possible explosion hazard if exposed to ignition source. Fire-fighters should wear

N/A

N/A

self-contained breathing apparatus.

Water Reactive:

Unusual Fire and Explosion Hazards: Polymer dust is combustible. The explosive limits of the polymer

particles suspended in air are approximately those of coal dust.

Explosion Hazard: Firefighters should wear self-contained breathing apparatus.

Sensitive to Hazard: No. Sensitive to Static Discharge: No.

2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

Eye Contact:

Skin Contact:

Inhalation:

MATERIAL SAFETY DATA SHEET

EzFlow High Definition - Clear Powder 30-2048				11/17/2005		
ity Hazard Data						
☑ Stable Heating above 240°C	☐ Unstable , 464°F					
rials to Avoid): Strong oxidizing ager	nts.					
ition:						
Methacrylate Monom	er and Oxides of Carbon when	burned.				
ation: ☐ May Occur	☑ Will Not Occur					
Hazard Data						
iry: ⊠ Inhalation	7 Skin Absorption	□ Indestion		I Evos		
M IIIIIalallon	M Skill Absorption	□ ingestion	Į¥.	l Eyes		
ПИТР	T IARC Monograph		IZI N	ot Listed		
	LIAIC Monograph	1 0011A	E 11	ot Listed		
Eye Contact:	Higher concentration can irritate eyes. May cause eye irritation or damage.					
Skin Contact: Inhalation:	Repeated or prolonged exposure may cause allergic skin rashes. Possible temporary discomfort due to inhalation of dust concentration above the permissible exposure limit. Dust may cause irritation of the nose, throat, and lungs.					
Ingestion:	-					
•		, , , , , ,				
skin and Respiratory Classified, no matter to prevent possible in For decomposition procan irritate eyes, respheadaches, nausea, and prolonged over eskin rashes, eye corroor damage.	tract may be irritated by gross of how they are generated. Avoid ritation. oduct: Methyl Methacrylate Mo biratory system and cause skin staggering gait, confusion, drow xposure may cause permanent osion and permanent injury, as	overexposure to Pad inhalation of dust. onomer; Liquid or his rashes. Prolonged wsiness and unconst brain and nervous well as changes in	rticulates Keep du igh vapor exposure sciousnes system d liver and	, Not Otherwise ust out of eyes concentration e can lead to ss. Repeated damage, allergic kidney function		
	ity Hazard Data Stable Heating above 240°C rials to Avoid): Strong oxidizing agerition: Methacrylate Monomation: ☐ May Occur Hazard Data Ty: ☐ Inhalation ☐ NTP Eye Contact: Inhalation: Ingestion: For Polymer: OSHA oskin and Respiratory Classified, no matter to prevent possible in For decomposition proan irritate eyes, respheadaches, nausea, and prolonged over eskin rashes, eye corroor damage.	Tity Hazard Data Stable □ Unstable Heating above 240°C, 464°F Tials to Avoid): Strong oxidizing agents. Ition: Methacrylate Monomer and Oxides of Carbon when ation: □ May Occur ☑ Will Not Occur Hazard Data Ty: ☑ Inhalation ☑ Skin Absorption □ NTP □ IARC Monograph Eye Contact: Higher concentration can irridamage. Skin Contact: Repeated or prolonged exponose, throat, and lungs. Ingestion: Higher concentration can irridatory above the permissible exposonose, throat, and lungs. Ingestion: Higher concentration can irridatory and Respiratory tract may be irritated by gross of Classified, no matter how they are generated. Avoid to prevent possible irritation. For decomposition product: Methyl Methacrylate Mecan irritate eyes, respiratory system and cause skin headaches, nausea, staggering gait, confusion, drow and prolonged over exposure may cause permanen skin rashes, eye corrosion and permanent injury, as or damage.	ity Hazard Data ☑ Stable ☐ Unstable Heating above 240°C, 464°F rials to Avoid): Strong oxidizing agents. ition: Methacrylate Monomer and Oxides of Carbon when burned. ation: ☐ May Occur ☑ Will Not Occur Hazard Data ry: ☑ Inhalation ☑ Skin Absorption ☐ Ingestion ☐ NTP ☐ IARC Monograph ☐ OSHA Eye Contact: Higher concentration can irritate eyes. May cau damage. Skin Contact: Repeated or prolonged exposure may cause all Inhalation: Possible temporary discomfort due to inhalation above the permissible exposure limit. Dust may nose, throat, and lungs. Ingestion: Higher concentration can irritate respiratory syst For Polymer: OSHA classifies this material as Particulates, Not Otherwiskin and Respiratory tract may be irritated by gross overexposure to Pa Classified, no matter how they are generated. Avoid inhalation of dust. to prevent possible irritation. For decomposition product: Methyl Methacrylate Monomer; Liquid or h can irritate eyes, respiratory system and cause skin rashes. Prolonged headaches, nausea, staggering gait, confusion, drowsiness and uncons and prolonged over exposure may cause permanent brain and nervous skin rashes, eye corrosion and permanent injury, as well as changes in or damage.	ity Hazard Data ☑ Stable ☐ Unstable Heating above 240°C, 464°F itals to Avoid): Strong oxidizing agents. ition: Methacrylate Monomer and Oxides of Carbon when burned. ition: ☐ May Occur ☑ Will Not Occur Hazard Data ITY: ☑ Inhalation ☑ Skin Absorption ☐ Ingestion ☑ May Cause eye in damage. Skin Contact: Higher concentration can irritate eyes. May cause eye in damage. Skin Contact: Repeated or prolonged exposure may cause allergic skin Inhalation: Possible temporary discomfort due to inhalation of dust cabove the permissible exposure limit. Dust may cause in nose, throat, and lungs. Ingestion: Higher concentration can irritate respiratory system. For Polymer: OSHA classifies this material as Particulates, Not Otherwise Classiskin and Respiratory tract may be irritated by gross overexposure to Particulates Classified, no matter how they are generated. Avoid inhalation of dust. Keep dust to prevent possible irritation. For decomposition product: Methyl Methacrylate Monomer; Liquid or high vapor can irritate eyes, respiratory system and cause skin rashes. Prolonged exposure headaches, nausea, staggering gait, confusion, drowsiness and unconsciousness and prolonged over exposure may cause permanent brain and nervous system oskin rashes, eye corrosion and permanent injury, as well as changes in liver and		

help if discomfort persists.

Flush with water for 15 minutes, including under eyelids. Get medical

Wash with soap and water. Get medical help if discomfort persists. Remove to fresh air. Get medical help if discomfort persistsage 2 of 6



2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EzFlow High Definition - Clear Powder DATE: 11/17/2005

FORMULA: 30-2048 REV.

Ingestion: Rinse mouth out with water. Call doctor if amount was large.

Section 6. Control and Protective Measures

General:

Dust collectors are recommended for handling powder in bulk.

Respiratory Protections (Specific Type):

Avoid breathing dust and mist. Use dust mask.

Protective Gloves:

Minimize contamination by following good industrial practice. Wearing nitrile, neoprene, pvc, latex or other impermeable gloves is recommended.

Eye Protection:

Use safety glasses and have eye flushing equipment immediately available.

Ventilation to be Used:

Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well ventilated. Use explosion-proof equipment. Provide ventilation if necessary to control exposure levels below airborne exposure limits.

Other Protective Clothing and Equipment:

No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the EC members states, or US OSHA. Provide eyewash, safety shower and impervious clothing are recommended. High temperature processing equipment should be well be ventilated.

Hygienic Work Practices:

Good Manufacturing Practices.

Section 7. Precautions for Safe Handling and Use / Leak Procedures

Steps to be Taken if Material is Spilled or Released:

Before cleaning any spill or leak, individuals involved in spill clean-up must wear appropriate Personal Protective Equipment. Wear appropriate personal protective equipment (e.g., goggles, gloves). Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills. Dispose of properly in accordance with local, state, and federal regulations. Wash all affected areas with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

Waste Disposal Methods:

Dispose in a landfill or incinerate according to Federal, State, and Local regulations.

Disposal of Empty Containers:

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual material, associated with empty containers. It is our policy to discourage the reuse of empty containers and to dispose of all empty containers properly, in accordance with Federal, State, and Local regulations.

Page 3 of 6

2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EzFlow High Definition - Clear Powder DATE: 11/17/2005

FORMULA: 30-2048 REV.

Precautions for Handling:

Use in well ventilated areas. Avoid contact with skin, eyes, and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping.

Precautions for Storage:

Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Material should be stored in secondary containers as appropriate. Keep container closed to prevent water absorption and contamination.

Explosion Hazard:

Polymer dust is combustible, explosive limits of the polymer particles suspended in air are approximately those of coal dust.

Industrial Hygiene Practices:

Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans.). After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling product.

Section 8. Toxicological Properties

Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology

data for the components of the product, which are found in scientific literature. These data have

not been presented in this document.

Mutagenicity Data: This product is not reported to produce mutagenic effects in humans.

Reproductive Toxicity Data:

For Polymer: Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.

Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.

Section 9. Ecological Information

Aquatic Toxicity:

For Polymer: There is no specific data available for this product; however, very large releases of this product

may be harmful or fatal to overexposed aquatic life.

Environmental Fate:

There is no specific data available for this product.

Section 10. Transportation

DOT/UN Shipping Name: Non-Regulated Material

Section 11. Regulatory Information

Clean Air Act: HAP/ODS:

2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EzFlow High Definition - Clear Powder DATE: 11/17/2005

FORMULA: 30-2048 REV.

This product contains the following hazardous air pollutants (HAP's) or ozone depleting substances (ODS's) as defined by the U.S. Clean Air Act:

* NONE

Clean Water Act: Priority Pollutant:

This product contains the following chemicals listed under the U.S. Clean Water Act Priority

Pollutant List:

* NONE

FDA: Food Packaging Status:

This product has not been cleared by the FDA for use in food packaging and/or other

applications as an indirect food additive.

Occupational Safety and Health Act:

This product is not considered a hazardous chemical under the OSHA Hazard Communication

Standard.

RCRA:

This product contains no chemicals considered to be hazardous waste under RCRA (40 CFR

261).

SARA Title III: Section 302 (TPQ)

This product contains no chemicals regulated under Sec. 302 as extremely hazardous

substances.

SARA Title III: Section 302 (RQ)

This product contains no chemicals regulated under Sec. 304 as extremely hazardous

chemicals for emergency release notification ("CERCLA" List).

SARA Title III: Section 311-312:

This product does not contain hazardous substances under the OSHA Hazard Communication

Standard, and is not regulated under Section 311-312 (40 CFR 370).

SARA Title III: Section 313:

This product contains the following chemicals outlined in SARA Title III: Section 313: Benzoyl

Peroxide CAS #94-36-0.

TSCA Section 8(b) Inventory:

This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA

premanufacture notification requirements.

TSCA Significant New Use Rule:

None of the chemicals listed have a SNUR under TSCA.

State Regulations:

CA Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0

MA Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0 NJ Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0

PA Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0

FL Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0

MN Right-to-Know Law: Benzoyl Peroxide CAS #94-36-0

Section 12. Other Information



2220 GASPAR AVENUE LOS ANGELES, CA 90040 CHEM-TEL: (800) 255-3924

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: EzFlow High Definition - Clear Powder DATE: 11/17/2005

FORMULA: 30-2048 REV.

Hazardous Material Identification System (HMIS) Rating:

Health = 1/Flammability = 1/Reactivity = 1

Personal Protective Equipment: Gloves and Safety Glasses or Chemical Splash Goggles.

National Fire Protection Association (NFPA) Hazard Identification Rating:

Health = 1/Flammability = 1/Reactivity = 1