#### **HALLIBURTON**

# MATERIAL SAFETY DATA SHEET

Product Trade Name: HIGH TEMPERATURE BAILER CEMENT

Revision Date: 04-Jan-2011

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: HIGH TEMPERATURE BAILER CEMENT

Synonyms: None
Chemical Family: Cement
Application: Cement

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	<b>CAS Number</b>	PERCENT	<b>ACGIH TLV-TWA</b>	OSHA PEL-TWA
Portland cement	65997-15-1	30 - 60%	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
Crystalline silica, quartz	14808-60-7	30 - 60%	0.025 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
				%SiO2 + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

#### 3. HAZARDS IDENTIFICATION

Hazard Overview CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation.

**DANGER! - CHRONIC HEALTH HAZARD** 

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney

disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

#### 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation

develops or if breathing becomes difficult.

**Skin** Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

**Ingestion** Under normal conditions, first aid procedures are not required.

Notes to Physician Not Applicable

#### 5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Flash Point Method:

Autoignition Temperature (F):

Autoignition Temperature (C):

Flammability Limits in Air - Lower (%):

Flammability Limits in Air - Upper (%):

Not Determined

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media None - does not burn.

Special Exposure Hazards Not applicable.

Special Protective Equipment for Not applicable.

Fire-Fighters

NFPA Ratings: Health 1, Flammability 0, Reactivity 0
HMIS Ratings: Health 1\*, Flammability 0, Reactivity 0

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

**Environmental Precautionary** 

**Measures** 

None known.

**Procedure for Cleaning /** 

**Absorption** 

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate

methods for collection, storage and disposal.

# 7. HANDLING AND STORAGE

**Handling Precautions** Avoid contact with eyes, skin, or clothing. This product contains quartz, cristobalite,

and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is

slippery when wet.

**Storage Information** Store in a cool, dry location. Use good housekeeping in storage and work areas to

prevent accumulation of dust. Close container when not in use. Product has a shelf

life of 24 months.

# **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls

Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits listed in Section 2.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when

using this product.

Hand Protection Normal work gloves.

**Skin Protection** Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

**Eye Protection** Wear safety glasses or goggles to protect against exposure.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid
Color: Gray
Odor: Odorless
pH: 12.4

Specific Gravity @ 20 C (Water=1): Not Determined Density @ 20 C (lbs./gallon): Not Determined Bulk Density @ 20 C (lbs/ft3): Not Determined **Boiling Point/Range (F):** Not Determined Boiling Point/Range (C): Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined

Percent Volatiles:

Evaporation Rate (Butyl Acetate=1):

Not Determined

Solubility in Water (g/100ml): Insoluble

Solubility in Solvents (g/100ml):

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistrokes):

Partition Coefficient/n-Octanol/Water:

Molecular Weight (g/mole):

Not Determined

Not Determined

#### 10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

**Conditions to Avoid** Keep away from any contact with water.

Incompatibility (Materials to

Avoid)

Hydrofluoric acid.

**Hazardous Decomposition** 

Products

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or

cristobalite (1470 C).

Additional Guidelines Not Applicable

# 11. TOXICOLOGICAL INFORMATION

**Principle Route of Exposure** Eye or skin contact, inhalation.

#### Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

**Skin Contact** 

Can dry skin. May cause an allergic skin reaction. May cause alkali burns with confined contact.

Eye Contact

May cause severe eye irritation.

Ingestion

None known

**Aggravated Medical Conditions** 

Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

**Chronic Effects/Carcinogenicity** 

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Other Information

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).

**Toxicity Tests** 

Oral Toxicity:

Dermal Toxicity:

Not determined

Not determined

Not determined

Not determined

Not determined

Not determined

Carcinogenicity Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June

1997).

Genotoxicity: Not determined

Reproductive /

Not determined

**Developmental Toxicity:** 

## 12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not applicable

Bio-accumulation Not determined

# **Ecotoxicological Information**

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate InformationNot determinedOther InformationNot applicable

#### 13. DISPOSAL CONSIDERATIONS

**Disposal Method**Bury in a licensed landfill according to federal, state, and local regulations.

**Contaminated Packaging** Follow all applicable national or local regulations.

#### 14. TRANSPORT INFORMATION

# **Land Transportation**

DOT

Not restricted

#### **Canadian TDG**

Not restricted

**ADR** 

Not restricted

# Air Transportation

ICAO/IATA

Not restricted

# Sea Transportation

**IMDG** 

Not restricted

## Other Shipping Information

Labels: None

#### **REGULATORY INFORMATION** 15.

#### **US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely Hazardous Substances** 

Not applicable

**EPA SARA (311,312) Hazard** 

Class

Acute Health Hazard Chronic Health Hazard

This product does not contain a toxic chemical for routine annual "Toxic Chemical **EPA SARA (313) Chemicals** 

Release Reporting" under Section 313 (40 CFR 372).

**EPA CERCLA/Superfund Reportable Spill Quantity**  Not applicable.

**EPA RCRA Hazardous Waste** 

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

**California Proposition 65** The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

**Canadian DSL Inventory** All components listed on inventory.

**WHMIS Hazard Class** E Corrosive Material D2A Very Toxic Materials

Crystalline silica

## OTHER INFORMATION

# The following sections have been revised since the last issue of this MSDS

Not applicable

**Additional Information** For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement** This information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

# \*\*\*END OF MSDS\*\*\*