



1. Chemical product and company identification

Product name STICK WAX

MSDS # 464402

Historic MSDS #: 08039-AT

Code 464402-US10

Manufacturer Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563

Supplier Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563
Product Information: 1-800-621-2661

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Refined paraffin wax	8002-74-2	20 - 25
hydrocarbon waxes, petroleum, hydrotreated microcryst.	64742-60-5	10 - 15

3. Hazards identification

Physical state Waxy solid.

Color Tan.

Emergency overview CAUTION!

MAY CAUSE EYE IRRITATION.
MAY CAUSE SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

Avoid contact with eyes, skin and clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

Routes of entry Skin Contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes May cause eye irritation.

Skin May cause skin irritation.

Inhalation May cause respiratory tract irritation.

Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.

Medical conditions aggravated by over-exposure None identified.

See toxicological information (section 11)

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if irritation develops.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

5. Fire-fighting measures

Flammability of the product	May be combustible at high temperature.
Flash point	243.3 °C (Open cup) Cleveland.
Products of combustion	These products are carbon oxides (CO, CO ₂).
Unusual fire/explosion hazards	Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
Fire-fighting media and instructions	In case of fire, use water spray (fog), foam or dry chemicals.
Protective clothing (fire)	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
Special remarks on fire hazards	No additional remark.

6. Accidental release measures

Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Environmental precautions and clean-up methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

7. Handling and storage

Handling	Avoid contact with skin and clothing. Avoid contact with eyes. Use only with adequate ventilation In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Product name STICK WAX	MSDS # 464402-US10	Page: 2/5
Version 1	Date of issue 04/20/2006.	Format US
	Build 4.2.7	Language ENGLISH. (ENGLISH)

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Refined paraffin wax

hydrocarbon waxes, petroleum, hydrotreated microcryst.

Occupational exposure limits

ACGIH TLV (United States, 1/2005).

TWA: 2 mg/m³ 8 hour(s). Form: Fume

ACGIH (United States).

TWA: 5 mg/m³ 8 hour(s).

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s).

Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes

Avoid contact with eyes. Chemical splash goggles.

Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

Wear suitable gloves.

Not available.



Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state

Waxy solid.

Color

Tan.

Heat of combustion

Not available.

Melting point / Range

62.778 to 79.444 °C

Density

900 kg/m³ (0.9 g/cm³) at 15.6°C

Solubility

insoluble in water.

10. Stability and reactivity

Stability and reactivity

The product is stable.

Conditions to avoid

None known.

Incompatibility with various substances

Strong oxidizing materials

Hazardous decomposition products

Not available.

Hazardous polymerization

Will not occur.

Product name STICK WAX

MSDS #

464402-US10

Page: 3/5

Version 1

Date of issue 04/20/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)

11. Toxicological information

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.

Reproductive effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.

Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

RCRA Waste Code(s)

USED OIL

Remarks

No additional remark.

[Consult your local or regional authorities.](#)

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: STICK WAX: Immediate (Acute) Health Hazard

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: This material is not regulated under CERCLA Sections 103 and 107.

State regulations

Massachusetts RTK: Refined paraffin wax

Pennsylvania RTK: Refined paraffin wax (generic environmental hazard)

Product name STICK WAX

MSDS #

464402-US10

Page: 4/5

Version 1

Date of issue 04/20/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)

Inventories

California Prop 65: No products were found
AUSTRALIAN INVENTORY (AICS): Not determined.
CANADA INVENTORY (DSL): In compliance.
CHINA INVENTORY (IECS): Not determined.
EC INVENTORY (EINECS/ELINCS): Not determined.
JAPAN INVENTORY (ENCS): Not determined.
KOREA INVENTORY (ECL): Not determined.
PHILIPPINE INVENTORY (PICCS): Not determined.

16. Other information

Label requirements

CAUTION!
MAY CAUSE EYE IRRITATION.
MAY CAUSE SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health 1 -
Flammability 1
Physical 0
Hazard
Personal B
protection

National Fire
Protection
Association
(U.S.A.)



Other special considerations

No additional remark.

History

Date of issue

04/20/2006.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name STICK WAX

MSDS #

464402-US10

Page: 5/5

Version 1

Date of issue 04/20/2006.

Format US

Language ENGLISH.

Build 4.2.7

(ENGLISH)