

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677

CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **IVC 2025 FLEX-PRIM FIBERGLASS BACKED SHEET ACR. LATEX PRIMER**
ITEM NUMBER: 2025-1-IVC
ITEM DESCRIPTION: IVC 2025 Flex Prim Fiberglass Backed Sheet Vinyl 1-GAL
PRODUCT DESCRIPTION: ACRYLIC LATEX SOLUTION
CHEMICAL FAMILY: ACRYLIC LATEX
REVISION DATE: 06/17/14 REVIEW DATE: / / PRINT DATE: 07/21/14 PRINT TIME: 13:55

MANUFACTURED FOR: IVC US INC.
101 IVC DRIVE
DALTON, GA 30721
UNITED STATES

PHONE NO.: (706) 529-2600
www.ivcgroup.us

HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

No Hazardous ingredients per current OSHA regulations.

SECTION III PHYSICAL DATA

<u>Hazard</u>	<u>CAS #</u>	<u>WT/Wt % Less Than</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS		
BOILING POINT:	212 DEGREES F	
LBS/GAL:	8.4 - 8.8	
SOLUBILITY IN WATER: MISCIBLE		
EVAPORATION RATE (nBuAc=1): SAME AS WATER		
VAPOR DENSITY (AIR=1): >1		
VAPOR PRESSURE, MM, HG AT 20 DEGREES C: 250 MPAS		
PERCENT VOLATILE: 83 - 87 (BY WEIGHT)		
APPEARANCE AND ODOR: CREAM COLORED LIQUID, SWEET AROMATIC- MILD		
V.O.C. less water, less exempt solvents: 0 g/l (cvalculated)		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

PRODUCT NAME: **IVC 2025 FLEX-PRIM FIBERGLASS BACKED SHEET ACR. LATEX PRIMER**
ITEM NUMBER: 2025-1-IVC
ITEM DESCRIPTION: IVC 2025 Flex Prim Fiberglass Backed Sheet Vinyl 1-GAL
REVISION DATE: 06/17/14 REVIEW DATE: / / PRINT DATE: 07/21/14 PRINT TIME: 13:55

DOT CATEGORY: NOT REGULATED
FLASH POINT: NONE LEL: NA
EXTINGUISHING MEDIA: NONE REQUIRED
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
SPECIAL FIRE FIGHTING PROCEDURES: NONE

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:
INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.
EYES: VAPOR MAY CAUSE IRRITATION.
SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.
INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

HEALTH EFFECTS OR RISK FROM EXPOSURE:
ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.
CHRONIC: NOT KNOWN

SECTION VI FIRST AID PROCEDURES

FIRST AID PROCEDURES:
EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.
SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.
INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.
INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VII HANDLING AND STORAGE

PRECAUTION FOR HANDLING AND STORING: DO NOT PUNCTURE. PROTECT AGAINST PHYSICAL DAMAGE. AVOID BREATHING BUILD-UP OF VAPORS. USE WITH ADEQUATE VENTILLATION.
KEEP OUT OF THE REACH OF CHILDREN.
PROTECT FROM FREEZING. STORE IN A DRY PLACE (50 - 90 DEGREES F).
CAUTION: DO NOT TAKE INTERNALLY. IF INGESTION , DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.
RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.
CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT CONTACT.
EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD
OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.
WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.
PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

SECTION IX SPILL OR LEAK PROCEDURES

PRODUCT NAME: **IVC 2025 FLEX-PRIM FIBERGLASS BACKED SHEET ACR. LATEX PRIMER**
ITEM NUMBER: 2025-1-IVC
ITEM DESCRIPTION: IVC 2025 Flex Prim Fiberglass Backed Sheet Vinyl 1-GAL
REVISION DATE: 06/17/14 REVIEW DATE: / / PRINT DATE: 07/21/14 PRINT TIME: 13:55

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

SECTION X STABILITY AND REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: KEEP AWAY FROM EXTREME TEMPERATURE CONDITIONS.

INCOMPATIBILITY-MATERIALS TO AVOID: METAL SALTS MAY COAGULATE THE PRODUCT.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION XI TOXICOLOGICAL PROPERTIES

NOT AVAILABLE

SECTION XII ECOLOGICAL INFORMATION

NOT AVAILABLE

SECTION XIII DISPOSAL CONSIDERATION

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS

SECTION XIV: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT APPLICABLE

PROPER HAZARD CLASS: NOT HAZARDOUS

HAZARD CODE: NOT HAZARDOUS

SECTION XV REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200) HAZARD CLASS (ES): NONE

SARA TITLE III SECTION 312 HAZARD CLASS: NONE

EPA SARA TITLE III SECTION 313: NONE

SECTION XVI OTHER INFORMATION

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
