



SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD
(HCS) 29 CFR 1910.1200

Page 1 of 5
Revision Date 6/1/2015
Supersedes Date 1/8/2014

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** JAX Big Jim (Aerosol)
Part number: JAX206
- 1.2 Identified uses:** Lubricant where there is no possibility of contact with food
Uses advised against: Not for use where there is the possibility of contact with food. Other uses advised against may be specified elsewhere in this SDS.
- 1.3 Supplier:** Pressure-Lube Inc. JAX
W134 N5373 Campbell Drive
Menomonee Falls, WI 53051 USA
Email contact: info@jax.com
Non-emergency contact: Phone: 262-781-7660 Fax: 262-781-3906
- 1.4 Emergency telephone:** INFOTRAC:
North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926
International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARDS IDENTIFICATION

- 2.1 GHS Classification:**
Hazard class(es): Flammable Aerosol Cat. 1, Aspiration Toxicity Cat. 1, Aquatic Chronic Cat. 3
- 2.2 Label elements**
Pictograms:  
- Signal word:** Danger
- Hazard-determining components of labeling:** Solvent naphtha (petroleum), light arom.*
- Hazard statements:** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.
- Precautionary statements:** Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. IF SWALLOWED: Immediately call a poison center/ doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.
- Additional information** Not applicable
- 2.3 Other hazards**
Results of PBT and vPvB assessment
PBT: Not applicable
vPvB: Not applicable

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Composition	Components	%	CAS #	Impurities
	Asphalt	10-25	8052-42-4	None
	Propane	10-25	74-98-6	None
	Solvent naphtha (petroleum), light arom.*	10-25	64742-95-6	None
	Butane	2.5-10	106-97-8	None
	Acetone	2.5-10	67-64-1	None
	Pentane	2.5-10	109-66-0	None
	Molybdenum disulfide	<2.5	1317-33-5	None

3.2 Additional information

*Contains less than 0.1 % w/w benzene.

SECTION 4. FIRST AID MEASURES

- 4.1 First aid measures**
Eye contact:

persists, consult a physician.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

Ingestion: If swallowed, DO NOT induce vomiting. As a precaution, give the person a glass of water to drink and seek medical attention. Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment available.

No further relevant information available.

SECTION 5. FIREFIGHTING MEASURES

5.1 Suitable extinguishing media: Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.

Unsuitable extinguishing media: Do not use direct stream of water.

5.2 Special hazards: Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

5.3 Advice for firefighters: Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

6.3 Containment and clean-up:
Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.
Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

6.4 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment.

SECTION 7. HANDLING AND STORAGE

7.1 Handling: Keep away from heat and direct sunlight. Keep away from ignition sources - Do not smoke. Protect against electrostatic discharges. Ensure good ventilation/exhaustion at the workplace.

See Section 8.2 for information on occupational hygiene.

7.2 Storage: Store in a cool, dry place in tightly sealed containers. Observe official regulations on storing packagings with pressurized containers. Store away from oxidizing agents. Store out of direct sunlight. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Store away from oxidizing agents. Rotate stock.

See Section 10 for information on conditions and materials to avoid.

7.3 End Uses: Refer to Section 1 for identified uses, and uses advised against.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Workplace exposure limits: Components

Asphalt

Propane

Solvent naphtha (petroleum), light arom.*

Butane

Exposure limit and source

Long-term value = 5 mg/m³

Short-term value = 10 mg/m³

Not available

Not available

Long-term value = 1810 mg/m³, 750 ppm

Short-term value = 1450 mg/m³, 600 ppm

Acetone	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm
Pentane	Long-term value = 1800 mg/m ³ , 600 ppm
Molybdenum disulfide	Long-term value = 10 mg/m ³ , as Mo
	Short-term value = 20 mg/m ³ , as Mo

8.2 Exposure controls

Engineering controls:	Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective occupational exposure limits.
Ventilation:	Use in a well-ventilated area. See Engineering Controls.
Personal hygiene:	Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.
Eye protection:	Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.
Hand protection:	Any lined non-permeable rubber gloves.
Respiratory protection:	Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical and chemical properties

Appearance / odor:	Thick black liquid with faint ethereal odor	Vapor pressure:	Not available
Physical state:	Liquid and compressed gas in aerosol can	Vapor density:	Not available
Odor threshold:	Not available	Relative density:	0.76-0.80 g/cm ³ (conc.)
pH:	Not available	Solubility in water:	Not available
Melting / freezing point:	Not available	Partition coefficient (n-octanol/water):	Not available
Boiling point / range:	Not available	Autoignition temperature:	Not available
Flash point:	Not available	Decomposition temperature:	Not available
Evaporation rate:	Not available	Viscosity:	Not available
Upper flammability limit:	Not available	Explosive properties:	Not applicable
Lower flammability limit:	Not available	Oxidizing properties:	Not an oxidizer
Percent Volatile:	Not available		

9.2 Other information No further relevant information available.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity:	See sub-sections below.
10.2 Chemical stability:	This material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	Hazardous reactions are not expected to occur.
10.4 Conditions and materials to avoid:	Avoid direct sunlight, heat, sparks, open flames, welding arcs or other high-temperature sources which induce thermal decomposition, strong oxidizers such as liquid chlorine, hydrogen peroxide and oxygen, strong acids such as nitric and sulfuric acids, and alkalis.
10.5 Hazardous decomposition products:	Carbon monoxide, carbon dioxide, smoke and irritating vapors as products of incomplete combustion.

11.1 Information on toxicological effects

Acute toxicity / LD₅₀ and LC₅₀ of ingredients:	Components	LD₅₀	LC₅₀
	Asphalt	Not available	Not available
	Propane	Not available	Not available
	Solvent naphtha (petroleum), light arom.*	>6800 mg/kg (oral, rat)	Not available
	Butane	Not available	658 mg/l/4h (inhalation, rat)
	Acetone	5800 mg/kg (oral, rat)	Not available

	Pentane	Not available	Not available
	Molybdenum disulfide	Not available	Not available
Routes of exposure:	Eyes, skin, ingestion and inhalation		
Other information:	Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis, which can be fatal.		

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity:	<u>Components</u>	<u>L(E)C₅₀</u>
	Asphalt	Not available
	Propane	Not available
	Solvent naphtha (petroleum), light arom.*	Not available
	Butane	Not available
	Acetone	Not available
	Pentane	Not available
	Molybdenum disulfide	Not available
Toxicity notes:	Not available	
12.2 Persistence and degradability:	Not available	
12.3 Bioaccumulative potential:	Not available	
12.4 Mobility in soil:	Not available	
12.5 Persistence, bioaccumulation and toxicity for substance(s):	This product is not, or does not contain, a substance that is a PBT or a vPvB.	
12.6 Other adverse effects:	No adverse effects are expected.	

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:	Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Consult national or regional authorities for proper disposal and reporting procedures.
--------------------------------------	---

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

	<u>Proper Shipping Name:</u>	<u>UN Number:</u>	<u>Hazard Class:</u>	<u>Packing Group:</u>	<u>Remarks:</u>
U.S. D.O.T.	Aerosols, flammable, n.o.s.	UN1950	2.1	None	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Aerosols, flammable, n.o.s.	UN1950	2.1	None	Tunnel Restriction D
IMDG	Aerosols, flammable, n.o.s.	UN1950	2.1	None	None
IATA	Aerosols, flammable, n.o.s.	UN1950	2.1	None	None

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

U.S. Federal Regulations:

SARA Section 302 Extremely Hazardous Substances	This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List: None
--	---

SARA Section 304 CERCLA Hazardous Substances	Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to reporting to the National Response Center under CERCLA: None
---	---

SARA Section 313 Toxic Chemicals	This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations: 1,2,4-Trimethylbenzene (CAS #95-63-6) present at 1-5% max.
---	--

TSCA Inventory	All components of this material are on the U.S. TSCA Inventory.
-----------------------	---

California Proposition 65 Status This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California Proposition 65 Listed Components None

International Regulations:

European Union: This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. A Chemical Safety Assessment has not been carried out.

Canada All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.

Japan MITI Not available

Australia Not available

Switzerland Not available

SECTION 16. OTHER INFORMATION

Sections Revised: New SDS format

Revision Date: 6/1/2015

The information and recommendations contained herein are, to the best of Pressure-Lube Inc.'s knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc.'s interpretation of the available data.

*** END OF SDS ***