

Material Safety Data Sheet

Revision Date: 06-Jan-2014 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name BENJAMIN MOORE REMOVE

Product Code K31500

Product Class SURFACE PREPARATION PRODUCT

Color

Manufacturer Emergency Telephone Number(s)

Benjamin Moore & Co. CANUTEC: 613-996-6666 101 Paragon Drive

Montvale, NJ 07645 Phone: 855-724-6802 www.benjaminmoore.com

2. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Components

nazarada dempenente					
Chemical Name	CAS-No	Weight % (max)			
Sodium hydroxide	1310-73-2	7 - 13%			
Sodium metasilicate	6834-92-0	1 - 5%			
2-Butoxyethanol	111-76-2	0.5 - 1%			

3. HAZARDS IDENTIFICATION

Emergency Overview DANGER

Corrosive. Causes severe eye and skin burns. Harmful if swallowed. May cause irritation of respiratory tract.

Appearance liquid Odor little or no odor

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects

Eyes Corrosive to the eyes and may cause severe damage including blindness.

Skin Causes burns.

Inhalation Irritating to respiratory system. Avoid breathing vapors or mists.

Ingestion Can burn mouth, throat, and stomach.

Chronic Effects Prolonged exposure may cause chronic effects. May cause blood damage.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions None known

HMIS Health: 3 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

General Advice Take off contaminated clothing and shoes immediately. Immediate medical attention

is required. Show this safety data sheet to the doctor in attendance.

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. Immediate medical

attention is required.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes. Consult a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial

respiration.

Ingestion Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting

without medical advice. Never give anything by mouth to an unconscious person.

Consult a physician..

Notes To Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Revision Date: 06-Jan-2014

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 06-Jan-2014

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Upper Explosion LimitNot applicableLower Explosion LimitNot applicable

NFPA Health: 3 Flammability: 0 Instability: 0 Special: COR

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with the skin and the eyes. Use personal protective equipment. Ensure

adequate ventilation.

Environmental Precautions Do not flush into surface water or sanitary sewer system. Prevent product from

entering drains. Should not be released into the environment.

Methods For Clean-UpSoak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists. In case

of insufficient ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Revision Date: 06-Jan-2014

Exposure Limits

Hazardous Components

Chemical Name	ACGIH	Alberta	British Columbia	Ontario	Quebec
Sodium hydroxide	2 mg/m ³ - Ceiling	2 mg/m ³ - Ceiling	2 mg/m ³ - Ceiling	2 mg/m ³ - CEV	2 mg/m ³ - Ceiling
Sodium metasilicate	N/E	N/E	N/E	N/E	N/E
2-Butoxyethanol	20 ppm - TWA	20 ppm - TWA 97 mg/m³ - TWA Substance may be readily absorbed through intact skin		20 ppm - TWAEV Absorption through skin, eyes, or mucous membranes	20 ppm - TWAEV 97 mg/m³ - TWAEV

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Goggles. Face-shield.

Skin Protection Impervious butyl rubber gloves. Impervious clothing.

Respiratory Protection In case of mist, spray or aerosol exposure wear suitable personal respiratory

protection and protective suit.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor
Density (lbs/gal) 9.0 - 9.4
Specific Gravity 1.07- 1.13
pH 14

Viscosity (centistokes)Not availableEvaporation RateNot availableVapor PressureNot availableVapor DensityNot availableWt. % Solids5 - 20

 Wt. % Solids
 5 - 20

 Vol. % Solids
 0 - 15

 Wt. % Volatiles
 80 - 95

 Vol. % Volatiles
 85 - 100

 VOC Regulatory Limit (g/L)
 Not applicable

Boiling Point (°F) 212 Boiling Point (°C) 100

9. PHYSICAL AND CHEMICAL PROPERTIES

Freezing Point (°F) 32
Freezing Point (°C) 0

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Upper Explosion Limit

Lower Explosion Limit

Not applicable

Not applicable

Not available

Not available

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Conditions To Avoid Prevent from freezing

Incompatible Materials Strong oxidizing agents. alkalies. acids. halogens. Ammonia.

amines. reducing sugars. nitromethane.

Revision Date: 06-Jan-2014

Hazardous Decomposition Products

None under normal use.

Possibility Of Hazardous Reactions Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

Revision Date: 06-Jan-2014

Acute Toxicity

Product

No information available

Component

Sodium hydroxide

LD50 Oral: 220 mg/kg (Rat) vendor data LD50 Dermal: 1350 mg/kg (Rabbit)

Sensitization: No sensitizing effects known.

Sodium metasilicate

LD50 Oral: 1153 mg/kg (Rat)

2-Butoxyethanol

LD50 Oral: 470 mg/kg (Rat) LD50 Dermal: 220 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 2.2 mg/L (Rat, 4 hr.) Sensitization: No sensitizing effects known.

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	ACGIH	IARC	NTP	OSHA Carcinogen
	A3 - Confirmed			
2-Butoxyethanol	Animal			
	Carcinogen with			
	Unknown			
	Relevance to			
	Humans			

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish

No information available

12. ECOLOGICAL INFORMATION

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Component

Acute Toxicity to Fish

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options..

Revision Date: 06-Jan-2014

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name

Corrosive liquid, basic, inorganic, n.o.s

Hazard Class

8

UN-No

UN3266

Packing Group

Ш

ICAO / IATA

Contact Benjamin Moore & Co. for further information.

IMDG / IMO

Contact Benjamin Moore & Co. for further information.

15. REGULATORY INFORMATION

International Inventories

United States TSCA

Yes - All components are listed or exempt.

Canada DSL

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

15. REGULATORY INFORMATION

Revision Date: 06-Jan-2014

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical Name CAS-No Weight % (max)

2-Butoxyethanol 111-76-2 0.5 - 1%

This product may contain trace amounts of (other) NPRI Parts I-4 reportable chemicals. Contact the preparer for further information.

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

Chemical Name CAS-No Weight % (max)

2-Butoxyethanol 111-76-2 0.5 - 1%

This product may contain trace amounts of (other) NPRI Part 5 reportable chemicals. Contact the preparer for further information.

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2A Very toxic materials E Corrosive material



16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/hl-vs/iyh-vsv/prod/paint-peinture-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Monvale, NJ 07645 855-724-6802

Revision Date: 06-Jan-2014

Revision Summary No information available

Revision Date: 06-Jan-2014

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of MSDS