



## MATERIAL SAFETY DATA SHEET

MSDS-5-030

7700 SETZLER PARKWAY  
MINNEAPOLIS, MN  
55445  
TOLL FREE PHONE: 1.800.328.7720

**Emergency Phone:** CHEMTREC 1.800.424.9300, INTERNATIONAL (202)483.7616

### SECTION I - PRODUCT IDENTIFICATION.

Product Name: **KELTACK**  
Product Use: **SUNDRY EMBALMING**  
Chemical Family: **N/A**  
Whmis Classification: **NOT REGULATED**  
TDG Hazard Class: **NOT REGULATED**

### SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>Cas#</u>	<u>wt. %</u>	<u>LC50</u> (Rat.lhl)	<u>LD50</u> (Rat.oral)	<u>LD50</u> (rbt.skin)
Paraffin Oil	8012-95-1	80	n/a	n/a	n/a

### SECTION III - PHYSICAL DATA

Boiling Point:	n/a	Specific Gravity (H2O=1):	n/a
Vapour Pressure (mm hg):	n/a	Volatile %:	n/a
Vapour Density (air=1):	n/a	Evaporation Rate (BuAe=1):	n/a
Solubility in water:	n/a	Ph:	n/a
Coeff. water/oil dist:	n/a	Freezing Point:	49 C
Appearance & odour:	purple, soft sticky wax, mild odour	Odour Threshold:	n/a

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability: **YES** Combustible solid  
Flash Point: 193C  
Upper Explosion Limit: n/a  
Lower Explosion Limit: n/a  
Auto Ignition Temp: 245C  
Hazardous Combustion Products: none  
Explosion Data: none  
Rate of Burning: n/a  
Explosive Power: none  
Sensitivity to Static Discharge: n/a  
Means of Extinction: Carbon dioxide, dry chemical, water spray.  
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and complete personal protective equipment.

### SECTION V - REACTIVITY DATA

Stability: stable  
Incompatibility: Strong oxidizing agents.  
Hazardous Polymerization: Will not occur  
Conditions to Avoid: Keep away from heat, sparks and flames  
Hazardous Decomposition: Carbon dioxide

## SECTION VI - TOXICOLOGICAL PROPERTIES

### **\*\*\*OCCUPATIONAL EXPOSURE LIMITS\*\*\***

**Exposure Limit:** Paraffin Oil (TLV-C) n/a (TLV-STEL) 10 mg/m<sup>3</sup>  
(TLV-TWA) 5 mg/m<sup>3</sup>

**Inhalation:** May cause irritation or injury.

**Eye Contact:** Causes irritation.

**Skin:** May cause irritation.

**Ingestion:** n/a.

## SECTION VII - FIRST AID

**Inhalation:** Move victim to fresh air, contact physician.

**Eye Contact:** Flush eyes with lukewarm water. If irritation persists, obtain medical attention immediately.

**Skin Contact:** Wash contaminated skin. If irritation persists contact physician.

**Ingestion:** Do not induce vomiting. Have victim drink large amounts of water. Contact physician immediately.

## SECTION VIII - PREVENTIVE MEASURES

**Spill and Leak Procedures:** Use absorbent material and place in closed pail.

**Waste Disposal:** None.

### **\*\*Personal Protective Equipment\*\***

**Respiratory protection:** None required.

**Protective Gloves:** Neoprene or latex recommended.

**Eye Protection:** Chemical safety goggles should be worn to prevent eye contact.

**Other Protective equipment:** None.

**Ventilation:** Local exhaust.

### **\*\*Storage and Handling\*\***

**Handling:** Do not store below 5C or above 49C.

**Storage:** The hazard potential of this material is relatively low. General ventilation is usually sufficient.

## SECTION IX - ADDITIONAL INFORMATION

<b>Abbreviations:</b>	TLV:	Threshold Limit Values	STEL:	Short-term Exp. Level
	TWA:	8 hr Time-Weighted Average		
	ACGIH:	American Conference of Governmental Industrial Hygienists 1993-94		
	OSHA:	Occupational Safety and Health Administration		
	N/A:	Not Available		

## SECTION X - PREPARATION INFORMATION

**Prepared by:** H.S. Eckels and Company (Canada) Ltd.

**Telephone:** 519-824-8020

**Preparation Date:** May 9