

SAFETY DATA SHEET

Kleen Lube

Section 1. Identification

GHS product identifier

Kleen Lube

Other means of identification

: Not available.

Product type

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Dental product:

Area of application : Professional applications.

Manufacturer : Kerr Corporation

1717 West Collins Avenue Orange, CA 92867-5422

Telephone no.: 1-800-KERR-123

e-mail address of person responsible for this SDS

: edwin.varela@kavokerrgroup.com

Emergency telephone number (with hours of

operation)

: CHEMTREC® (24 hours) U.S.: 1-800-424-9300 International: +1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Health effects are based on the uncured material.

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

TOXIC TO REPRODUCTION (Fertility) - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (nervous system

and peripheral nervous system) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 4.7%

GHS label elements

Hazard pictograms







Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 1/14

Section 2. Hazards identification

Signal word

: Warning

Hazard statements

: Flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

Suspected of damaging fertility.
May cause respiratory irritation.
May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure. (nervous

system, peripheral nervous system)

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response

Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Hazards not otherwise

classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture
Other means of identification

: Not available.

: Mixture

CAS number/other identifiers

CAS number : Not applicable.

Product code : Not available.

Ingredient name	Other names	%	CAS number
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	60-100	64742-49-0
n-hexane Stoddard solvent		10-30 1-5	110-54-3 8052-41-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 2/14

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: No special measures are required. In case of contact with eyes, rinse immediately with

plenty of water. Get medical attention if symptoms occur.

Inhalation : No special measures required. If inhaled, remove to fresh air. Get medical attention if

symptoms occur.

Skin contact: No special measures required. In case of contact, immediately flush skin with plenty of

water. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Get medical attention if adverse health effects persist or

are severe.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact: Causes skin irritation. Defatting to the skin.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision: 06/02/2015Date of previous issue: No previous validationVersion: 13/14

Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: In case of major fire and large quantities: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds

metal oxide/oxides

Special protective actions for fire-fighters

: In case of major fire and large quantities: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue/Date of revision 4/14 : 06/02/2015 Date of previous issue : No previous validation Version: 1

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Low release. For professional use only. Handling of product in very small amounts or in situations where release is highly unlikely

For emergency responders: Low release. See also the information in "For non-emergency personnel".

Environmental precautions

: Low release. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: No special measures are required for small quantities under normal and intended conditions of product use. For professional use only. Put on appropriate personal protective equipment (see Section 8). Handle with care and dispose in a safe manner.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
n-hexane			OSHA PEL 1989 (United States, 3/1989). TWA: 50 ppm 8 hours. TWA: 180 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 50 ppm 10 hours. TWA: 180 mg/m³ 10 hours. ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 50 ppm 8 hours.
ate of issue/Date of revision	: 06/02/2015 D	Date of previous issue	: No previous validation Version : 1 5/1

United States

Stoddard solvent

Section 8. Exposure controls/personal protection

OSHA PEL (United States, 2/2013). TWA: 500 ppm 8 hours.

TWA: 300 ppin 6 flours.
TWA: 1800 mg/m³ 8 hours.

ACGIH TLV (United States, 4/2014).

TWA: 100 ppm 8 hours. TWA: 525 mg/m³ 8 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 100 ppm 8 hours. TWA: 525 mg/m³ 8 hours.

NIOSH REL (United States, 10/2013).

TWA: 350 mg/m³ 10 hours. CEIL: 1800 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013).

TWA: 500 ppm 8 hours. TWA: 2900 mg/m³ 8 hours.

Appropriate engineering controls

Environmental exposure controls

: No special measures are required for small quantities under normal and intended conditions of product use.

: No special measures are required for small quantities under normal and intended conditions of product use.

Individual protection measures

Hygiene measures

: No special measures are required for small quantities under normal and intended conditions of product use.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version :1 6/14

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Clear.

Odor : Solvent.

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

 Boiling point
 : 160 to 176.11°C (320 to 349°F)

 Flash point
 : Closed cup: 43.889°C (111°F)

Evaporation rate : Not available.

Flammability (solid, gas) : Not applicable.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : 0.27 kPa (2 mm Hg) [room temperature]

Vapor density : 4.3 [Air = 1]

Relative density : 0.88

Solubility : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 7/14

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-hexane	LC50 Inhalation Vapor	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-hexane	Eyes - Mild irritant	Rabbit	-	10 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrotreated light n-hexane	Category 3 Category 3	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation and Narcotic effects
Stoddard solvent	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
n-hexane	Category 2		nervous system and peripheral nervous system

Aspiration hazard

Name	Result
n-hexane n-hexane	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Date of issue/Date of revision: 06/02/2015Date of previous issue: No previous validationVersion: 1

Section 11. Toxicological information

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact: Causes skin irritation. Defatting to the skin.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness dryness cracking

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity: No known significant effects or critical hazards.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 9/14

Kleen Lube

Section 11. Toxicological information

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
n-hexane	Acute LC50 2500 μg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Naphtha (petroleum), hydrotreated light	2.2 to 5.2	10 to 2500	high
n-hexane Stoddard solvent	4 3.16 to 7.06	501.187 -	high high

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 10/14

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN3295	UN3295	UN3295
UN proper shipping name	Hydrocarbons, liquid, n.o.s Marine pollutant (Naphtha (petroleum), hydrotreated light, n- hexane) RQ (n-hexane)	HYDROCARBONS, LIQUID, N. O.S Marine pollutant (Naphtha (petroleum), hydrotreated light, nhexane)	Hydrocarbons, liquid, n.o.s.
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	No.
Additional information	This product may be reclassified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids, that are marine pollutants, are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by vessel. This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173. 24a. Reportable quantity 20000 lbs / 9080 kg [2725.8 gal / 10318.2 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Limited quantity Yes.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-E, S-D Special provisions 223	The environmentally hazardous substance mark may appear if required by other transportation regulations. Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 355 Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 366 Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y344 Special provisions A3, A324

Date of issue/Date of revision: 06/02/2015Date of previous issue: No previous validationVersion: 1

Kleen Lube

Section 14. Transport information

Packaging instruction Passenger aircraft Quantity limitation: 60 L

Cargo aircraft

Quantity limitation: 220 L

Special provisions

144, B1, IB3, T4, TP1, TP29

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL

: Not available.

73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations : United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard

> Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Naphtha (petroleum), hydrotreated light n-hexane Stoddard solvent	60-100	Yes.	No.	No.	Yes.	No.
	10-30	Yes.	No.	No.	Yes.	Yes.
	1-5	Yes.	No.	No.	Yes.	No.

Date of issue/Date of revision : 06/02/2015 Date of previous issue Version: 1 12/14 : No previous validation

Kleen Lube

Section 15. Regulatory information

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	n-hexane	110-54-3	10-30
Supplier notification	n-hexane	110-54-3	10-30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: HEXANE; STODDARD SOLVENT

New York : The following components are listed: Hexane

New Jersey : The following components are listed: n-HEXANE; HEXANE; STODDARD SOLVENT

Pennsylvania: The following components are listed: HEXANE; STODDARD SOLVENT

California Prop. 65

None of the components are listed.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

: 06/02/2015

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 13/14

Section 16. Other information

Date of issue/Date of

revision

Date of previous issue : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of revision : 06/02/2015 Date of previous issue : No previous validation Version : 1 14/14