



MATERIAL SAFETY DATA SHEET

REVISION DATE: 01/29/2009 REVISION NUMBER: 6
DATE PRINTED: 01/29/2009 PREPARED BY: EH&S DEPARTMENT

1. CHEMICAL PRODUCT

PRODUCT NAME: LA 175P, Heavy Duty Alkaline Cleaner
PRODUCT CODE: 117420

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 2/2 **Fire:** 0/0
Reactivity: 0/0 **Special/Protective Equipment:** ALK/B

NAME OF THE MANUFACTURER: Rochester Midland Corporation
333 Hollenbeck Street
Rochester, New York 14621
Information: 585-336-2200
Emergency Phone:
INFOTRAC: 1-800-535-5053
OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Causes vomiting, nausea, and diarrhea. May cause burns to mucous membranes of mouth, throat, and digestive tract.
SKIN CONTACT: Prolonged contact causes severe burns which may not be immediately painful or visible. Glycol ether component can be absorbed through the skin.
INHALATION: Inhalation of spray mists irritating to nose and throat; possible nausea, dizziness.
EYE CONTACT: May Cause Eye Burns. Possible tissue damage.
CHRONIC EFFECTS: Long term overexposure to some glycol ethers by skin absorption or inhalation may cause kidney, liver, or blood effects based on animal testing.
EFFECTS/CARCINOGENICITY: None listed under OSHA, IARC, or NTP.
ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
Potassium phosphate 7778-53-2	3 max.	NA	NA
Diethylene glycol butyl ether 112-34-5	8 max.	NA	NA

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING. Drink several glasses of water or milk. Get immediate medical attention. Never give anything by mouth to an unconscious person.
SKIN: Flush with water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention if irritation persists.
INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
EYES: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.
NOTES TO PHYSICIAN: None.

LA 175P, Heavy Duty Alkaline Cleaner

5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): None (C): NA
METHOD: TCC

FLAMMABLE LIMITS IN AIR

- LOWER (%): None
- UPPER (%): None

SENSITIVITY TO MECHANICAL IMPACT(Y/N):

NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

SUITABLE EXTINGUISHING MEDIA:

As appropriate for surrounding fire-product is mostly water and will not burn.

FIRE FIGHTING PROCEDURES:

Corrosive material. Avoid exposure to mist and splashes. Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires. Cool exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

SMALL SPILLS:

Mop up all possible. Rinse down drain.

LARGE SPILLS:

Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Flush remainder with water. Releases of some glycol ethers may be CERCLA reportable.

PERSONAL PRECAUTIONS:

NA

ENVIRONMENTAL PRECAUTIONS:

NA

METHODS FOR CLEANING UP:

NA

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN
IN HANDLING AND STORAGE:

Caution: Alkaline liquid. Avoid contact with eyes, skin and clothing. Do not breathe mist or vapors. Store only in original container and keep closed. Store in a cool, dry area. Store in a well ventilated area. Keep from freezing.

OTHER PRECAUTIONS:

Do not reuse container. Empty containers may retain product residue, follow MSDS/label precautions even after container is emptied. Contact with certain food sugars can release hazardous amounts of carbon monoxide gas in enclosed vessels. Read and follow label instructions.

SPECIFIC USE(S):

NA

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



EXPOSURE CONTROLS:
RESPIRATORY PROTECTION:

Use in a well ventilated area.

None normally required. Use NIOSH approved alkaline respirator with dust/mist filter as needed to meet exposure limits if product is used in a manner which creates dust or mist above recommended exposure limits.

PROTECTIVE GLOVES:

Rubber or plastic gloves recommended to minimize skin contact.

EYE PROTECTION:

Safety Glasses. Goggles.

OTHER PERSONAL PROTECTION

Eyewash fountains and safety showers must be easily accessible. Appropriate protective clothing as needed to prevent skin contact.

EQUIPMENT:

VENTILATION:

General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

9. PHYSICAL AND CHEMICAL PROPERTIES

LA 175P, Heavy Duty Alkaline Cleaner

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Light yellow liquid. Mild odor.
BOILING POINT (F): 212° F (C) NA
VAPOR PRESSURE: 15.7 mm Hg @ 22.2° C
VAPOR DENSITY (AIR=1): 0.625
SOLUBILITY IN WATER: NA
SPECIFIC GRAVITY: 1.040 - 1.046
VOC Content (%): 0 (ARB 310 Method)
VOV Content (%): NE
EVAPORATION RATE: (BuAc = 1) : 1.26
PH: 12.0 - 12.4

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE
POLYMERIZATION: Will Not Occur.
HAZARDOUS DECOMPOSITION: If evaporated to dryness, as in a fire, may release: Soot. Smoke. Carbon Monoxide. Traces of:
Sulfur compounds.
INCOMPATIBILITY (MATERIALS TO AVOID): Do not mix with acidic materials. Neutralizes active ingredients and may release acid fumes.
CONDITIONS/HAZARDS TO AVOID: None.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: NE
EFFECTS OF CHRONIC EXPOSURE: NE
OTHER TOXIC EFFECTS: NE

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time.
MOBILITY: NA
PERSISTENCE/DEGRADABILITY: NA
BIOACCUMULATIVE POTENTIAL: NA
OTHER ADVERSE EFFECTS: NA

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
Potassium phosphate 7778-53-2	3 max.	Listed	Listed	Listed	Not Listed
Diethylene glycol butyl ether 112-34-5	8 max.	Listed	Listed	Listed	Not Listed

LA 175P, Heavy Duty Alkaline Cleaner

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
Potassium phosphate 7778-53-2	3 max.	Not Listed	Not Listed	Not Listed
Diethylene glycol butyl ether 112-34-5	8 max.	Not Listed	Not Listed	Listed

PRODUCT COMPOSITION CAS#	%	Canada WHMIS:
Potassium phosphate 7778-53-2	3 max.	Listed
Diethylene glycol butyl ether 112-34-5	8 max.	Listed

None of the components of this material are included in the Massachusetts Substance List nor are present at or above reportable levels.

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	NJRTK:
Diethylene glycol butyl ether 112-34-5	8 max.	Listed

The following components of this material are included in the Pennsylvania Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	PARTK:
Diethylene glycol butyl ether 112-34-5	8 max.	Listed

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***