

Safety Data Sheet: LUBEMASTER SYSTEM PURGE(7GAL)

Supersedes Date 04/19/2011

Issuing Date 10/16/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name LUBEMASTER SYSTEM PURGE(7GAL)

Recommended use Lubricant assistant

Information on Manufacturer

CERTIFIED LABS, DIV. OF NCH CORP.

BOX 152170

IRVING, TEXAS 75015

Product Code 256J

Chemical nature Petroleum distillates

Emergency Telephone Number

CHEMTREC® 800-424-9300

Telephone inquiry

972-579-2477

2. HAZARD IDENTIFICATION

Color Brown

Physical State Liquid

Odor Mild Petroleum-like

GHS

Classification

Physical Hazards

None

Health Hazard

Serious Eye Damage/Eye Irritation

Category 2B

Other hazards

None

Labeling

Signal Word

WARNING

Hazard Statements

H320 - Causes eye irritation

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists, get medical attention.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
White mineral oil, solvent refined	8042-47-5	60-100
Calcium sulfonate	61789-86-4	10-30

4. FIRST AID MEASURES

General advice

Avoid contact with skin, eyes and clothing. Avoid breathing mist.

Eye Contact

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.

Skin Contact

Wipe up with absorbent material (e.g. cloth, fleece). Wash off with soap and plenty of water. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.

Notes to physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point 400 °F / 204 °C

Method Open cup

Flammability Limits in Air % Not applicable.

Upper No data available **Lower** No data available

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Foam. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA
HMIS

Health 1
Health 1

Flammability 1
Flammability 1

Instability 0
Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust)
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing mist.			
Storage	Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.			
Storage Temperature	Minimum	0 °F / -18 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	
			Heated	Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
White mineral oil, solvent refined	5 mg/m ³	5 mg/m ³	IDLH 2500 mg/m ³ STEL 10 mg/m ³
Calcium sulfonate	No data available	No data available	No data available

Engineering Measures	Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	For prolonged or repeated contact, use protective gloves with appropriate chemical resistance.
Respiratory Protection	In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
General Hygiene Considerations	Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Slight Viscous
Color	Brown	Odor	Mild Petroleum-like
Odor Threshold	Not applicable	Appearance	Transparent
pH	Not applicable	Specific Gravity	0.88
Evaporation Rate	0 (Butyl acetate=1)	Percent Volatile (Volume)	0
VOC Content (%)	0	VOC Content (g/L)	0
Vapor Pressure	0.01 mmHg @ 70°F	Vapor Density	8.8 (Air = 1.0)
Solubility	Negligible	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition Temperature	No data available
Boiling Point/Range	> 575 °F / 302 °C	Flammability (solid, gas)	No data available
Flash Point	400 °F / 204 °C	Method	Open cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %	Not applicable.	Upper	No data available
		Lower	No data available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	None known
Incompatible Products	Strong oxidizing agents
Hazardous Decomposition Products	Carbon oxides, Sulfur oxides, Aldehydes.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50	No information available
Dermal LD50	No information available
Inhalation LC50	
Gas	No information available
Mist	No information available
Vapor	No information available

Principle Route of Exposure Eye contact, Inhalation, Skin contact.

Primary Routes of Entry None known

Acute Effects

Eyes May cause eye irritation.

Skin May cause skin irritation.

Inhalation May cause irritation of respiratory tract. (Mist).

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity Prolonged or repeated inhalation may cause damage to the lungs. Prolonged skin contact may defat the skin and produce dermatitis.

Target Organ Effects Respiratory system

Aggravated Medical Conditions Skin disorders, Respiratory disorders.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
White mineral oil, solvent refined	> 5000 mg/kg (Rat)	no data available	no data available	no data available	no data available
Calcium sulfonate	> 5000 mg/kg (Rat)	> 4000 mg/kg (Rabbit)	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
White mineral oil, solvent refined	no data available	no data available	no data available	no data available	respiratory system
Calcium sulfonate	no data available	no data available	no data available	no data available	no data available

Carcinogenicity

There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
White mineral oil, solvent refined	not applicable	not applicable	not applicable	not applicable	not applicable
Calcium sulfonate	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
White mineral oil, solvent refined	no data available	LC50 > 10000 mg/L Lepomis macrochirus 96 h	no data available	no data available	>6
Calcium sulfonate	no data available	LC50 5.7 - 9.7 mg/L Pimephales promelas 96 h LC50 1.0 - 10.0 mg/L Pimephales promelas 96 h	no data available	EC50 6.2 - 12 mg/L 48 h	N/A

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Dispose of in accordance with local regulations.

Container Disposal

Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

Inventories

TSCA Complies

DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	No	No	No	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
White mineral oil, solvent refined	Not applicable	Not applicable
Calcium sulfonate	Not applicable	Not applicable

16. OTHER INFORMATION

Prepared By Sarah Williamson
Supersedes Date 04/19/2011
Issuing Date 10/16/2013
Reason for Revision No information available.
Glossary No information available.
List of References. No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.