

SAFETY DATA SHEET LEMON SPIRIT

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: LEMON SPIRIT

PART No.: RM323

SUPPLIER: J M Loveridge plc

Southbrook Road, Southampton

Hampshire SO15 1BH

Tel: 023 8022 2008 Fax: 023 8022 2117

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME

CAS No.: EINECS Nr.: CLASSIFICATION

ETHANOL 60-100 %

64-17-5 200-578-6 F R-11

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Highly flammable.

4. FIRST AID MEASURES:

GENERAL: IN ALL CASES OF DOUBT OR WHEN SYMPTOMS PERSIST, ALWAYS SEEK

MEDICAL ATTENTION

INHALATION: Move affected person to fresh air. If recovery not rapid, seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. In case of spontaneous vomiting, be sure that vomit

can freely drain because of danger of suffocation. Only when conscious, rinse mouth with plenty of water and give plenty of water to drink - (approx 500ml). Keep patient at

rest and obtain medical attention.

SKIN: Remove contaminated clothing. Wash affected area with plenty of soap and water. If

irritation persists, seek medical attention.

EYES: Rinse immediately with copious amounts of water. If irritation or discomfort persists,

seek medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.

Halon.

SPECIAL FIRE FIGHTING

PROCEDURES:

Use gentle application of water spray to keep exposed containers cool or to dissipate

vapour.

UNUSUAL FIRE & EXPLOSION

HAZARDS:

May explode when heated or when exposed to flames or sparks. Vapour may travel

considerable distance to source of ignition and flash back.

HAZARDOUS COMBUSTION

PRODUCTS:

Burning will produce oxides of carbon.

PROTECTIVE MEASURES IN FIRE: Fire fighters should wear self-contained breathing apparatus.

6. A CCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTION IN SPILL: Wear appropriate protective clothing. Eliminate all sources of ignition.

PRECAUTIONS TO PROTECT

ENVIRONMENT:

Prevent contamination of soil, drains and surface water.

SPILL CLEAN UP METHODS: Take-up spillage with absorbent, inert material and place in a suitable and closable

labelled container for recovery or disposal. Wash the area clean with water and

detergent, observing environmental requirements.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: HANDLING - Product should be used in accordance with good industrial principles for

handling and storing of hazardous chemicals.

Spillages will create a fire hazard. Avoid vapour formation and ignition sources. Avoid inhalation of vapours. Ensure good ventilation and local exhaust extraction in work place. (engineering controls must be to explosion/flameproof standard). Earth container and transfer equipment to eliminate accumulation of static charge.

STO RAGE PRECAUTIONS: Store in a cool, dry, well ventilated place, in securely closed original container.

Flammable/combustible - Keep away from oxidising agents, heat and flames.

STO RAGE CRITERIA: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME: CAS No.: STD LT EXP 8 Hrs ST EXP 15 Min

ETHANOL 64-17-5 OES 1000 ppm No std.

VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS: Respiratory protection required in insufficiently ventilated working areas.

PROTECTIVE GLOVES:

Use impervious gloves made of butyl rubber or PVC.

Approved chemical safety goggles or face protection.

EYE PROTECTION: Approved chemical safety goggles or face protection.

OTHER PROTECTION:

Use engineering controls to reduce air contamination to permissible exposure level.

Wear personal protective equipment appropriate to the quantity of material handled.

HY GIENIC WORK PRACTICES: SKIN PROTECTION - apply barrier cream to hands and exposed skin.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Clear colourless to pale yellow mobile liquid.

ODOUR/TASTE: Faint odour of lemon.

BOILING POINT (°C, interval): ~ 78 Pressure:

DENSITY/SPECIFIC GRAVITY (g/ml): ~ 0.81 - 0.82 Temperature (°C): 20

VAPOUR DENSITY (air=1): Ethanol: 1.59

VAPOUR PRESSURE: Ethanol: 5.81 kPa Temperature (°C): 20

EVAPORATION RATE: Ethanol: 3.4 Reference: BuAc=1

SOLUBILITY DESCRIPTION: Miscible with water.

FLASH POINT (°C): ~ 15 Method: CC (Closed cup).

AUTO IGNITION TEMP. (°C): Ethanol: ~ 365°C

FLAMMABILITY LIMIT - Ethanol vapour: 3.3

LOWER(%):

FLAMMABILITY LIMIT - UPPER (%): Ethanol vapour: 19

10. STABILITY AND REACTIVITY:

STABILITY: Stable under normal conditions of use.

CONDITIONS TO A VOID: Avoid heat, flames and other sources of ignition. Avoid accumulation of static

electricity.

MATERIALS TO AVOID: Oxidising agents. Sulphuric acid, Nitric acid.

HAZARDOUS DECOMP. PRODUCTS: Thermal decomposition or burning will release oxides of carbon.

11. TOXICOLOGICAL INFORMATION:

TOXIC DOSE - LD 50: Ethanol: 7060 mg/kg (oral rat)

HEALTH HAZARDS, GENERAL: Intoxicating if inhaled or ingested.

INHALATION: May cause transient irritation to the respiratory system. Exposure to high vapour

concentration may cause central nervous system depression or systemic effects similar

to those of ingestion.

INGESTION: May cause nausea, vomiting, dizziness and depression of CNS.

Aspiration during swallowing or vomiting may severely damage the lungs.

SKIN: Repeated or prolonged contact may cause mild irritation and/or drying (defatting) of

skin.

EYES: May cause transient eye irritation or damage.

OTHER HEALTH EFFECTS: For ethanol component of the preparation, adverse effects on male reproductive system

have been reported in laboratory animals on prolonged exposure. Inconsistent

mutagenic activity has also been reported.

ROUTE OF ENTRY: Inhalation.

12. ECOLOGICAL INFORMATION:

Ecotoxicological data LC50 24 hours fish (trout) 11400 mg/l (applicable to ethanol component)

MOBILITY: Water soluble, will partition to aqueous phase. Lost within short period through

evaporation and dissolution. Poorly absorbed onto soils or sediments.

BIO ACCUMULATION: Low bioaccumulation potential.

DEGRAD ABILITY: Readily biodegradable. Ethanol component - BOD5 = 37.74% of ThOD; BOD20 =

75-84% of ThOD.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: This material and/or its container must be disposed of as hazardous waste according to

Special Waste Regulations 1996 or according to local regulations, in compliance with

Duty of Care Regulations and Special Waste Regulations.

WASTE CLASS: WASTE CODE:0705** HAZARDOUS PROPERTY: H3-A

14. TRANSPORT INFORMATION:

ADR CLASS No.:

ADR CLASS: Class 3: Flammable liquids.

ADR ITEM No.: 3°(b)

HAZARD No. (ADR): 33 Highly flammable liquid (flash-point below 23°C).

ADR MARGINAL: 2301

ADR LABEL No.: 3

HAZCHEM CODE: 3YE

PROPER SHIPPING NAME I: FLAMMABLE LIQUID, NOS

PROPER SHIPPING NAME II: Technical name - (contains ethanol)

No.

ROAD TRANSPORT NOTES: Flash point: 15°C

UN No. SEA: UN 1993

IM DG CLASS: 3.2
IM DG PAGE No.: 3230

IM DG PACK GR::

MARINE POLLUTANT:

UN No., AIR: UN-ID 1993

ICAO CLASS:

AIR PACK GR .:

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES: R-11 Highly flammable.

SAFETY PHRASES: S-16 Keep away from sources of ignition - No Smoking.

> S-51 Use only in well ventilated areas. S-9 Keep container in a well ventilated place.

UK REGULATORY REFERENCES: Classification, Packaging and Labelling Regulations 1984. Chemicals (Hazard

Information & Packaging) Regulations 1993.

16. OTHER INFORMATION:

INFORMATION SOURCES: This product has been classified in accordance with CHIP3 regulations.

REVISION COMMENTS: Edition 01; Revised item(s):

565

ISSUED BY: MK SDS No .:

DATE: 12/07/02

DISCLAIMER: The foregoing data has been compiled for safety information only and does not form

part of any selling specification. Information contained in this Data Sheet is to the best of JMLs knowledge correct at the time of publication. Customers should always satisfy themselves, that the product which they have selected is entirely suitable for their purpose under their conditions of use and in compliance with current regulations. For

any further information, please contact the supplier.

R-PHRASES (Full Text): R-11 Highly flammable.