



Revision Number: 001.2

Issue date: 04/01/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LePage® Carpenter's Glue
Product use: Adhesive
Company address:
Henkel Canada Corporation
2515 Meadowpine Boulevard
Mississauga, Ontario L5N 6C3

IDH number: 530539
Region: Canada
Contact information:
Telephone: 905.814.6511
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Physical state: Liquid
Color: Opaque, Yellow
Odor: Characteristic

WHMIS hazard class: D.2.A, D.2.B

CAUTION: MAY CAUSE SLIGHT EYE, SKIN OR RESPIRATORY TRACT IRRITATION ON REPEATED CONTACT.
MAY CAUSE GASTROINTESTINAL IRRITATION IF SWALLOWED.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause slight irritation.
Skin contact: May cause mild skin irritation.
Eye contact: May cause mild irritation
Ingestion: May cause gastrointestinal tract irritation if swallowed. Not expected under normal conditions of use.

Existing conditions aggravated by exposure: None known

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Boric acid	10043-35-3	0.1 - 1

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. Get immediate medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. Remove contaminated clothing and footwear. Get immediate medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.

Ingestion:

DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash point:	Not applicable
Autoignition temperature:	Not determined
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Extinguishing media:	Use media appropriate for surrounding material.
Special firefighting procedures:	Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
Unusual fire or explosion hazards:	None identified.
Hazardous combustion products:	Smoke. Oxides of carbon.
Sensitivity to Mechanical Impact:	None
Sensitivity to static discharge:	None

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Do not allow product to enter sewer or waterways.
Clean-up methods:	Keep unnecessary personnel away. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Dispose of contaminated material as waste according to Section 13.

7. HANDLING AND STORAGE

Handling:	Avoid breathing vapors or mists of this product. Use only in well-ventilated areas. Wash thoroughly after handling.
Storage:	Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Boric acid	6 mg/m ³ STEL Inhalable fraction. 2 mg/m ³ TWA Inhalable fraction.	None	None	None

Engineering controls:	Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).
Eyeface protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Opaque, Yellow
Odor:	Characteristic
Odor threshold:	Not available.
pH:	4 - 5
Vapor pressure:	101.3 kPa
Boiling point/range:	100 °C (212°F)
Melting point/ range:	Not determined
Specific gravity:	1.08
Vapor density:	Not determined
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Evaporation rate:	0.36 (Butyl acetate = 1)
Solubility in water:	Dispersible
Partition coefficient (n-octanol/water):	Not determined
VOC content:	< 0.45 % (by weight)

10. STABILITY AND REACTIVITY

Stability:	Normally stable.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Smoke. Oxides of carbon.
Incompatible materials:	This product may react with strong acids, bases and oxidizing agents.
Conditions to avoid:	Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Toxicologically synergistic products:	Not available.
--	----------------

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	ACGIH Carcinogen
Boric acid	No	No	No	Group A4

Hazardous components	LD50s and LC50s	Health Effects/Target Organs
Boric acid	Oral LD50 (RAT) = 2,660 mg/kg Dermal LD50 (RABBIT) = > 2,000 mg/kg Inhalation LC50 (RAT, 4 h) = > 0.002 mg/l	Behavioral, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Liver, Reproductive, Skin, Less weight gain and food intake.

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product.

14. TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR), and the MSDS contains all the information required by the CPR.

Prepared by: Jennifer Altman, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.