SECTION 1. IDENTIFICATION

Product identifier used on the label

: Liquid Muscle Top Lube

Product Code(s) : FP-SL173

Recommended use of the chemical and restrictions on use

: Fuel additive. No restrictions on use known.

Chemical family : Mixture.

Name, address, and telephone number of Name, address, and telephone number of

the manufacturer: the supplier:

FPPF Chemical Company, Inc. Refer to manufacturer

117 West Tupper Street Buffalo, NY, USA

14201

Manufacturer's Telephone # : 1-800-735-3773

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Light amber liquid. Hydrocarbon odour.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Skin Corrosion/Irritation - Category 2
Aspiration Toxicity - Category 1
Carcinogenicity - Category 2

Specific Target Organ Toxicity, Single Exposure - Category 3 (cns)

Label elements

Hazard pictogram(s)





Signal Word

DANGER!

Hazard statement(s)

Causes skin irritation.

May be fatal if swallowed and enters airways.

May cause drowsiness and dizziness.

Suspected of causing cancer.

Precautionary statement(s)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors or mists. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash hands and face thoroughly after handling.

IF exposed or concerned: Get medical attention/advice.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation occurs, get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. May be mildly irritating to skin, eyes and respiratory system. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

emical name	Common name and synonyms	CAS#	Concentration 0.1 - 0.9	
Naphthalene	Moth balls Moth flakes Tar camphor	91-20-3		
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	0.1 - 0.3	
Heavy aromatic solvent naphtha	Aromatic solvent naphtha Heavy Aromatic Naphtha	64742-94-5	4.0 - 6.0	
oleic acid	Oleinic acid; 9-Octadecenoic acid; Elaic acid	112-80-1	4.0 - 6.0	
Distillates, petroleum, hydrotreated light	Hydrotreated kerosene; Distillate Fuel Oils Light	64742-47-8	*1.0 - 90.0	
Solvent naphtha (petroleum), medium aliphatic	Medium aliphatic solvent naphtha; White Spirit	64742-88-7	*1.0 - 90.0	

The exact concentrations of the above listed chemicals are being withheld as a trade secret. Note: The * means this product could contain one or both CAS numbers within the concentration range listed with the possibility of a blend of both.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Skin contact

Ingestion

: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Aspiration hazard Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTRE or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical

personnel only.

; IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation occurs, get medical advice/attention.

Eye contact : Flush eyes with water for at least 20 minutes. Remove contact lenses if present and

easy to do. Continue rinsing.

Most important symptoms and effects, both acute and delayed

IF exposed or concerned: Get medical attention/advice.
 Causes skin irritation. Symptoms may include redness, itching and swelling.
 May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.
 Symptoms include coughing, shortness of breath and wheezing.
 May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
 Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.
 Direct eye contact may cause slight or mild, transient irritation.
 If product is heated or mists are formed, inhalation may cause irritation to the nose,

throat and respiratory tract.

Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Indication of any immediate medical attention and special treatment needed

: Immediate medical attention is required. Provide general supportive measures and treat symptomatically. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

 Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Not flammable.

Hazardous combustion products

Carbon oxides.Reactive hydrocarbons. Aldehydes Unidentified organic compounds. . Other irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

: Ventilate the area. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labelled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

SDS Preparation Date (mm/dd/yyyy): 06/02/2015

SAFETY DATA SHEET

Special spill response procedures

In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): Naphthalene (100 lbs / 45.4 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Avoid breathing mist or vapours. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

Conditions for safe storage

Store in a well ventilated place. Keep container tightly closed. Store locked up. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials

Strong oxidizing agents. Reactive metals.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:					
Chemical Name	ACGIH 1	TLV	OSHA PEL		
	<u>TWA</u>	STEL	<u>PEL</u>	STEL	
Naphthalene	10 ppm (skin)	N/Av	10 ppm ; 50 mg/m³	15ppm; 75mg/m ³	
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av	
Heavy aromatic solvent naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av	
oleic acid	N/Av	N/Av	N/Av	N/Av	
Distillates, petroleum, hydrotreated light	200 mg/m³ (jet fuel/kerosene - as total hydrocarbonvapour)	N/Av	N/Av	N/Av	
Solvent naphtha (petroleum), medium aliphatic	N/Av	N/Av	N/Av	N/Av	

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection : Wear eye/face protection. Chemical splash goggles are recommended. A full face

shield may also be necessary.

Other protective equipment : Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Remove and wash contaminated clothing before re-use. Handle in

accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Light amber liquid.Odour: Hydrocarbon odour.

Odour threshold : N/Av
pH : N/Av
Melting/Freezing point : N/Av
Initial boiling point and boiling range

: N/Av

Flash point : $>149^{\circ}\text{C} / >300^{\circ}\text{F}$

Flashpoint (Method) : Pensky Martens Closed Cup

Evaporation rate (BuAe = 1) : < 1Flammability (solid, gas) : N/Ap

Lower flammable limit (% by vol.)

N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None known.

Relative density / Specific gravity

: 0.915

Solubility in water : Negligible
Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av
Decomposition temperature : N/Av
Viscosity : N/Av
Volatiles (% by weight) : N/Av
Volatile organic Compounds (VOC's)

. N/

: N/Av

Absolute pressure of container

: N/Ap

Flame projection length : N/Ap

nonte

Other physical/chemical comments

: None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization will not occur. No dangerous reaction known under

conditions of normal use.

Conditions to avoid : Keep away from direct sunlight. Ensure adequate ventilation, especially in confined

areas. Avoid contact with incompatible materials.

Incompatible materials : Strong oxidizing agents. Reactive metals.

Hazardous decomposition products

None reported by the manufacturer. Refer also to hazardous combustion products,

Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

May cause drowsiness or dizziness. Causes central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowiness, slurred speech, nausea, and possible nervous system depression. Inhalation of mists or sprays may mildly irritate the upper respiratory tract and cause coughing or sneezing.

tion

Sign and symptoms ingestion

: May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Ingestion may cause symptoms similar to inhalation.

symptoms similar to

Sign and symptoms skin : Causes skin irritation. Symptoms may include redness, itching and swelling.

Sign and symptoms eyes : May cause eye irritation. Symptoms may include stinging and tearing.

Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin. Prolonged overexposure may cause slight liver and kidney effects, such as increased

organ weights.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity : This material is classified as hazardous under U.S. OSHA regulations (29CFR

1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products

Regulations) (WHMIS 2015).

Classification Carcinogenicity- Category 2 Suspected of causing cancer.

Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B)

and NTP (Group 2 - Reasonably anticipated).

Reproductive effects & Teratogenicity

: Not classifiable as a reproductive toxin.

Sensitization to material : Not expected to be a skin sensitizer.

Not expected to be a respiratory sensitizer.

Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system, blood

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Specific target organ toxicity - single exposure Category 3 May cause drowsiness and dizziness.

Not classified as a specific target organ toxicity-repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None reported by the manufacturer.

Toxicological data

: The calculated ATE values for this mixture are:

ATE oral = Not applicable. ATE dermal = 41667mg/kg

ATE inhalation (mists) = 285mg/L/4H

See below for individual ingredient acute toxicity data.

	LCso(4hr)	LD ₅₀			
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)		
Naphthalene	No information available.	490 mg/kg	>20,000 mg/kg		
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg		
Heavy aromatic solvent naphtha	> 17.1 mg/L/4 hours	> 6000 mg/kg	> 3160 mg/kg		
oleic acid	N/Av	>19200 mg/kg	>3000mg/kg guinea pig		
Distillates, petroleum, hydrotreated light	>5.2 mg/L (aerosol)	>5000 mg/kg	>2000 mg/kg		
Solvent naphtha (petroleum), medium aliphatic	21.4 mg/L	>5000 mg/kg	>2000 mg/kg		

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: No data is available on the product itself.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

			Toxicity to Fish				
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor			
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	0.12mg/L (40 days) (pink salmon)	None.			
1,2,4-Trimethylbenzene	95-63-6	7.72 mg/L (Fathead minnow)	N/Av	None.			
Heavy aromatic solvent naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.			
oleic acid	112-80-1	205mg/L Fathead minnow	N/Av	None.			
Distillates, petroleum, hydrotreated light	64742-47-8	N/Av	N/Av	N/Av			
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	2 - 5 mg/L (Rainbow trout)	0.098 mg/L/28-day QSAR NOEL	None.			

<u>Ingredients</u>	CAS No	Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor		
Naphthalene	91-20-3	3.4 mg/L/ (Water flea)	0.6mg/L	None.		
1,2,4-Trimethylbenzene	95-63-6	3.6 mg/L (Daphnia magna)	N/Av	None.		
Heavy aromatic solvent naphtha	64742-94-5	1.1 mg/L (Water flea)	N/Av	None.		
oleic acid	112-80-1	N/Av	N/Av	N/Av		
Distillates, petroleum, hydrotreated light	64742-47-8	N/Av	N/Av	N/Av		
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1.4 mg/L (Water flea)	0.48 mg/L QSAR NOEL (Water flea)	None.		

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Naphthalene	91-20-3	0.4mg/L/72hr (Marine diatom)	N/Av	None.		
1,2,4-Trimethylbenzene	95-63-6	2.356mg/L QSAR	N/Av	None.		
Heavy aromatic solvent naphtha	64742-94-5	7.2 mg/L/72 hours (Green algae)	0.22 mg/L/72 hours (Green algae)	None.		
oleic acid	112-80-1	N/Av	N/Av	N/Av		
Distillates, petroleum, hydrotreated light	64742-47-8	N/Av	N/Av	N/Av		
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1 - 3 mg/L/72hr (Green algae)	1 mg/L/72hr (Green algae) NOEL	None.		

Persistence and degradability

: No data is available on the product itself.

The following ingredients are considered to be readily biodegradable: Solvent Naphtha (Petroleum) Medium Aliphatic

Bioaccumulation potential

: No data is available on the product itself.

See the following data for ingredient information.

<u>Components</u>	Partition coefficent n-octanol/ater (log Kow)	Bioconcentration factor (BCF)
laphthalene (CAS 91-20-3)	3.7	30 - 430 species: fish
1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78	31 - 275
Heavy aromatic solvent naphtha (CAS 64742-94-5)	2.9 - 6.1	No information available.
oleic acid (CAS 112-80-1)	7.64	10
Distillates, petroleum, hydrotreated light (CAS 64742-47-8)	5.1 - 8.8	No information available.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	N/Av	No information available.

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

: The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

- : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
- **Methods of Disposal**
- : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION Transport Regulatory Packing hazard Label **UN Number** UN proper shipping name Information Group class(es) 49CFR/DOT not regulated None Not regulated. none 49CFR/DOT This product meets the criteria for an environmentally hazardous material according to the IMDG Code. Additional information TDG None Not regulated. not regulated none TDG This product meets the criteria for an environmentally hazardous material according to the IMDG Code. Additional information

Special precautions for user

: Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards

: This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

la sura dia nda	040#	TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
<u>Ingredients</u>	CAS#	Inventory	Quantity(RQ) (40 CFR 117.302):	Hazardous Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration	
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	N/Ap	Yes	0.1%	
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	1%	
Heavy aromatic solvent naphtha	64742-94-5	Yes	N/Ap	N/Ap	No	N/Ap	
oleic acid	112-80-1	Yes	N/Ap	N/Ap	No	N/Ap	
Distillates, petroleum, hydrotreated light	64742-47-8	Yes	N/Ap	N/Ap	No	N/Ap	
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Yes	N/Ap	N/Ap	No	N/Ap	

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS#	Cas #		State "Right to Know" Lists					
ingredients	CAS#	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Naphthalene	91-20-3	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
Heavy aromatic solvent naphtha	64742-94-5	No	Not listed	No	No	No	No	No	No
oleic acid	112-80-1	No	Not listed	No	No	No	No	Yes	Yes
Distillates, petroleum, hydrotreated light	64742-47-8	No	Not listed	No	No	No	No	No	No
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	No	Not listed	No	No	No	Yes	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

Ingredients	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
Heavy aromatic solvent naphtha	64742-94-5	265-198-5	Present	Present	(3)-7	KE-31656	Present	May be used as a single component chemical under an appropriate group standard
oleic acid	112-80-1	204-007-1	Present	Present	(2)-975; (2)-609	KE-26450	Present	HSR003153
Distillates, petroleum, hydrotreated light	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	May be used as a single component chemical under an appropriate group standard
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	265-191-7	Present	Present	(9)-1700	KE-31664	Present	May be used as a single component chemical under an appropriate group standard

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

ATE: Acute Toxicity Estimate

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations CNS: Central Nervous System CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%.

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances

EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

IMDG: International Maritime Dangerous Goods KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration LD: Lethal Dose MA: Massachusetts

MN: Minnesota

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

NJ: New Jersey

NOEC: No observable effect concentration

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References Canadian Centre for Occupational Health and Safety (CCOHS), CCInfoWeb

databases, 2015 (CHEMINFO, HSDB and RTECS).

OECD- The Global Portal to Information on Chemical Substances - eChemPortal,

2015

European Chemicals Agency, Classification Legislation, 2015

Material Safety Data Sheet from manufacturer

Information taken from reference works and the literature.

Preparation Date (mm/dd/yyyy)

: 06/02/2015

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

FPPF Chemical Company, Inc. 117 West Tupper Street Buffalo, NY, USA 14201 Telephone: 1-800-735-3773

Please direct all enquiries to FPPF Chemical Company

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

END OF DOCUMENT