

## **Safety Data Sheet**

### **FLOOR TILE MORTAR GRAY**

Safety Data Sheet dated: 5/19/2016 - version 2

Date of first edition: 6/2/2015

### 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: FLOOR TILE MORTAR GRAY

Recommended use of the chemical and restrictions on use

Recommended use: Mortar Restrictions on use: N.A.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

## **Emergency 24 hour numbers:**

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-613-996-6666

# 2. HAZARD(S) IDENTIFICATION







## Classification of the chemical

Skin Corr. 1A Causes severe skin burns and eye damage.

Eve Dam. 1 Causes serious eye damage. Skin Sens. 1 May cause an allergic skin reaction. Carc. 1A May cause cancer if inhaled. STOT SE 3 May cause respiratory irritation.

Description

STOT RE 1 Causes damage to organs through prolonged or repeated exposure if inhaled.

### **Label elements**

## Symbols:



P301+P330+P331

# Danger

Code

H314

	, ,
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350.A	May cause cancer if inhaled.
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled
Code	Description
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260.B	Do not breathe dust.
P264.2	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

Causes severe skin burns and eye damage.

Date 5/19/2016 **Production Name** FLOOR TILE MORTAR GRAY Page n. 1 of P302+P352.A IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310.B Immediately call a doctor.

P314 Get medical advice/attention if you feel unwell.

P321.A Specific treatment (see supplementary instructions on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501.A Dispose of contents/container in accordance with applicable regulations.

### Ingredient(s) with unknown acute toxicity:

None

### Hazards not otherwise classified identified during the classification process:

None

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Substances**

N.A.

# Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

#### List of components

Quantity	Name	Ident. Numb.	Classification
50-75 %	Silica Sand	CAS:14808-60-7	Carc. 1A, H350; STOT RE 1, H372
10-25 %	Portland cement	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314

## 4. FIRST AID MEASURES

### **Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

## Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### 5. FIRE-FIGHTING MEASURES

### **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

# Unsuitable extinguishing media:

None in particular.

# Specific hazards arising from the chemical

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 2 of 8

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

### **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

#### 7. HANDLING AND STORAGE

### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# Conditions for safe storage, including any incompatibilities

Storage temperature: N.A.

Always keep in a well ventilated place.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

### List of components with OEL value

Component	OEL Type Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term	Behaviour	Note
Silica Sand	ACGIH		0,025					A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
Portland cement	OSHA		15					
	OSHA		5					
	ACGIH		1					A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;

Appropriate engineering controls: N.A.

# Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 3 of 8

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: Powder grey

Odour: Cement like Odour threshold: N.A.

pH in Water Dispersion: 11.50

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: Not Applicable Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 2.15 g/cm3
Solubility in water: Dispersible

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A. Oxidizing properties: N.A. Solid/gas flammability: N.A.

#### Other information

Substance groups relevant properties: N.A.

Miscibility: N.A. Fat Solubility: N.A. Conductivity: N.A.

### 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

## **Chemical stability**

Data not Available.

### Possibility of hazardous reactions

None.

### Conditions to avoid

Stable under normal conditions.

### **Incompatible materials**

None in particular.

## **Hazardous decomposition products**

None.

## 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

## Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

### Toxicological information on main components of the mixture:

Silica Sand a) acute toxicity LD50 Oral Rat = 500mg/kg

## If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 4 of 8

- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

#### Substance(s) listed on the IARC Monographs:

Silica Sand Group 1

#### Substance(s) listed as OSHA Carcinogen(s):

Silica Sand

#### Substance(s) listed as NIOSH Carcinogen(s):

Silica Sand

#### Substance(s) listed on the NTP report on Carcinogens:

Silica Sand

#### 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of components with eco-toxicological properties

Quantity Component Ident. Numb. Ecotox Infos

50-75 % Silica Sand CAS: 14808-60-7 LC50 a) Aquatic acute toxicity carp> 10000,0000mg/L 72h

#### Persistence and degradability

N.A.

#### **Bioaccumulative potential**

N.A.

### Mobility in soil

N.A.

## Other adverse effects

N.A.

### 13. DISPOSAL CONSIDERATIONS

## **Waste treatment methods**

Any disposal practice must be in compliance with local, state and federal laws and regulations (contact local or state environmental agency for specific rules). Do not dump into sewers, any body of water or onto the ground.

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

# 14. TRANSPORT INFORMATION

## **UN** number

ADR-UN number: N/A
DOT-UN Number: N/A
IATA-Un number: N/A
IMDG-Un number: N/A

## **UN** proper shipping name

ADR-Shipping Name: N/A
DOT-Proper Shipping Name: N/A
IATA-Technical name: N/A
IMDG-Technical name: N/A

## Transport hazard class(es)

ADR-Class: N/A
DOT-Hazard Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

## **Packing group**

ADR-Packing Group: N/A DOT-Packing group: N/A IATA-Packing group: N/A

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 5 of 8

IMDG-Packing group: N/A

### **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: N.A.

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

### **Special precautions**

Department of Transportation (DOT):

DOT-Special Provision(s): N/A

DOT-Label(s): N/A
DOT-Symbol: N/A
DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A DOT-Bulk: N/A

DOT-Non-Bulk: N/A Road and Rail (ADR-RID):

ADR-Label: N/A

ADR-Hazard identification number: N/A ADR-Tunnel Restriction Code: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A
IATA-Subrisk: N/A
IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A

IMDG-Subrisk: N/A

IMDG-Special Provisions: N/A

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: N/A IMDG-MFAG: N/A

# 15. REGULATORY INFORMATION

# **USA - Federal regulations**

### **TSCA - Toxic Substances Control Act**

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Silica Sand is listed in TSCA Section 8b

Portland cement is listed in TSCA Section 8b

## **SARA - Superfund Amendments and Reauthorization Act**

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

no substances listed

Section 313 - Toxic chemical list:

no substances listed

# **CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act**

Substance(s) listed under CERCLA:

no substances listed

## **CAA - Clean Air Act**

### **CAA listed substances:**

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 6 of 8

#### **CWA - Clean Water Act**

#### CWA listed substances:

no substances listed

# **USA - State specific regulations**

## **California Proposition 65**

Substance(s) listed under California Proposition 65:

Silica Sand Listed as carcinogen

## Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Silica Sand

Portland cement

## Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Silica Sand

Portland cement

### **New Jersey Right to know**

Substance(s) listed under New Jersey Right to know:

Silica Sand

Portland cement

## **Canada- Federal regulations**

## **DSL - Domestic Substances List**

DSL Inventory:

All the substances are listed in the DSL.

### **NDSL - Non Domestic Substances List**

NDSL Inventory:

no substances listed

## **NPRI - National Pollutant Release Inventory**

Substances listed in NPRI:

no substances listed

## **16. OTHER INFORMATION**

**Additional classification information** 

Description

Code

H314	Causes severe skin burns and eye damage.				
H317	May cause an allergic skin reaction.				
H318	Causes serious eye damage.				
H335	May cause respiratory irritation.				
H350	May cause cancer .				
H350.A	May cause cancer if inhaled.				
H372	Causes damage to organs through prolonged or repeated exposure .				
H372.A	Causes damage to organs through prolonged or repeated exposure if inhaled.				
Safety Data Sheet dated: 5/19/2016 - version 2					
Product	Product code: 1105				

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 7 of 8



HMIS Health: 2 = Moderate

HMIS Health - Is health hazard chronic?: Yes HMIS Flammability: 0 = Not Combustible

HMIS Reactivity: 0 = Minimal

HMIS P.P.E.: Safety glasses, gloves, dust respirator

NFPA Health: 2 = Moderate

NFPA Flammability: 0 = Not Combustible

NFPA Reactivity: 0 = Minimal NFPA Special Risk: NONE

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

## Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.

WGK: German Water Hazard Class.

KSt: Explosion coefficient.

# Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Date 5/19/2016 Production Name FLOOR TILE MORTAR GRAY Page n. 8 of 8