



E K Industries, Inc.

1403 Herkimer Street
Joliet, IL 60432-1059
(815) 723-4000
www.eki-chem.com

MATERIAL SAFETY DATA SHEET

PRODUCT QUIK-DIP STAIN-Solution 1

PRODUCT CODES MER-QD1

REVISION DATE 09/30/2009

Page 1 of 4

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME QUIK-DIP STAIN-Solution 1

PRODUCT CODES MER-QD1

SYNONYMS N/I

CAS NUMBER Does not apply.

FORMULA Does not apply.

FORMULA WEIGHT Does not apply.

REVISION DATE 09/30/2009

24 HOUR EMERGENCY TELEPHONE

CALL CHEMTREC (800) 424-9300

Contact CHEMTREC (Chemical Transportation Emergency Center) only in the event of emergencies involving a chemical spill, leak, fire, exposure or other accident.

SECTION 2 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH THE SKIN. CAUSES IRRITATION. AFFECTS CNS AND LIVER.

PRECAUTIONARY MEASURES

Keep away from heat, sparks and flame. Avoid contact with skin, eyes and clothing. Avoid breathing vapor. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

ROUTES OF ENTRY AND EFFECTS OF OVEREXPOSURE

SKIN CONTACT Causes irritation and defatting of skin.

EYE CONTACT Causes irritation.

IF INHALED Causes irritation. May cause headache, drowsiness, nausea, vomiting, blurred vision, blindness, coma, and death.

IF SWALLOWED Intoxicant. Symptoms similar to inhalation.

CHRONIC Skin irritation, vision loss.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE Skin and eye disorders, impaired liver and kidney function.

TARGET ORGANS Liver, kidneys.



E K Industries, Inc.

1403 Herkimer Street
Joliet, IL 60432-1059
(815) 723-4000
www.eki-chem.com

MATERIAL SAFETY DATA SHEET

PRODUCT QUIK-DIP STAIN-Solution 1

PRODUCT CODES MER-QD1

REVISION DATE 09/30/2009

Page 2 of 4

CARCINOGENICITY Not listed by NTP, IARC, or OSHA.

SECTION 3 FIRST AID PROCEDURES

SKIN CONTACT Immediately flush with plenty of water for at least 15 minutes while removing contaminated garments. Get medical attention for persistent irritation.

EYE CONTACT Immediately flush with plenty of water for at least 15 minutes, separating eyelids occasionally. Get immediate medical attention.

IF INHALED Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

IF SWALLOWED If conscious, induce vomiting immediately as directed by medical personnel.

SECTION 4 FIRE FIGHTING MEASURES

FLASH POINT (C) 12

EXPLOSIVE LIMITS (%) **UPPER** 36 **LOWER** 6

AUTOIGNITION TEMPERATURE (C) 464

NFPA HAZARD IDENTIFICATION Health: 1 Flammability: 3 Reactivity: 0 Special Hazards: -

NFPA HAZARD IDENTIFICATION is *not* intended to address occupational exposure occurring under normal conditions of use. It only addresses hazards presented by Fire, Spill or Similar Emergencies. NFPA 704 2007 ed. 1.1 and 1.3.2(1).

EXTINGUISHING MEDIA "Alcohol foam," dry chemical, CO₂

SPECIAL FIRE FIGHTING PRODECURES Fire fighters should wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS Vapors may spread long distances and ignite.

SECTION 5 ACCIDENTIAL RELEASE MEASURES

IF SPILLED Eliminate sources of ignition. Absorb spill with inert material, scoop up and containerize for disposal.



E K Industries, Inc.

1403 Herkimer Street
Joliet, IL 60432-1059
(815) 723-4000
www.eki-chem.com

MATERIAL SAFETY DATA SHEET

PRODUCT QUIK-DIP STAIN-Solution 1

PRODUCT CODES MER-QD1

REVISION DATE 09/30/2009

Page 3 of 4

WASTE DISPOSAL METHOD Dispose in accordance with all local, state and federal environmental regulations.

SECTION 6 EXPOSURE CONTROL AND STORAGE

VENTILATION Local preferred.

RESPIRATORY PROTECTION If necessary, APPROVED Organic Vapor respirator.

EYE PROTECTION Chemical splash safety goggles and/or chemical splash face shield.

SKIN PROTECTION Nitrile gloves, lab coat and impervious apron.

STORAGE Store tightly closed in an approved FLAMMABLE LIQUIDS storage area.

SECTION 7 HAZARDOUS COMPONENTS AND EXPOSURE LIMITS

COMPONENT	CAS NUMBER	OSHA PEL	ACGIH TLV
Methyl Alcohol	67-56-1	200 ppm TWA	200 ppm TWA Skin 250 ppm STEL Skin

Methyl Alcohol may be subject to the reporting requirements of SARA313 and 40CFR372.

SECTION 8 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR	Green liquid with characteristic Methyl Alcohol Odor.	BOILING POINT (C)	64.5
		EVAPORATION RATE	5.9 Butyl Acetate=1
SOLUBILITY IN WATER	Miscible	VAPOR PRESSURE (mm Hg)	97@20C
DENSITY / SPECIFIC GRAVITY	SG 0.8	VAPOR DENSITY	1.1 Air=1
MELTING POINT (C)	-98		



E K Industries, Inc.

1403 Herkimer Street
Joliet, IL 60432-1059
(815) 723-4000
www.eki-chem.com

MATERIAL SAFETY DATA SHEET

PRODUCT QUIK-DIP STAIN-Solution 1

PRODUCT CODES MER-QD1

REVISION DATE 09/30/2009

Page 4 of 4

SECTION 9 STABILITY AND REACTIVITY

STABILITY Stable

CONDITIONS TO AVOID Excessive heat, sources of ignition

MATERIALS TO AVOID Strong oxidizers, aluminum

HAZARDOUS DECOMPOSITION PRODUCTS CO, CO₂, Formaldehyde

HAZARDOUS POLYMERIZATION Will not occur

DISCLAIMER:

E K Industries, Inc. makes no representation as to the comprehensiveness or accuracy of this information. Individuals using this information, or the product to which it refers, must exercise their independent judgment in determining all appropriateness for a particular purpose. Accordingly, E K Industries, Inc. will not be responsible for damages of any kind or nature resulting from the use of this information or the corresponding product. No representations or warranties of any kind or nature, including but not limited to: express warranties, implied warranties or merchantability, or warranties of fitness for a particular purpose, are made hereunder with respect to the information set forth herein or to the product to which the information refers.