

Prepared according to U.S. OSHA, CMA, ANSI, Canadian WHMIS regulations

CeramAlloy CL+AC Base

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CeramAlloy CL+AC Base

CHEMICAL FAMILY NAME: Mixture U.N. NUMBER: UN3082

U.N. DANGEROUS GOODS CLASS: Environmentally Hazardous Substances, Liquid, n.o.s (Diglycidyl Ether

Bisphenol A Polymer), Class 9, PG III

SUPPLIER/MANUFACTURER'S NAME: ENECON Corporation

ADDRESS: 6 Platinum Court, Medford, New York 11763-2251

EMERGENCY PHONE: 800-255-3924 (U.S.A.) 813-248-0585 (International)

BUSINESS PHONE: 516-349-0022 BUSINESS FAX: 516-349-5522 DATE OF CURRENT REVISION: August 4, 2015

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a colored viscous liquid with no odor. Exposure to this product can be irritating to eyes, respiratory system and skin. It is a non-flammable liquid with a flash point >250°C. The Environmental effects of this product have not been investigated, however it may cause adverse effects.

US DOT SYMBOLS



GHS HAZARD SYMBOLS



NFPA RATING SYSTEM



Signal Word: Warning!

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200

COMPONENTS DETERMINING HAZARDS:

Epoxy Phenol Novolac Resin, Bisphenol A Diglycidyl Ether Polymer

GHS HAZARD CLASSIFICATION(S):

Skin Sensitizer Category 1 Aquatic Chronic Category 2 Skin Irritant Category 2 Eye Irritant Category 2

HAZARD STATEMENTS:

Causes skin irritation

Causes serious eye irritation

Hazardous to the aquatic environment, long-term hazard

May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS:

Wash hands thoroughly after handling.

Wear protective gloves.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE:

INHALATION: Inhalation of vapors from heated materials may cause irritation to respiratory tract

EYE CONTACT: Direct contact may cause irritation with pain, burning and tearing.

SKIN CONTACT: Prolonged or repeated contact may cause skin irritation or dermatitis. May also cause skin sensitization.

INGESTION: Not a normal route of entry in normal application, however Ingestion of this product will cause gastrointestinal irritation.

CHRONIC: Prolonged or repeated exposure may cause dermatitis to the skin.

TARGET ORGANS: ACUTE: Eye, Skin CHRONIC: Skin

CeramAlloy CL+AC Base

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS#	EINECS#	ICSC#	WT %	HAZARD CLASSIFICATION; RISK PHRASES
Ceramic Microspheres	66402-68-4	266-340-9	Not Listed	30 – 40%	NOT CLASSIFIED
Bisphenol A Diglycidyl Ether Polymer	25068-38-6	500-033-5	Not Listed	25 – 35%	Skin Irritant 2, Eye Irritant 2, Skin Sensitizer 1, Aquatic Chronic 2
Aluminum Oxide	1344-28-1	215-691-6	0351	10 – 20%	NOT CLASSIFIED
Wolastonite	13983-17-0	237-772-5	Not Listed	5 – 15%	NOT CLASSIFIED
Epoxy Phenol Novolac Resin	28064-14-4	Not Listed in ESIS	Not Listed	1 - 8%	Skin Irritant 2, Eye Irritant 2, Skin Sensitizer 1, Aquatic Chronic 2
Titanium Dioxide	13463-67-7	236-675-5	0338	1 – 3%	NOT CLASSIFIED
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

Each of the other components present are less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens.

SECTION 4 - FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, or eye problems may be aggravated by prolonged contact.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

FLASH POINT: >250°C **FLAMMABILITY CLASS:** 111B

AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): NA Upper (UEL): NA

FIRE EXTINGUISHING MATERIALS: As appropriate for surrounding fire. Carbon dioxide, foam, dry chemical, halon, or

water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion products may be toxic.

<u>Explosion Sensitivity to Mechanical Impact</u>: Not Sensitive. <u>Explosion Sensitivity to Static Discharge</u>: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear

Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other

environmentally sensitive areas.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with an absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing dusts generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Containers of this product must be properly labeled. Store containers in a cool, dry location. Keep container tightly closed when not in use. Store away from strong acids or oxidizers.

CeramAlloy CL+AC Base

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Ceramic Microspheres	66402-68-4	Not Listed	Not Listed
Bisphenol A Diglycidyl Ether Polymer	25068-38-6	Not Listed	Not Listed
Aluminum Oxide	1344-28-1	10 mg/m³	15 mg/m³
Wolastonite	13983-17-0	10 mg/m³	15 mg/m³
Epoxy Phenol Novolac Resin	28064-14-4	Not Listed	Not Listed
Titanium Dioxide	13463-67-7	10 mg/m³	15 mg/m³

Currently, International exposure limits are not established for all the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

EYE PROTECTION: Safety glasses or chemical goggles where splashing is possible. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

SKIN PROTECTION: Use chemical resistant gloves to prevent skin contact. Use body protection appropriate to prevent skin contact (e.g. lab coat, overalls).If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid APPEARANCE & ODOR: Colored viscous liquid with no odor. None **ODOR THRESHOLD (PPM):** VAPOR PRESSURE (mmHq): Not Available VAPOR DENSITY (AIR=1): Not Available Not Available BY WEIGHT: **EVAPORATION RATE (nBuAc = 1):** Not Available **BOILING POINT (C°):** >200°C FREEZING POINT (C°): Not Available Not Available pH: SPECIFIC GRAVITY 20°C: (WATER =1) 1.78 **SOLUBILITY IN WATER (%)** Non-Soluble PRODUCT VOC: 10 g/L

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: When heated to decomposition this product may form formaldehyde, carbon dioxide, carbon monoxide and phenolic materials as products of incomplete combustion.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong acids and strong oxidizing agents. Uncontrolled reactions with amines and bases.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contact with incompatible materials.

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA: No Data available at this time.

SUSPECTED CANCER AGENT: One or more of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is considered to be, or suspected to be a cancer-causing agent by these agencies.

Titanium Dioxide CAS# 13463-67-7 IARC Group 2B (possible carcinogen to humans)

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin, eyes and respiratory system.

SENSITIZATION OF PRODUCT: This product is considered a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No information concerning the effects of this product and its components on the human reproductive system.

SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: No Data available at this time.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: No evidence is currently available on this product's effects on plants or animals, however release of this product may have long term adverse effects to the environment.

August 2015 Page 3 of 9

CeramAlloy CL+AC Base

EFFECT OF CHEMICAL ON AQUATIC LIFE: No evidence is currently available on this product's effects on aquatic life, however release of this product may have long term adverse effects to the environment.

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Environmentally Hazardous Substances, Liquid, n.o.s (Diglycidyl Ether Bisphenol A Polymer)

HAZARD CLASS NUMBER and DESCRIPTION: Class 9, Environmentally Hazardous Substance

UN IDENTIFICATION NUMBER: UN3082

PACKING GROUP: PGIII

DOT LABEL(S) REQUIRED: Class 9, Environmentally Hazardous Substance

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): 171

MARINE POLLUTANT: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is classified as Dangerous Goods by the International Maritime Organization.

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: No Reactivity: No

<u>U.S. SARA THRESHOLD PLANNING QUANTITY:</u> There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains ingredients that are on the California Proposition 65 lists. Titanium Dioxide- CAS# 13463-67-7

WARNING! This product contains ingredients that are known to the State of California to cause cancer.

CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This is considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and is therefore subject to the labeling and MSDS requirements of the Workplace Hazardous Materials Information System (WHMIS).Class D Division 2B

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:

Australian Inventory of Chemical Substances (AICS):

Korean Existing Chemicals List (ECL):

Japanese Existing National Inventory of Chemical Substances (ENCS):

Listed or Exempt

Listed or Exempt

Philippines Inventory if Chemicals and Chemical Substances (PICCS):

Listed or Exempt

Swiss Giftliste List of Toxic Substances:

Listed or Exempt

U.S. TSCA:

Listed or Exempt

SECTION 16 - OTHER INFORMATION

PREPARED BY: Chris Eigbrett MSDS to GHS Compliance

Disclaimer: To the best of ENECON Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type either express or implied are provided. The information contained herein relates only to this specific product.

August 2015 Page 4 of 9

Prepared according to U.S. OSHA, CMA, ANSI, Canadian WHMIS regulations CeramAlloy CL+AC Activator

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CeramAlloy CL+AC Activator

CHEMICAL FAMILY NAME: Mixture U.N. NUMBER: UN1760

U.N. DANGEROUS GOODS CLASS: Corrosive Liquid, n.o.s. (Contains polyoxyalkyleneamine, Isophoronediamine

and Aminoethylpiperazine), Class 8, PG III

SUPPLIER/MANUFACTURER'S NAME: ENECON Corporation

ADDRESS: 6 Platinum Court, Medford, New York 11763-2251

EMERGENCY PHONE: 800-255-3924 (U.S.A.) 813-248-0585 (International)

BUSINESS PHONE: 516-349-0022
BUSINESS FAX: 516-349-5522
DATE OF CURRENT REVISION: August 4, 2015

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is an amber colored liquid with an ammonia odor. Corrosive: may cause severe eye damage. Vapors may be irritating to eyes. May be toxic if absorbed through skin. Inhalation of vapors can be irritating to the respiratory tract. It is a non-flammable liquid with a flash point >95°C. The Environmental effects of this product have not been investigated, however this product may cause significant adverse effects.

US DOT SYMBOLS

GHS HAZARD SYMBOLS


NFPA RATING SYSTEM











Signal Word: Warning!

This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200

COMPONENTS DETERMINING HAZARDS:

Benzyl Alcohol, Isophoronediamine, Polyoxyalkylenamine, Nonylphenol, Aminoethyl Piperazine, Methylenebiscyclohexanamine GHS HAZARD CLASSIFICATION(S):

Acute Toxicity Category 4 (Oral)

Acute Toxicity Category 4 (Inhalation)

Acute Toxicity Category 4 (Dermal)

Skin Corrosion Category 1

Skin Sensitization Category 1

Aquatic Chronic Category 2

Aquatic Acute Category 2

Reproductive Toxicity Category 2

HAZARD STATEMENTS:

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Harmful if swallowed

Harmful if inhaled

Harmful in contact with skin

Suspected of damaging fertility or the unborn child

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Contaminated work clothing should not be allowed out of the workplace.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE:

INHALATION: Inhalation of mists or vapors from heated materials may cause irritation to respiratory tract **EYE CONTACT:** Corrosive to the eye and may cause severe damage. Vapors may be irritating to eyes. **SKIN CONTACT:** May be toxic if absorbed through skin. Sensitization may occur. Corrosive to the skin.

INGESTION: Not a normal route of entry in normal application, however ingestion of this product will cause burns to mouth and throat.

August 2015 Page 5 of 9

CeramAlloy CL+AC Activator

CHRONIC: Prolonged or repeated exposure may cause dermatitis to the skin.

TARGET ORGANS: ACUTE: Eye, Skin CHRONIC: Skin

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS#	EINECS#	ICSC#	WT %	HAZARD CLASSIFICATION; RISK PHRASES
Benzyl Alcohol	100-51-6	202-859-9	0833	10 – 25%	Acute Toxicity 4 (Oral, Inhalation)
Isophoronediamine	2855-13-2	220-666-8	0498	10 - 25%	Acute Toxicity 4 (Oral, Dermal), Skin Corrosive 1B, Skin Sensitizer 1, Aquatic Chronic 3
Epoxy-Amine Adduct	Not Available	Not Listed in ESIS	Not Listed	10 – 25%	NOT CLASSIFIED
Nonylphenol	84852-15-3	284-325-5	Not Listed	5 – 20%	Acute Toxicity 4 (Oral), Skin Corrosive 1B, Reproductive Toxicity 2, Aquatic Acute 1, Aquatic Chronic 1
Polyoxyalkylenamine	9046-10-0	Not Listed in ESIS	Not Listed	5 – 15%	Skin Corrosive 1B
Aminoethyl Piperazine	140-31-8	205-411-0	Not Listed	1 – 10%	Acute Toxicity 4 (Oral, Dermal), Skin Corrosive 1B, Skin Sensitizer 1, Aquatic Chronic 3
Nonylphenol	25154-52-3	246-672-0	0309	1 – 10%	Acute Toxicity 4 (Oral), Skin Corrosive 1B, Reproductive Toxicity 2, Aquatic Acute 1, Aquatic Chronic 1
Methylenebiscyclohexanamine	1761-71-3	217-168-8	Not Listed	1 – 3%	Acute Toxicity 4 (Oral), Skin Corrosive 1B, Skin Sensitizer 1, Aquatic Chronic 3

Each of the other components present are less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens.

SECTION 4 - FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, or eye problems may be aggravated by prolonged contact.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

FLASH POINT: >95°C **FLAMMABILITY CLASS:** 111B

AUTOIGNITION TEMPERATURE: Not Established

FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): NA Upper (UEL): NA

FIRE EXTINGUISHING MATERIALS: As appropriate for surrounding fire. Carbon dioxide, foam, dry chemical, halon, or water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Oxides of nitrogen and nitrogen containing organic compounds may be formed during

combustion. Combustion products may be toxic.

Explosion Sensitivity to Mechanical Impact:

Not Sensitive.

Not Sensitive.

Not Sensitive.

<u>Explosion Sensitivity to Static Discharge</u>: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-

Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering

storm drains, bodies of water, or other environmentally sensitive areas.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with an absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

August 2015 Page 6 of 9

CeramAlloy CL+AC Activator

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing dusts generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Containers of this product must be properly labeled. Store containers in a cool, dry location. Keep container tightly closed when not in use. Store away from strong acids or oxidizers and reactive materials.

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA
Benzyl Alcohol	100-51-6	Not Listed	Not Listed
Isophoronediamine	2855-13-2	Not Listed	Not Listed
Epoxy-Amine Adduct	Not Available	Not Listed	Not Listed
Nonylphenol	84852-15-3	Not Listed	Not Listed
Polyoxyalkylenamine	9046-10-0	Not Listed	Not Listed
Aminoethyl Piperazine	140-31-8	Not Listed	Not Listed
Nonylphenol	25154-52-3	Not Listed	Not Listed
Methylenebiscyclohexanamine	1761-71-3	Not Listed	Not Listed

Currently, International exposure limits are not established for all the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapors. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93.

EYE PROTECTION: Safety glasses or chemical goggles where splashing is possible. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

SKIN PROTECTION: Use chemical resistant gloves to prevent skin contact. Use body protection appropriate to prevent skin contact (e.g. lab coat, overalls). If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

APPEARANCE & ODOR: Amber colored liquid with an ammonia odor.

ODOR THRESHOLD (PPM): None Not Available VAPOR PRESSURE (mmHq): VAPOR DENSITY (AIR=1): Not Available Not Available BY WEIGHT: **EVAPORATION RATE (nBuAc = 1):** Not Available >200°C **BOILING POINT (C°):** FREEZING POINT (C°): Not Available Not Available SPECIFIC GRAVITY 20°C: (WATER =1) 0.98**SOLUBILITY IN WATER (%)** Non-Soluble PRODUCT VOC: 10 g/L

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: When heated to decomposition this product may form carbon dioxide, carbon monoxide, oxides of nitrogen and unidentified organic compounds.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong acids and strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contact with incompatible materials.

August 2015 Page 7 of 9

CeramAlloy CL+AC Activator

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA: Toxicity data is available for the following components:

CAS# 9046-10-0 Oral LD50 400 - 2000 mg/kg Rat CAS# 25154-52-3 Oral LD50 1300 mg/kg Rat CAS# 140-31-8 Oral LD50 >1620 mg/kg Rat

SUSPECTED CANCER AGENT: None of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin, eyes and respiratory system.

SENSITIZATION OF PRODUCT: This product is considered a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No information concerning the effects of this product and its components on the human reproductive system.

SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: No Data available at this time.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: No evidence is currently available on this product's effects on plants or animals, however release of this product may cause significant adverse effects.

EFFECT OF CHEMICAL ON AQUATIC LIFE: No evidence is currently available on this product's effects on aquatic life, however release of this product may cause significant adverse effects.

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Corrosive Liquid, n.o.s. (Contains polyoxyalkyleneamine, Isophoronediamine and Aminoethylpiperazine)

HAZARD CLASS NUMBER and DESCRIPTION: Class 8 Corrosive

UN IDENTIFICATION NUMBER: UN1760

PACKING GROUP: PGIII

DOT LABEL(S) REQUIRED: Corrosive

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): 154

MARINE POLLUTANT: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is classified as Dangerous Goods by the International Maritime Organization.

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: No Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): None of the ingredients are on the California Proposition 65 lists.

CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This is considered to be a hazardous material under the Hazardous Products Act Class D Division 2 and Class E, as defined by the Controlled Products Regulations and is therefore subject to the labeling and MSDS requirements of the Workplace Hazardous Materials Information System (WHMIS).

August 2015 Page 8 of 9

CeramAlloy CL+AC Activator

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:

Australian Inventory of Chemical Substances (AICS):

Korean Existing Chemicals List (ECL):

Japanese Existing National Inventory of Chemical Substances (ENCS):

Listed or Exempt Listed or Exempt Philippines Inventory if Chemicals and Chemical Substances (PICCS):

Listed or Exempt Listed or Exempt Listed or Exempt

Swiss Giftliste List of Toxic Substances:

U.S. TSCA:

Listed or Exempt
Listed

SECTION 16 - OTHER INFORMATION

PREPARED BY: Chris Eigbrett MSDS to GHS Compliance

Disclaimer: To the best of ENECON Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type either express or implied are provided. The information contained herein relates only to this specific product.

August 2015 Page 9 of 9